

# SCIENTIFIC AMERICAN

[Entered at the Post Office of New York, N. Y., as Second Class Matter. Copyright, 1907, by Munn & Co.]

Vol. XXVII.—No. 19.  
ESTABLISHED 1845.

NEW YORK, NOVEMBER 9, 1907.

[10 CENTS A COPY  
\$3.00 A YEAR.]




**The 18-Horse-Power White Steam Army Ambulance.**

The photograph was taken while the machine was making a 300-mile trip from Washington, D. C., to Gretna, Pa., loaded with a ton of medical supplies. An average speed of about 17 miles per hour was maintained.



**"When Greek Meets Greek." A Scene in the Middle West.**

A "Peerless Six" is shown encountering a steam traction engine as it emerges from a field drawing a threshing machine. The steam traction engine was the forerunner of the automobile in both England and America and many of these machines are used throughout the West to-day.



**The Wysong Gasoline Autotractor, Which is Superseding the Steam Traction Engine in the West.**

This machine is equipped with a 4-cylinder, 2-cycle scavenging engine of a novel type. On account of the light weight of the tractor it can be used on soft ground where it would be impossible for the heavier steam tractor to go.



**A "Rapid" Gasoline Motor Ambulance.**

This type chassis has a double-ported cylinder motor of 24 horse-power, direct-connected to a two-speed planetary gear transmission which drives a countershaft by a chain. The final drive is by double side chains to the rear wheels.



**Scene on Fifth Avenue at Forty-Second Street Since the New Automobile 'Buses Have Come Into Use.**

These 'buses were built in America and mounted upon imported chassis of the De Dion type, fitted with 24-horse-power 4-cylinder motors. Despite the double rate of fare the new omnibuses are generally crowded.

NOVEL TYPES OF UTILITY MOTOR VEHICLES

## SCIENTIFIC AMERICAN

ESTABLISHED 1845

MUNN &amp; CO. - Editors and Proprietors

Published Weekly at

No. 361 Broadway, New York

CHARLES ALLEN MUNN, President

361 Broadway, New York

FREDERICK CONVERSE BEACH, Sec'y and Treas.

361 Broadway, New York

## TERMS TO SUBSCRIBERS

One copy, one year for the United States or Mexico, \$3.00  
 One copy, one year, for Canada, 3.75  
 One copy, one year, to all foreign countries, postage prepaid, 4.50

## THE SCIENTIFIC AMERICAN PUBLICATIONS

Scientific American (Established 1845).....\$3.00 a year  
 Scientific American Supplement (Established 1876).....4.50  
 American House and Garden.....2.00  
 Scientific American Export Edition (Established 1878).....8.00  
 The combined subscription rates and rates to foreign countries, including Canada, will be furnished upon application.  
 Remit by postal or express money order, or by bank draft or check.  
 MUNN & CO., 361 Broadway, New York.

NEW YORK, SATURDAY, NOVEMBER 9, 1907.

The Editor is always glad to receive for examination illustrated articles on subjects of timely interest. If the photographs are sharp, the articles short, and the facts authentic, the contributions will receive special attention. Accepted articles will be paid for at regular space rates.

## SINGLE-PHASE ELECTRIC EQUIPMENT ON THE ERIE RAILROAD.

The year 1907 must ever be memorable in the history of the development of electric traction, because of the notable installations which have been made on three of the leading railroad systems of the United States. Early in the year we recorded the opening for regular service of the terminal line of the New York Central and Hudson River Railroad Company in this city. Six months later, the New Haven system put in partial operation the single-phase system on its four-track road from Woodlawn to Stamford; and in the middle of June, of the same summer, an important change from steam to electric traction was made on a 34-mile stretch of the Rochester division of the Erie Railroad. The same month, also, saw the inauguration of electric operation on forty-four miles of the West Shore steam railroad between Utica and Syracuse, the system used being the direct-current with the third rail, and the equipment being in general similar to that of the New York Central terminal lines, with the important exception that the multiple unit system is used throughout. The equipment of the New York Central and West Shore lines, as well as that of the New Haven system, have already been fully described in this journal. The Erie electrification is of the same general character as that of the New Haven road. A working pressure of 11,000 volts is used on the trolley line, the current being transmitted at the high pressure of 60,000 volts. The overhead construction is much simpler than that employed on the four tracks of the New Haven road. In the latter case, it will be remembered, each line is made up of two messenger wires with a trolley wire suspended below and between them, by means of rigid triangles. The messenger or suspending wire is of seven strands, and 7/16 of an inch in diameter, and is made of "extra high strength steel." The trolley wire is suspended from this at 10-foot intervals by means of a series of 3/4-inch iron hanger rods. This wire is, of course, much more flexible than that in use on the New Haven system; and for that reason we should expect to see fewer disarrangements than are liable to occur where the trolley wires are stretched under high tension, and because of the rigid connection of the latter to the triangles are liable to rather serious hammer blows from the contact shoe. The current is taken from the trolley wire by means of pantograph trolleys, and passes through transformers of 200-kilowatt capacity, before it is led to the four 100-horse-power, single-phase railway motors with which the cars are equipped. The control system is of the electro-pneumatic type of the Westinghouse Company, by whom the whole of this work has been done. The above-described equipments serve to operate single cars, with one stop per mile over the entire road, at an average schedule speed of twenty-four miles per hour; or to haul one trailer, making stops about 2 1/4 miles apart, at the same speed.

## THE AUTOMOBILE AT THE RECENT SHOWS.

Nothing at the two fall automobile shows—that in the Grand Central Palace from October 24 to 31 and the other in Madison Square Garden from November 2 to 9—indicates so surely that the automobile has reached the final stage of its development, as the fact that novelties of type are conspicuous by their absence. Outside of the buggy-type machine and the two-engine automobile, there is very little among the exhibits which can be called a radical departure from the all-prevailing type.

Compared with last year, there is a marked increase in the number of runabouts exhibited, this, in-

deed, being the fashionable machine of the season. The runabout owes its popularity largely to its smart appearance and the absence of that heavy and more or less cumbersome appearance which characterizes the limousine top or the hood-covered tonneau. Most of those exhibited have 4-cylinder engines of from 30 to 40 horse-power, although there are also a number of 6-cylinder models.

There are not many changes in the chassis from last year. The pressed-steel, riveted, frame is used almost universally; but a decided improvement in appearance and ease of riding has been secured by the more general adoption of the platform spring suspension, in which a transverse spring is carried at the rear, in place of the old spring hangers, and attached at its ends to the two half-elliptical side springs by universal joints. A few manufacturers are making the frame with a drop to clear the axles, the object of this being to place the frame and gear lower down, and keep the whole driving shaft in as near a straight line as possible. The arrangement has the further advantage of lowering the center of gravity of the car.

The car bodies are, almost without exception, exceedingly handsome examples of the coach-builder's art, and there is noticeable a gratifying tendency toward severity and simplicity of outline and detail, the more or less elaborate curvature of earlier cars giving place to straight lines. There is evidence, also, of better taste in the matter of color; although a few fanciful designs are shown which stand out in rather unfavorable contrast with the other machines.

As the engine is the all-important element in a car, so it was the first to be brought to its final type. There is but little change of consequence to be noticed from last year's models. The most significant feature is the growing popularity of the six-cylinder engine. This is attributable to the fact that the increased cost and trouble of maintenance which were predicted, have not materialized, and the public have found that the theoretical advantages of less vibration and a more constant torque abundantly justify the extra cost of this type. For hill climbing and the general emergencies of the road, the six has proved itself to be decidedly superior to the four-cylinder type. As a rule, magneto ignition is used, with the jump spark as an auxiliary; ball bearings have advanced in favor, and a few makers are using the non-adjustable silent type. Fans are now driven by gears instead of by the old belt drive. A few makers are doing away with the pump and substituting thermo-siphon circulation, which has been used for some years on the foreign Renault car. Two-cycle engines are exhibited in both shows. One maker has three and four-cylinder models in addition to the two-cylinder runabout of last year. On the other hand, the older maker of this type has returned from the use of four to the use of two vertical cylinders.

The most popular form of transmission appears to be the three and four-speed, sliding gear, selective type. Some machines with four-speed transmission have the direct drive on the third speed, the fourth being used for sprints and the direct for all ordinary running. Friction disk transmission is exhibited on a few makes. It owes its success largely to the perseverance of one or two western firms; and their lead is now being followed by several other manufacturers. An improvement on the original type, which is shown on a six-cylinder, 75-horse-power car, consists of a planetary gear transmission, in which conical rollers, made of compressed paper, take the place of the usual spur and internal gear. This transmission has two speeds, and its merit lies in the fact that the friction drive is in use only on the low speed and the reverse. This car has no gears in the transmission, the only gears being those of the bevel gear drive at the rear axle. The friction disk transmission is used extensively in the increasingly popular buggy type of machine, in which differential gears are dispensed with and double ratchets are fitted to the ends of the countershaft for forward and backward motion. A few cars carry a transmission connected to the differential at the rear axle. This arrangement has proved very successful during the past two or three years on one of the leading American cars; it is also in limited use in France. The advantages claimed are that it permits of a long straight shaft from engine to rear axle, and reduces the angularity, and, therefore, the loss of power.

There are few parts of the automobile in which such diversity can be found as in the clutch. There are three main types which share in popular favor. Chief among them is the well-established cone clutch, which has the advantage of extreme simplicity. Its reputation has been acquired in many years of service, and when it is made of sufficient size to match the power of the engine, it gives most satisfactory results. The other devices have been designed to secure large frictional resistance with small size and weight, and chief among them is the floating-disk or ring clutch, in which, by making use of several rings and disks, it is possible to secure a large frictional surface in a small space and with relatively little weight. The

rings vary both as to their diameter and number, one car using as many as nineteen disks, and another disks that are as much as 14 inches in diameter. The expanding and contracting band types also meet with much favor, since they can be compactly and accessibly mounted in the flywheel, and also since they hold well and can be readily adjusted.

Not very much that is novel is exhibited by the tire manufacturers, although there has been an all-round advance in quality. A non-puncturable, self-healing tube, exhibited at last year's show, has been tested with promising results, and is again on exhibition this year. There is also shown a filled tire, containing a special composition of glue, glycerine, etc. It is said to have been quite successful and has been welcomed on those machines whose service exposes them to severe tire troubles. Some half-dozen types of quick-detachable rims seem to have all given satisfactory results. This device has proved to be a great advance over the old style clincher tire.

Unquestionably one of the most novel cars at the Automobile Club of America's show in the Grand Central Palace was a large electric touring car fitted with the new Edison storage battery, the card on which announced that the batteries were good for a continuous run of 100 miles. Another car which excited considerable interest was provided with a two-engine motor, there being two entirely separate 24-horse-power, four-cylinder engines, arranged side by side, parallel with the longitudinal axis of the machine, and connected by transverse chains to the transmission shaft. The makers claim that such a car, with two 30-horse-power engines, exhibits a saving of weight of some 5 per cent over a 60-horse-power car with a single engine. The principal merit of the car is that, in case of one engine breaking down, the other remains to bring the car home. The advantages of twin engines have long been recognized for marine service, and the safeguard against absolute breakdown which the division of the power insures is as valuable on an automobile as on a steamship. The other distinct novelty is the buggy-type automobile, of which no less than twenty different makes are on the market. These cars use a friction disk, or other form of friction drive, and are very simple and economical in construction. The wheels and bodies are essentially those of the standard type of horse buggy, the former being of large diameter and shod with solid tires. It is claimed that the cost of such tires, including maintenance, is not more than one-fourth as much as that of the pneumatic tire. They are capable of a speed of from 15 to 20 miles an hour and their low cost of from \$500 to \$850 is rendering them exceedingly popular with people who are satisfied with a moderate speed and who cannot afford the heavier cost of a large machine. They are used extensively by physicians, and are becoming popular among the farmers and residents of smaller towns and villages.

The low-cost car is also represented by several small runabouts, one manufacturer offering a single-cylinder engine car at a cost of \$500, while a double-opposed-cylinder or four-cylinder runabout can be had for from \$650 to \$700. Although there seems to be no relative gain in the number of steam cars, the two companies which exhibit are doing a large business. The well known advantages of good hill-climbing ability, simplicity of operation, and reliability, have served to maintain the steam car in popular favor.

## A NEW FRENCH AEROPLANE RECORD.

Saturday, the 26th of October, M. Henri Farman's new aeroplane, which we illustrated in the SCIENTIFIC AMERICAN of that date, accomplished a record-breaking flight of 771 meters (2,529.52 feet) above the drill ground of Issy les Moulinaux, near Paris. The flight was made in 53 seconds, or at an average speed of 32.54 miles an hour. Earlier in the day M. Farman made a flight of 363 meters (1,190.94 feet) in 30 seconds, which was equivalent to a speed of 27.06 miles per hour.

The flight of nearly half a mile is by far the longest which has ever been made in Europe with an aeroplane, and it marks a long stride forward in the navigation of the air by a heavier-than-air machine, especially when the fact is borne in mind that it came as the culmination of a long series of flights made during a number of days without any accident or damage to the machine. On October 15, M. Farman flew 935 feet; on the 25th, 984 feet, and on the 29th, the distances given above.

When this machine is compared with that of the sculptor Delagrange, which earlier in the year made some short but successful flights of considerable promise, the Farman aeroplane is found to have a somewhat greater supporting surface (697 1/2 square feet as against 645.84). Like the former machine, M. Farman's consists of two long superposed surfaces 33.45 feet in length by 6.56 feet wide, followed, at a distance of about 15 feet, by two other superposed surfaces 19.68 feet long by 6.56 feet wide. The same type of double horizontal rudder is fitted at the front, and the



forward pair of planes also carry the 50-horse-power motor and the 6.56-foot propeller, the pitch of which is 3.6 feet. The weight lifted per horse-power with this machine ranges from 22 to 25 pounds, supposing that the motor developed its full power. The probabilities are, however, that the lift per horse-power was somewhat greater. The amount lifted per square foot of supporting surface was about 1½ pounds, which is considerably less than most modern French aeroplanes are capable of lifting. Notwithstanding the large supporting surface, the speed of the machine was as great, and probably greater than that of any of its foreign predecessors. The fact that it exhibited good stability goes to show that this type of machine is one which apparently has a future.

#### RESCUING OUR ROADS.

BY GEORGE ETHELBERT WALSH.

Foreigners continue to anathematize American roads after a tour over them, especially if the trip takes them through parts of the Middle West and the South or in the rocky regions of New England. But much as we recognize the justice of this criticism, we look with pardonable pride upon the obverse side of the shield. In the past five years we have redeemed upward of five thousand miles of highways from the wayward habit of going to the bad, rescued some six thousand more from sloughs and swamps of mud and water, and mapped out plans for improving many other thousands so they will in time become at least passable. We have inaugurated new systems of road building, framed new methods of taxation for highway improvement, and interested nearly every progressive community in the work of developing better highways.

The ideal road is still in the stage of experimental evolution. Consult road engineers and experts, and one will inform you that Telford and MacAdam laid down the principles of road construction that cannot be properly departed from, and another will tell you that to attempt to adhere to such principles would ruin half the counties of a dozen States. One set of engineers places drainage as the chief aim in road building, but another will point to the fact that one-third of our roads cross arid or semi-arid regions, where drainage is not a factor of any considerable value. Others have made extensive studies of French and English roads, and are positive that we must duplicate these foreign highways here if we expect to secure ideal results.

But happily the consensus of engineering opinion is crystallizing around the very simple proposition that road making is largely a local matter, depending upon the topography, climate, geological formation, and requirements of any community. The roads in the United States must be developed according to special standards, and not according to those set in other countries. The sentiment of the country is in favor of good roads, but not for French or English roads or necessarily for Telford or MacAdam roads. It is for good roads, worked out by engineers who can best appreciate the needs, conditions, and materials of any particular section. We have many typical illustrations of how certain sections have already solved the road problem according to special needs. In California there are the best types of oiled roads, which answer for the dusty highways of that State better than anything yet attempted. But what road making from the conservative point of view of a Telford or MacAdam principle!

The roadbed of dirt and sand is first plowed, harrowed, rolled, and graded, until there is a layer of finely pulverized soil ten to twelve inches deep over the surface, but no signs of crushed or broken stone, no material whatever—except a little sand on top—such as is used for the foundation of the Telford or MacAdam roads. Then when this graded road has dried and settled, crude petroleum or asphalt residuums are spread over the surface. The oil is heated from 175 to 300 deg., and spread over the road at this very high temperature. From one hundred to three hundred barrels of oil are used on each mile of road, eighteen feet wide, at an estimated cost of \$15 to \$20 per mile. Coarse sand or gravel is spread over the oil, to increase the absorption and to protect passing vehicles. Sometimes a second coating of oil is put on within a few weeks. This method of road building in California costs about one and a half cents per square foot, while asphalt costs fifteen cents, and powdered granite about five cents. California's road problem is the suppression of dust and the modification of the hot glare on bright sand. The oiled roads become indurated and resilient with oil, so that the dust is permanently laid and the bright sand modified to dark brown. There are nearly 1,500 miles of these oiled roads in California, and with the exception of staining white dresses or shoes coming in contact with the oil, they make the best possible highways for hot, sandy, dusty regions, with hardly a single drawback. The surface is not easily cut up with wagon tires, for the oiled surface does not soften like asphalt pavement, and the rubber tires of motor cars are not injured by the oil, as first supposed.

California has thus made a long stride toward at-

taining the ideal road for the sandy strip of country reaching from the mountains to the coast. Other States with similar soil and climate have entered upon the work of building oiled roads. Texas has obtained some excellent results in this direction, and wherever oil is cheap the work has assumed considerable progress. Crude oil ranges in price in California from 70 to 80 cents per barrel, but in many other States the cost of oil makes road building of this character a physical impossibility.

As a direct result of successful experiments with oil for roads in California—and in Oran, Africa, and several towns of Algiers where aloe and massot oil were used—road builders took up the question of employing tar, either alone or in connection with oil for road surfacing. In France a mixture of tar and oil was tried in 1900, and by 1901 such good effects were obtained with various tar mixtures, that many miles of roads were surfaced with them. The French engineers pursued the subject with intelligent perseverance, and they secured some ideal roads for traveling. The tar is applied hot at about 210 deg., and only in dry weather. After the tar is applied, a sprinkling of sand is made over the surface to harden the mixture and to prevent slipping of horses and vehicles. By the addition of heavy oils, the tar is hardened more quickly, and the road thrown open to general traffic. All dust and mud are eliminated by the tarring process, and the roadbed itself is kept from injury by heavy traffic. The waterproof character of the tar surface keeps the water from entering the roadbed, and thus eliminates one of the most destructive agencies of highways.

In England tar is also used quite extensively for the maintenance of the surface of the roads, and in this country it is also a well-recognized practice. One of the first applications of tar to the surface was made at Jackson, Tenn. The surfacing lasted about seven or eight months. In Montclair, N. J., a mixture of tar and screenings was tried in 1904 on a steep grade, and for a year practically no wear or tear was noticeable on the road. Since then a number of other roads in that town have been similarly treated at a cost of about 17 cents per square foot, including the cracked stone and screenings. The tarring itself cost only about five to six cents per square foot. In several other New Jersey towns and on Long Island, roads are now being treated with tarred surface for eliminating dust and mud and for the protection of the road itself.

The difference between the method of tarring the surface of roads in France and this country is in the use of sand or screenings. In France they merely sprinkle sand on the tar after it has cooled a day or two, but in this country cracked stones or screenings are either mixed with the tar or sprinkled upon the surface, with the purpose of incorporating them as much as possible with the tar. The French roads are excellent, and form a dry, dustless surface, but they do not last as long as the American roads of equal excellence. The tar and screenings, when properly mixed together, form a sort of cushion, which greatly reduces abrasion.

The use of tar in territories where there are ample rainfalls is far superior to oil, for the latter then forms an emulsion with the water, which does great damage to vehicles and clothes. It makes the surface mushy, and resprinkling is necessary at intervals. But in dry, hot, arid regions the oil is superior to tar, and accomplishes the object of laying the dust and forming a smooth compact surface better. It is consequently a question of climate and topographical conditions which must determine the use of materials and methods in any part of the country.

But probably the great problem of road building in this country is confined more to the Mississippi Valley. In this vast region road-building materials are scarce and expensive. The use of oil or tar for surfacing would prove of little value, unless the roadbed itself could first be built up of proper material. There is no good gravel, no slates, shales, or silicates available for the roads of this region, but there is plenty of rich land and heavy soil. Drainage is naturally poor, and road building becomes an engineering problem of great difficulty.

In our New England and Eastern States stone and gravel are abundant, and road building is chiefly a problem of proper construction of beds with some of the nearby stones. Drainage is first essential, but this can be obtained by elevating the bed of the road sufficiently, and constructing ditches, culverts, and bridges at proper points. It is a work which any competent engineer can plan and carry to perfection. The principles of the Telford and MacAdam roads here come into vital use. Roads once properly built of the right material will, if repairs are made systematically and scientifically, last indefinitely. At the recent International Engineering Congress in England, an engineer of that country who had four hundred miles of road under his jurisdiction, reported that he had only to rebuild two or three miles a year. The vital point which he wished to emphasize in this report was that if proper methods of repair and maintenance are early

adopted, the roads can be made to last indefinitely, and practically do not require rebuilding oftener than once in a decade or two.

The automobile has had a somewhat paradoxical effect upon our roads. It has been a tremendous factor in stimulating the construction of better roads, and a good deal of money has flowed from the treasuries of the motor associations into road building. But the automobile has increased the dust problem of many localities, and it has made the treatment of macadam roads on the surface with tar or oil mixtures to lay the dust essential. In Massachusetts the rescue of many of the highways simply means an application of some surface mixture to lay the dust of finely powdered rocks and gravel. Several large appropriations have been made by the Highway Commission to test the various patent mixtures for solving the dust trouble, and the United States government is conducting some experiments near Wayland, Mass., for similar purposes. These dust layers consist for the most part of tar and oil in different proportions, and the very fact that so much attention is given to them by manufacturers and the public indicates a healthy condition of affairs, and it must in the end contribute toward road improvement.

But the larger aspect of the road problem in this country includes the construction of better highways in those great middle sections of our country where neither sand, gravel, stone, nor shales can be had without great cost. Where natural road-making material is abundant, the engineer has no very great problem to solve; and after good roads are once built, the rest depends upon good maintenance and the further improvement by dressing the surface with dust-laying materials of tar or oil. Good gravel, granite, and hard stones make the best materials for roads; but limestone, slates, shales, and the silicates are used in many sections with fair success. The soft limestones make fairly good foundations, but they do not last so long as harder stones, and the shales are affected by frost, so that they require renewal oftener. Some of the silicates, however, prove exceedingly durable, and it has been found profitable and economical to transport some of these two and three hundred miles for road building.

In the great Mississippi Valley there is practically no good road-making material at hand, and whatever is used must be transported great distances at considerable expense. In Illinois, Alabama, Kansas, Iowa, and other middle central States the road problem is acute to-day. Occasionally gravel beds are found which yield fair road-making material, and in the hands of the engineer good stretches of highways have been made at no great cost. The drainage on these rich farming sections is almost as bad as it could be, and this increases the cost and trouble of the work. Traveling through these States in an automobile makes one conscious of the great road problems facing our richest agricultural regions. In vain have local and national engineers sought to devise some means of making roads in these States without importing stones, gravel, and other building material. But apparently the roads must be built at great expense through the employment of materials transported from more favored sections. Transportation thus becomes the most vital factor in road making of the Mississippi Valley and of many of the Southern States. If good roads are to be had there, the materials must be brought by the railroads, and co-operation between the steam lines and local highway commissions must be secured.

No hard and fast rules of highway building could be laid down for this great central region, although the best granite or gravel would pay the best in the end, for it costs no more to transport it than the cheaper shales and softer limestones. The question of durability and cost of maintenance would have to be seriously considered. In the experiments made by the government and local commissions, good roads of broken stones, such as granite, flint, and silicates, prove more economical than cheaper materials, and many of the middle western towns and cities have miles of excellent highways built at only thirty to forty per cent more than the cost of similar roads in the East, which, with proper care, will last for many decades.

Good roads in the Mississippi Valley pay better than almost anywhere else in the country, owing to the vivid contrast between them and the natural poor roads. The increase in valuation of property along the line of macadam roads in this section has been all the way from fifty to sixty per cent, and many new, thriving towns are to-day making strenuous efforts to attract settlers and investors through improving roads. It has proved an economical success to increase road taxation in order to secure higher real estate values. Road construction across the middle of our continent at the present rate of development should within another decade completely revolutionize conditions; and a trip across from ocean to ocean by automobile should prove a popular pleasure instead of a tiresome struggle with muddy, dusty, and heavy stretches of roads.

## ENGINES

### LATEST IMPROVEMENTS IN THE FRANKLIN AIR-COOLED ENGINE.


From the time when it made its first appearance before the American public, the Franklin engine has always been noted for its light weight, powerfulness, and especially for its air-cooling feature. When this little engine was first brought out over five years ago, it consisted of four cylinders of  $3\frac{1}{4}$  inches bore and stroke, and rated at 7 horse-power. The next year, by refinements in construction, the horse-power was raised to 10; and subsequently, by adding an auxiliary exhaust, and thus disposing of the burnt gases faster and more effectively than is done in any other type of engine, the horse-power was raised to 12. For 1908, by the addition of a cylinder with a dome head and having a single concentric valve, the horse-power of this same sized engine has increased to 16, or, in other words, it is now over 100 per cent greater than it was at the start five years ago. Thus, in a half decade, Mr. John Wilkinson, the inventor of this engine and car, has not only been able to make a success of a type of engine which the French gave up in disgust, but he has also succeeded in obtaining results in the line of durability and economy which has not been duplicated abroad by the French or by any other nation.

Aside from the fact that it is placed in a cylinder head which is shaped correctly for the highest efficiency, the new concentric valve is interesting in itself as regards its construction and method of operation. Something of this sort was tried several years ago upon the Lanchester air-cooled engine made in England, but the valve used in that engine was constructed differently, and was subsequently abandoned. The new Franklin arrangement consists of a valve within a valve. The outer, or exhaust valve, is merely a shell having a long hollow stem through which passes the stem of the inlet valve. This latter valve seats against the inner surface of the shell, that is, against the part, 1, which forms the seat of the exhaust valve. Both valve stems are provided with washers and springs, as can readily be seen from a glance at

(Continued on page 346.)

### IMPROVEMENTS IN THE MARMON AIR-COOLED MOTOR.

One of the most successful American air-cooled motors is that constructed by the firm of Nordyke & Marmon, of Indianapolis, Ind. For several years past the Marmon 4-cylinder V, or 90-degree motor, has been one of the standard American makes. This year the



Partial Cross-Section of the Improved Franklin Air-Cooled Engine and Its Novel Valves.

One cylinder is shown in cross-section, while the auxiliary exhaust valve is shown in cross-section in the next one. The fan is shown driven by bevel gears. 1. Seat of exhaust valve. 2. Inlet valve. 3. Interior of exhaust valve. 4. Inlet port. 5 and 6. Valve springs. 6 and 7. Valve operating levers.

company produced a larger motor having eight cylinders in rows of four set at an angle of 90 degrees, but for 1908 this huge model has been dropped, and only the 4-cylinder, air-cooled V motor and an ordinary 4-cylinder vertical motor with water-cooled cylinders


usual radiating flanges, the head contains the inlet and exhaust valves and ports, so that there are no extra valve cages to be released before the valves can be removed. Access to the valves is greatly simplified and made easy for the chauffeur, and in case it is necessary to grind these valves, the whole head can be instantly removed and the valves ground without the danger of getting any emery into the cylinder.

Furthermore, by this construction, it is made easy for the chauffeur to scrape out the cylinders and remove any carbon deposit from the cylinder or the cylinder head. This is something that it is sometimes necessary to do, especially with an air-cooled motor, where carbon deposits in the cylinder or the head are apt to cause premature explosions. Beyond the bringing out of a 4-cylinder vertical water-cooled motor, the Marmon engines have not been changed any during the past year. They still retain the same system of force-feed lubrication by forcing oil through a hollow crank shaft to all the bearings. This system, as well as the car, was fully described and illustrated in our Automobile issue two years ago, and we refer our readers to that issue for a complete description of the machine as it stands to-day.

### THE NATIONAL 6-CYLINDER ENGINE.

The National Company was one of the very first concerns in this country to adopt the 6-cylinder engine for its touring cars. The new 1908 6-cylinder motor, which we illustrate, is one of the most compact engines of this type on the market. It has individual cylinders of 5 inches bore and stroke. The improvements in this engine have been such as to do away with what little vibration there sometimes is with an engine of this type, and also to reduce the noise as much as possible. For accomplishing the latter purpose, large, wide-faced, spiral gears are used for driving the two cam shafts, and the shafts are mounted in Hess-Bright ball bearings of generous size. The cams are especially large, as are also the nickel-steel valves, which have a very small lift, and are thus practically noiseless. The valve lifters have large rollers at their lower ends. The inlet, exhaust, and water pipes have been increased considerably in size, but they are attached to the engine in the same way as heretofore, that is, by a common yoke, which holds both the water


(Continued on page 346.)



Separate Cylinder and Head of the Marmon Engine.


The valves are located in the head, which is securely bolted to the cylinder.

ders will be built. A decided improvement in the new air-cooled motor is a detachable head, which is shown in the illustration. This head is fitted to the cylinder with a ground joint, and is held in place by four rods which bolt it to the crank case. Besides the



Inlet Side of the 6-Cylinder National Engine.

This engine is a typical 6-cylinder of the separate cylinder type. The valves are in chambers on opposite sides of the heads. The high-tension magneto and the distributor for the single spark coil are plainly visible in the illustration, as are also the carburetor, fan, and oiler.



Inlet Side of the New 85-Horse-Power Stoddard-Dayton Engine.

The valves are located in water-jacketed valve chambers placed on top of the cylinders, which are fitted with corrugated copper water jackets. Each pair of valves is operated by a single rocker arm. Description of engine will be found on page 346.


SOME IMPROVED ENGINES OF 1908 CARS.



**THE HEWITT 8-CYLINDER 90-DEGREE MOTOR.**

The Hewitt Motor Company will continue to manufacture, next year, the 8-cylinder V motor shown in our illustration, and will apply it to their touring car as heretofore. Mr. Edward R. Hewitt, the designer and builder of this motor, has done a great deal of experimenting with engines of this type, which is that used so largely in France for airships, aeroplanes, hydroplanes, and the like. He believes that this type of motor is far superior to the usual 4-cylinder, or even the 6-cylinder type, as it has in a still further degree the leading features of the latter, and yet does not take up any more space than does the former. As far as weight is concerned, the 6-cylinder motor is heavier than the 8-cylinder motor of the same power, and besides this it has a very long crankshaft, which is springy and difficult to make. The 8-cylinder V motor has the usual four-throw crankshaft that is used on engines of the 4-cylinder type. When the piston of one cylinder is half-way down on its working stroke, that of the opposite cylinder is just ready to begin on the working stroke, the result being that there is a practically constant torque. This motor can also be perfectly balanced, and hardly requires a flywheel. The range of speed is very great; so great, in fact, that when mounted on the car speeds


every cylinder and every bearing. Splash lubrication is also used. The motor is fed from a single carbureter placed above and between the cylinders. The timer and distributor are located upon a vertical shaft

**The Hewitt 8-Cylinder V Motor.**

This is the only automobile motor of its kind constructed in America. It is of the same type as that used by Santos Dumont and other foreign experimenters on aeroplanes, hydroplanes, and dirigibles. The motor illustrated is much more substantial in construction, however, than those of its kind built abroad.

**THE CARTER TWO-ENGINE CAR.**

Probably the most novel automobile exhibited at the recent show in the Grand Central Palace was that in which two 4-cylinder air-cooled motors of 24 horse-power each formed the motive power of the car. The idea of a duplicate power plant came to Mr. Howard O. Carter, the inventor, one day when he was stranded many miles from home on account of a disabled engine; and that he has followed out this apparently somewhat freakish notion to a successful conclusion, can be seen from the accompanying illustration. The two engines are mounted side by side, and are connected, through cone clutches in the flywheels and by Morse silent chains, to a single three-speed transmission placed in the center of the car. Each engine, with all accessories, is entirely separate from its neighbor. The method of operation is as follows: One engine is started by cranking in the usual manner. The car is then run along on the one engine until a steep grade or bad piece of road is met with. Then the clutch of the other engine is engaged while the car is running slowly on the high speed. The second engine immediately starts, and with double the horse-power instantly available, the car can ascend the grade or traverse the bad road without dropping back to a lower gear. The main idea of the inventor, however, is the provi-


**Chassis of the Carter Twin-Engine Car.**

The inventor of this machine has adopted duplicate power plants mainly for the purpose of increasing the reliability of his car. The two engines are connected to the transmission through Morse silent chains.

of 3 to 70 miles can be had on the high gear. The ignition system consists of a high-tension magneto, with the addition of a battery and coil for the purpose of starting on the spark. The motor is lubricated by a gear-driven mechanical oiler, which forces the oil to

at the forward end of the motor, as is also the mechanical oiler. A centrifugal water pump, gear-driven from the crankshaft, is placed at the forward end. The valves are all mechanically-operated, and are


(Continued on page 347.)

**Front View of the Peerless Motor.**


This picture shows the carburetor and magneto, as well as the lever for advancing armature of the latter.

sion of a duplicate power plant, which is instantly available in case of a serious breakdown of the regular one. That this system does not make an abnormally heavy car can be seen from the fact that the

(Continued on page 347.)

**Exhaust Side of the Peerless 30-Horse-Power, 4-Cylinder Motor.**

Note the neat casings of the gears and governor. The latter is seen beside the crank case, its shaft being prolonged to drive the pump. The fan is driven by bevel gears. The commutator is seen on a vertical shaft between the cylinders, as are also the twin spark plugs in the head of each cylinder.

**The 45-Horse-Power, Two-Cycle Engine of the Reliance Truck.**

The simplicity of the two-cycle engine is apparent from this photograph. There are no valves, with their accompanying springs, push rods, and cams; while some engines of this type can also be reversed. The mechanical oiler is the only mechanism visible in the above illustration.

## TRANSMISSIONS AND CHASSIS

## THE HATFIELD BUGGY TYPE CHASSIS.

There are a large number of high-wheeled vehicles fitted with solid rubber tires, light opposed-cylinder motors, and planetary or friction-disk transmissions, now upon the market. One of the most interesting of these, as well as one of the simplest, is the Hatfield "Buggyabout," a plan view of the chassis of which we illustrate. As can be readily seen, the motive power consists of the double-opposed-cylinder, air-cooled motor of 12 horse-power, which drives, through a pair of friction disks, the transverse countershaft placed directly under the seat in the center of the machine. The disk on this countershaft can be slid to one side or the other of the disk on the motor crankshaft, thus securing the forward speeds and the reverse. Separate driving chains run from sprockets on the ends of this countershaft to the large sprockets, which are mounted on the rear wheels through a peculiar trussed-wire arrangement. To allow for the differential motion of the gear wheels at the countershaft, a patented type of double ratchet is provided in a drum on each end of this shaft. One set of these ratchets are used in going forward, and the other when the car is reversed.


The steering gear used on this car is very similar to that used on some of the first automobiles ever built in this country. The whole front axle is swung on a fifth wheel. Attached to this axle is a semicircle of angle iron upon which slides a chain. This chain is fastened to each end of the axle, and it passes around a horizontal sprocket mounted upon the vertical steering post. When the steering wheel is turned, the sprocket moves the chain and swings the entire front

## THE POWER PLANT OF THE HOLSMAN CAR.

One of the first, and possibly the most successful, of the buggy type machines is that made by the Holman Automobile Company, of Chicago. Our illustration shows the power plant used on this car, and its


## A UNIQUE FORM OF TRANSMISSION GEAR.

The transmission shown in the accompanying photograph is one of the simplest and neatest gears of its type that we have seen. In designing it, the inventor has done away with the usual type of sliding gear



PLAN VIEW OF THE HATFIELD "BUGGYABOUT" CHASSIS.

The above is one type of chassis used with machines of this kind. The motor flywheel is faced to act as a friction disk. Another disk on a countershaft is slid opposite different points on the flywheel to produce the various speeds. Ratchet clutches on the end of the countershaft replace the differential. In steering, the whole front axle is swung on a fifth wheel.



THE TWO-SPEED PLANETARY FRICTION ROLLER TRANSMISSION OF THE GEARLESS CAR.

This transmission is similar to the ordinary planetary gear type. Conical friction rollers take the place of the usual spur and internal gears. Two of these are visible between the two hand brakes. The hand brakes are applied by pedals, while the internal expanding ring clutch in the forward drum is operated by a hand lever.

axle. A turnbuckle makes it possible to tighten the chain if necessary.

The friction disk is slid upon the countershaft by means of a lever placed beside the driver's seat, while pressure upon a pedal applies this disk to that on the flywheel and starts the car ahead. Brakes are located upon the countershaft, and are very powerful. They are applied by another pedal. A gasoline tank is located in the dashboard, and carries sufficient fuel for a run of 160 miles.

Another machine exhibited at the Grand Central Palace show, and which was very similar in construction to the Hatfield, was that made by the Schacht Manufacturing Company, of Cincinnati, Ohio. A water-cooled motor is used to propel this machine, however, and the gasoline tank is located in the back of the seat, while the dashboard consists of a radiator. The steering gear of the Schacht machine is of the ordinary automobile type, but with the differences mentioned, the car is quite similar to the machine shown above.

## THE GEARLESS TWO-SPEED TRANSMISSION.

One of the most novel friction transmissions exhibited at the Automobile Club of America's show in the Grand Central Palace was that seen on the Gearless 6-cylinder touring cars. In this transmission the disadvantages of the usual form of friction disk arrangement have been done away with, and a gear of the planetary type having conical friction rollers in place of spur gears has taken its place. In this device there are no varying peripheral speeds of the friction surfaces at the point of contact, and consequently no

(Continued on page 340.)




THE CAMERON—A UNIQUE SLIDING GEAR TRANSMISSION.

The gears are first moved opposite the large gear on the differential and then meshed with it face on. To obtain the reverse, a wide intermediate pinion in the upper half of the gear case is dropped into mesh with the two large spur gears.

transmission in which the gears mesh from the side, and has made an arrangement that the gears can be put opposite the large gear placed upon the differential and can then be meshed face on.


As can be readily seen, there is a sliding member of



ENGINE AND TRANSMISSION OF THE HOLSMAN CARRIAGE-TYPE AUTOMOBILE.

This air-cooled engine has two opposed cylinders of four inches bore and stroke. It is connected to the countershaft by two Morse chains which produce the high or low speed. The large pulleys drive the rear wheels by patent chain cables. The reverse is obtained by pressing the small pulleys against the tires of the rear wheels. The engine has two spark plugs in each cylinder and fan-blades in the flywheel for cooling.






CHASSIS OF LAMBERT CAR, WITH FRICTION-DISK TRANSMISSION.

This is a typical double-opposed-cylinder car with friction-disk transmission. The drive is by a single chain to the live rear axle. The driving disk on the extension of the crankshaft is faced with aluminium and the periphery of the driven disk with compressed paper. The driven disk is slid across the face of the driver by a hand lever and is pressed against it by a pedal. The arrangement of the parts is clearly shown.

three spur gears mounted on a short countershaft carried in a yoke and placed beside the differential. This yoke can be moved forward and backward in a suitable bearing, and thus the gears can be brought face-on against the spur gear of the differential when once they are located opposite it. The location of the gears


the larger bevel, which it drives. In order to obtain the reverse there is a small spur pinion mounted in the case of the transmission, which can be brought into mesh with the spur gear on the differential, and also with the large spur gear on the countershaft, thus obtaining a reverse motion. The idea of bringing the



THE COMBINED TRANSMISSION AND REAR AXLE OF THE PENNSYLVANIA CAR.

This location of the transmission is gradually coming into vogue. It makes possible a straight line drive from the engine to the rear axle, which results in less loss of power in the universals.

in the proper direction is accomplished by sliding them upon the short shaft. The large bevel gear upon this shaft meshes with the bevel pinion upon the propeller shaft, and this pinion is also arranged to slide upon the shaft, so that it can go forward or backward with the yoke, and thus always keep in mesh with



THE PEERLESS FOUR-SPEED SELECTIVE TYPE, SLIDING-GEAR TRANSMISSION.

There are two pairs of sliding gears, viz., 5 and 6, and 7 and 8. The speeds are obtained as follows: Low speed through 5, 4, 1, 5. Second speed through 9, 4, 2, 6. Third speed through gears 9, 4, 3, 7. Fourth speed (direct drive) by telescoping gear 8 into gear 9. The reverse is obtained with gears in position shown by lowering 10 into contact with 1 and 5. A cam connected to gear 11 positively holds the gear 10 out of engagement while the other gears are in mesh. Toothed segment 11 is operated by a rack on one of the three sliding bars.


gears into mesh face-on was first used some years ago on the Renault car, in Paris, but there has been no subsequent development in this line until this little transmission was brought out. The device is found upon a small 4-cylinder runabout of the air-cooled type, and it has been very thoroughly tried out upon this

trate, for in this instance the designer has made a double drop in the frame, so that the whole center part is at a lower level than the forward and rear end. The main advantage of this method of forming the frame is claimed to be its great strength, while the secondary advantages are a lower center of gravity and a greater road clearance for the car. This shape of frame, it is claimed, follows the principles embodied in the more recent Pullman car construction, whereby great rigidity and strength are obtained. The motor is mounted upon a sub-frame, and made to line up with the transmission, which is hung from arms that are attached to the members of the main frame. On account of the drop of the frame, the rear shaft of the transmission is made to line perfectly with the propeller shaft when the car is going. The result is that practically all the time the propeller shaft is perfectly in line with the transmission and the crankshaft of the engine. Although two universal joints are fitted to the propeller shaft, these are rarely in operation when the car is running along on the road and power is being transmitted to the rear axle. The claim is made by the builders of the Imperial car, that from 7½ to 25 per cent of the engine power which should be delivered to the rear wheels is lost by bad alignment.

#### THE LAMBERT FRICTION-DRIVE CHASSIS.

The chassis shown above is a typical one employing the friction-disk transmission. An 18-horse-power, double-opposed-cylinder motor of 5 inches bore and 4 inches stroke is mounted in front and carries, on an extension of its crankshaft, a large aluminium-faced

(Continued on page 342.)



SIDE VIEW OF IMPERIAL CHASSIS, SHOWING THE DOUBLE DROPPED FRAME.

This is a new type of frame. The object of this construction is to make the center of gravity of the car as low as possible, and also to keep the universally-jointed driving shaft in a straight line. The engine is mounted upon a sub-frame. The location of the radiator back of the front axle should also be noted. The rear drop in the frame gives greater leg room to the occupants of the surrey-type rear seats.

## TYPES OF SHOCK ABSORBERS FOR AUTOMOBILES.

BY HOWARD GREENE.

Years of study and experimenting have been spent in the effort of evolving from the carriage spring a type of spring adapted for the suspension of automobile bodies on their chassis. At last a form of spring has been produced which possesses the maximum degree of strength and flexibility in proportion to weight and size.




Fig. 1.—The 1908 Truffault-Hartford Shock Absorber.

The highest possible elasticity is necessary in order to afford comfort to the passengers, while tensile strength is needed to resist the severe shocks incident to driving rapidly over uneven and rough roads. The high elasticity which is so essential in the automobile spring has been found to possess one serious drawback, however; that is, an excessive rebound. All the useful work of the spring has been done when, in passing over an obstruction, the spring has been compressed and then returns to its normal position on the first rebound. In practice the action of the spring does not cease there, but is succeeded by a series of vibratory movements, as a rubber ball bounds and rebounds many times when thrown upon a stone pavement, unless the motion is checked by catching the ball in the hands. Breakages of springs often result from the excessive rebound after compression. When the spring is suddenly compressed or flexed downward as the wheel passes over an obstruction, the long top leaf is supported below by the shorter leaves; but unless clips are provided to hold the leaves together, the momentum of the body and its load on the upward rebound is liable to lift the free ends of the top leaf away from the lower leaves, and cause it to break where it is secured at the center.

The purpose of the shock absorber is to check the tendency to excessive rebounds, stopping the disagreeable vibration of the vehicle body, and preventing breakage of springs from this cause. Like many other automobile improvements, we are indebted for it very largely to the big international automobile road races. The excessive bounding of the light racing cars when traveling at terrific speeds over the roads proved exceedingly dangerous, and devices were designed to check this action and make the cars ride more evenly. The first and one of the most successful devices of this kind was applied to racing cars in France five years ago. Since then a number of changes and improvements have been made, and the device, which is known as the Truffault-Hartford, is now part of the regular equipment of several high-grade American and French cars.

Since its first introduction the shock absorber has grown rapidly in popularity with automobile owners, and nearly a score of American inventions of devices for a similar purpose have been brought out and are now on the market. These are of a variety of types, which may be divided into friction checks, hydrau-

lic checks, pneumatic shock absorbers, and supplementary spring devices. In addition to the mechanisms belonging to these main divisions or principal classifications, there are a number of devices that make use of a combination of two of the general principles, such as hydraulic and friction and spring and friction. All are constructed to be attached at one end to the spring or rear axle near the middle of the spring, and at the other end to the side of the frame above the axle, so




Fig. 2.—General View of the Paternoster Shock Absorber Attached to Car.

that the resistance which it offers will act directly between the spring and the frame.

The Truffault-Hartford, which is made by the Hartford Suspension Company, of New York, and is illustrated in Fig. 1, belongs to the friction type and is of the simplest construction. In general form it is like the stop of a trunk lid. The end of one arm is held by a stud on a plate that is bolted to the side of the car frame, and the small ends of a pair of other arms are attached by a bolt to a plate that is held by the spring clamps. The other ends of the arms are enlarged into circular friction plates, the end of the upper arm being placed between the disks of the pair




Fig. 5.—Shippey Shock Absorber—Non-Friction Spring Action.

of lower arms. The arms are joined together firmly by a center stud fitted with a hardened steel bushing. Under the nut of the stud on one side is a star-shaped spring steel washer, that maintains constant compression on the friction plates and compensates for wear. An absorbent friction material is interposed between the faces of the disks, increasing the friction and at the same time providing a receptacle for retaining lubricant, enough of which is held in the material to last indefinitely. The device is both dustproof and waterproof, and each set is tested to a uniform tension. All arms are of equal length, making the suspension uniform and the shock absorbers interchangeable.

This form of shock absorber is simple, strong, unobtrusive, and durable. It acts in both directions, that is, against the compression and against the rebound of the car springs, acting as a brake to vibration. It does not have the same effect as the use of a stiffer spring, but, while leaving the springs as flexible and responsive as before, stops excessive play and absorbs the shocks by converting motion into frictional heat.

Many virtues are claimed for this shock absorber. Besides preventing breakage of springs in the way mentioned and increasing the comfort of riding, its use prevents racking of the car by reducing the rolling and pitching motions, saves wear on the tires by reducing skidding and making the use of brakes less often necessary, obviates the need of slowing down for ordinary crosswalks and holes in the road surface, and, by checking the rebound and keeping the wheels constantly in contact with the road, utilizes more of the power de-

veloped by the engine, thereby also increasing in some degree the speed of the machine.

The principle and general form of the Hartford shock absorber have been extensively copied, and a number of devices have been patented and offered for sale during the last two or three years that differ from it only in detail, such as the mechanical means for developing the friction.

It is held by many students of the subject that only




Fig. 3.—Roller Clutch, Brake Bands, and Adjustments of the Paternoster Shock Absorber.

the recoil of the spring should be checked, or that it should be checked more than the compression. Acting under this belief, a European inventor in 1905 patented the Paternoster shock absorber, which is now manufactured and on the market in this country. A general view of this attached to a car, is given in Fig. 2. The frictional elements are contained in a circular case attached to the frame, while the link from the arm to the spring is provided with a small cylindrical case that incloses two soft-rubber buffer springs, between which plays a plunger on the end of the rod. This device is called an "auxiliator," and is intended to permit a certain amount of play of the springs to go unchecked, when running over smooth roads.

Within the circular case attached to the frame of the car are two brake drums, each encircled by a stationary brake band. The bands are adjustable, so far as their pressure on the drums is concerned, by means of screw adjustments which can be manipulated from the outside of the case. One of the drums is connected with the arm rigidly and permanently, while the other is loose on a central arbor cast integral with the case, but is adapted to engage with the arm by means of a roller clutch (Fig. 3) only during the upward movement of the car spring, when there is danger of breakage of the spring and a certainty of a "toss" of the occupants of the car if a full rebound is permitted. Thus there is only one brake acting on the downward movement or compression of the spring, when the stresses are of a legitimate character, but two brakes act, producing twice as much friction, on the upward movement or rebound. The brake bands are of steel, hardened and ground on the wearing surfaces; wear can be taken up and accurate adjustments made by means of the screws already referred to, so that the checking action can be suited to the individual car. The bronze case containing the drums, brake bands, and clutch is closed by a tight cover with a ground joint and is filled with glycerine, which affords excellent lubrication and at the same time acts as a medium for conveying heat away from the brakes and drums.

(Continued on page 349.)




Fig. 4.—Gabriel Shock Absorber Attached.




Fig. 6.—Hotchkiss Hydraulic Anti-Jolt Device Attached.



**TAXIMETER MOTOR CABS IN AMERICA.**


BY HARRY W. PERRY.

Landaulet cabs driven by internal-combustion motors using gasoline for fuel were put in operation as public hacks in New York on October 1 last. They are of the type that has become popular in Paris and London during the last two or three years, being, in fact, of French manufacture, and imported to America


to the comfort of the passengers are two small drop seats suitable for children or adults of small size, two large side pockets for papers and programmes, an opera-glass holder and a cigar holder, and a narrow mirror set between the front windows. Without body, the chassis weighs 1,300 pounds, has a wheel base of 101½ inches and tread of 48½ inches, with a turning radius of 19 feet. The frame is of pressed steel, and

charge for extras. On the back of the instrument are smaller openings, where figures that change automatically show the total and daily mileage covered by the machine and the hours of service for the information of the operating company. Since the adoption of the taximeters, the drivers are paid regular daily wages plus a percentage of the daily receipts.

The other company which is operating taximeter



Interior of Delahaye Landaulet, Showing Taximeter Easily Read from Inside and Folding Seats Between Doors.



Rear of Popp Taximeter Used on Darracq Cabs. Face of Instrument Visible from Inside of Cab.



Face of German Taximeter Used on Delahaye Landaulet Cabs.

upon the order of two companies. Of these companies, one is now operating Delahaye and the other Darracq vehicles. For the company operating the Delahaye cabs, the tariff is now as follows: For one or two passengers: First half mile or fraction, 30 cents; each quarter mile thereafter, 10 cents; each four minutes of waiting, 10 cents. For three, four, or five passengers: First one-third mile or fraction, 30 cents; each one-sixth mile thereafter, 10 cents; each four minutes of waiting, 10 cents. Extra for ordering cab, each mile or fraction from stand or station to point ordered, 20 cents; for trunk, 20 cents.

Shipments of the remaining twenty-five Delahaye cabs of the first lot of fifty ordered were received during October, and the work of fitting them with American pneumatic tires, and German taximeter instruments for automatically calculating the fare to be paid by the passenger, is still in progress. All of the new gasoline cabs are equipped with taximeters before they are put on the streets.

The cabs have yellow running gears, olive-green bodies with black and yellow striping, and black tops trimmed with brass. The front inside seats are upholstered in smooth, black leather, which is also used for lining the lower half of the interior. It is serviceable and sanitary, and appropriate for the public service to which the cabs are put. The folding top is lined with very dark green broadcloth. All windows, of which there are six, let down into the body out of sight for fair weather. The permanent furnishings that contribute

has no bends back of the dash. It measures 8 feet from the dash to the rear end.

The taximeters are circular instruments about the size of street-car fare registers. Unlike the latter, however, they are automatic in action, calculating and indicating at all stages of the trip the precise amount of fare the customer has to pay, thereby eliminating any possibility of the driver making excessive charges, and pocketing a part of the receipts for himself. Although the mechanism is complicated, the principles are readily explained and understood. Each instrument contains clockwork, which drives the gears that operate the registering dials, while the cab is engaged but is standing still, as when waiting at a store or residence while the customer is shopping or calling. This computation by clockwork begins as soon as the passenger engages the cab and the driver turns down the small metal flag bearing the word "Vacant." But as soon as the cab begins to go, the work of driving the registering gearing is taken up by a flexible shaft, which is driven by one of the front wheels of the vehicle in the same way as a speed-indicating instrument, the speed of this shaft overrunning that of the clockwork. The indicating mechanism is similar in principle to the well-known cyclometer or odometer. On the face of the instrument, which is turned so as to be plainly visible from the inside of the cab, there are dials which indicate the "Tariff," whether No. 1 for one or two passengers, or No. 2 for three, four, or five passengers; the amount of fare to be paid and the

cabs was organized last spring, and employs Darracq cabs. A first lot of thirty landaulets was received during September and October, and after being fitted with American tires, were placed in public service, being installed first at hotel stands. The service is to be extended as further shipments are received, contracts having been made by the parent company with the Darracq works for the delivery of six hundred cabs to be shipped at the rate of seventy-five a month. They are being landed this fall at the rate of fifteen a week. Temporary quarters for their storage and care have been leased until May 1 on West 60th Street, between Broadway and Columbus Avenue. By the date named it is expected that a large garage, for which plans have been drawn and contracts let, will be completed on West 57th Street, between 11th and 12th Avenues, at an estimated cost of \$250,000. It is to be 225 by 150 feet, four stories high, and fireproof.

The cabs have dark green running gears, red bodies, and black leather tops. The interior is upholstered throughout in light tan-colored corduroy. Taximeters operating on the same principles as those previously described, but of different form and made under the Popp patents in Paris, are fitted to all the cabs. Only a single tariff is charged, however, whether the cab is occupied by one or four persons, the rates being the same as under tariff No. 1 of the other company; but if a cab is dismissed north of 125th Street or anywhere outside of Manhattan Borough, a charge of 40 cents a mile is made for the return trip.



The Delahaye 10-Horse-Power Cab Fitted with Taximeter.




The 14-16-Horse-Power Darracq Taximeter Cab.



**The Star—A Novel Two-Cycle Runabout with Friction Disk Transmission.**

Engine: Single-cylinder, two-cycle of 10 horse-power, water-cooled, and located in front under bonnet. Drive: Single chain. Transmission: Friction disk, with disk shifted by hand wheel below steering wheel.




**The Simplex Four-Passenger, 50-Horse-Power Roadster.**

Engine:  $5\frac{1}{2} \times 5\frac{1}{2}$ , four-cylinder, with ball-bearing crankshaft. Transmission: Four-speed selective type, with direct drive on the fourth speed. Drive: Double side chain. Weight: 2,500 pounds. Wheel base: 124 inches. Tires:  $36 \times 4\frac{1}{2}$  and  $36\frac{1}{2} \times 5\frac{1}{2}$ .



**A Powerful Electric Touring Runabout**

This runabout is capable of covering about 80 miles across country at an average speed of between 15 and 30 miles an hour. It has twenty-four 150-ampere-hour cells, a 2-horse-power motor, and 5-inch pneumatics.




**The Peerless 57-Horse-Power Six-Cylinder Touring Car.**

Engine:  $4\frac{1}{2} \times 5\frac{1}{2}$ , six-cylinder, water-cooled. Transmission: Four-speed selective type. Drive: Shaft. Weight: 3,800 pounds. Wheel base: 133 $\frac{1}{4}$  inches. Tires:  $36 \times 4$  and  $36 \times 5$ .



**The Lane 20-Horse-Power Steam Touring Car.**

Engine:  $2\frac{1}{2}$  and  $8\frac{1}{4} \times 3\frac{1}{4}$  inch, compound. Boiler: 30-inch; pressure, 225 pounds. Burner: Lane tubular type. Drive: Single chain. Weight: 2,800 pounds. Wheel base: 97 inches. Tires:  $22 \times 4$ .




**The Maxwell 16-20-Horse-Power Light Touring Car.**

Engine:  $4\frac{1}{2} \times 4\frac{1}{4}$ , four-cylinder, vertical, water-cooled. Transmission: Three-speed sliding gear, progressive type. Drive: Shaft. Clutch: Multiple disk in gear box. Wheel base: 96 inches. Weight: 2,100 pounds. Tires:  $22 \times 3\frac{1}{4}$ .



**The Holsman High-Wheeled Limousine.**


Engine:  $4 \times 4$  double-opposed cylinder, air-cooled. Transmission: Two Morse chains to countershaft. Drive: Steel cables to rear wheels. Weight: 900 pounds. Wheel base: 75 inches. Tires: Solid rubber,  $1\frac{1}{4} \times 44$  and  $1\frac{1}{4} \times 48$ .



**The Mora 50-Horse-Power, Six-Cylinder Touring Car.**

Engine:  $4 \times 5\frac{1}{4}$ , six-cylinder, water-cooled. Clutch: Cone. Transmission: Three-speed selective. Drive: Shaft. Weight: 2,500 pounds. Wheel base: 114 inches. Tires:  $36 \times 6$ . Note the bonnet which is apparently no longer than that of a 4-cylinder car. The engine and transmission of this car form a unit.






**The Northern 24-Horse-Power Runabout.**

Engine:  $5\frac{1}{2} \times 5\frac{1}{4}$  double-opposed-cylinder, water-cooled. Transmission: Two-speed planetary. Drive: Shaft. Weight: 2,000 pounds. Wheel base: 106 inches. Tires:  $32 \times 3\frac{1}{2}$ .




**The Cadillac 10-Horse Power Coupe.**

Engine:  $5 \times 5$ , single-cylinder, water-cooled. Transmission: Two-speed planetary gear. Drive: Single chain. Weight: 1,400 pounds. Wheel base: 74 inches. Tires:  $28 \times 3\frac{1}{4}$ .




**The Chadwick 50-Horse-Power Touring Runabout.**

Engine:  $5 \times 6$ , six-cylinder, water-cooled. Clutch: Cone with cork inserts. Transmission: Four-speed selective type. Drive: Double side chain, with chains encased. Weight: 2,800 pounds. Wheel base: 134 inches. Tires:  $34 \times 4$  and  $36 \times 5$ .



**The Autocar 30-35-Horse-Power Gentleman's Roadster.**

Engine:  $4\frac{1}{2} \times 4\frac{1}{2}$ , four-cylinder, water-cooled. Clutch: Floating ring with cork inserts. Transmission: Three-speed selective. Drive: Shaft. Weight: 2,400 pounds. Wheel base: 118 inches. Tires:  $34 \times 4$ .




**The Gearless 75-Horse-Power Six-Cylinder Runabout.**

Engine:  $4\frac{1}{2} \times 5\frac{1}{2}$ , 6-cylinder, water-cooled. Clutch: Metal expanding ring. Transmission: Two-speed planetary with friction rollers in place of gears. Drive: Shaft. Weight: 3,000 pounds. Wheel base: 126 inches. Tires:  $36 \times 4$ .



**The Haynes 45-Horse-Power Four-Cylinder Touring Car.**

Engine:  $4\frac{1}{2} \times 5$ , 4-cylinder, water-cooled; two flywheels. Clutch: Contracting band. Transmission: Three-speed selective. Drive: Shaft. Weight: 2,400 pounds. Wheel base: 100 inches. Tires:  $34 \times 4$ .



**The Moline 18-Horse-Power Two-Cylinder Touring Car.**

Engine:  $5 \times 5$ , double-opposed-cylinder, water-cooled. Transmission: Two-speed planetary. Drive: Single chain. Weight: 1,800 pounds. Wheel base: 92 inches. Tires:  $30 \times 3\frac{1}{4}$ .



**The Stoddard-Dayton 30-35-Horse-Power, Four-Cylinder Touring Car.**

Engine:  $4\frac{1}{2} \times 5$ , four-cylinder, water-cooled, with valves in heads. Clutch: Cone. Transmission: Three-speed selective. Drive: Shaft. Weight: 3,000 pounds. Wheel base: 113 inches. Tires:  $34 \times 4$  and  $34 \times 4\frac{1}{2}$ .


## HOW TO TOUR IN AN AUTOMOBILE.

BY HARRY D. HAINES.

Ideas differ widely, of course, as to the most suitable type of car for touring. Many enthusiastic motorists who have toured thousands of miles prefer to drive in a light high-powered runabout of the style that has leaped into sudden popularity within a year. A strictly limited amount of baggage can be stowed away on the rear deck in a leather waterproof bag or in a steamer trunk strapped on the deck, and a rubber poncho can be carried for protection against rain. With powerful headlights for night driving, and a good blanket for sleeping out at night, if necessary, one can drive for days through the roughest country to remote mountain regions. He will, however, enjoy a sort of selfish pleasure, for at most he can carry only one friend and a mechanic, as the car has only one regular double seat, which is supplemented by a folding rumble seat behind that offers nothing in the way of comfort on a hard day's jaunt. The majority of tourists prefer the regular touring car, with side entrance body, having comfortable seating accommodations for five or seven persons. In such a car, properly fitted out for the purpose, a whole family may travel for weeks almost as luxuriously as in a Pullman railroad car, regardless of weather.

The speedometer part of the combination is useful in view of the fact that speed ordinances and restrictions are becoming more severe every year, and when one is riding in an auto there is nothing more deceptive than speed. Even experienced men who have driven many thousands of miles are unable accurately to guess the speed at which a car is running,

instrument move up the scale as the car speeds steadily on under advanced spark and heavier charges of gas. When touring it is well to carry two new reserve tire shoes. When front and rear wheels are of different sizes, there should be one spare for each pair of tires. The new flat treads are recommended for the rear wheels, but not for the front, as they make steering rather difficult. Extra tires should be covered with waterproof and lightproof casings, as rubber deteriorates when exposed to the light. It is advisable to carry at least two rear inner tubes and one front tube; when touring myself I invariably carry four rear tubes and two front tubes, having experienced as many as five punctures in a single day. Tire troubles are due to various causes, and it is well to be prepared for them. A pigskin repair cover will be found valuable in temporarily fixing a blown-out casing. In the event of a puncture it is advisable to insert a new inner tube rather than to repair an old one, as it is almost impossible to make a satisfactory repair job on the road. Inner tubes for use in rear shoes should never be repaired with rubber patches cemented on. The heat caused by road friction melts these patches off. The only sure way is to have the tube vulcanized. Inner tubes should not be carried loose in a storage box, but should be put



The Evening Meal.




After Pitching the Tent the Cooking Utensils are Soon Put in Use.



A Limited Amount of Baggage Can be Carried on the Folding Trunk Rack.



The question of suitable equipment for touring is one that requires considerable thought. It is possible to spend many hundreds of dollars for all sorts of fittings. Some of these are almost indispensable to comfort and satisfaction on the road, while others only serve to encumber the machine unnecessarily. Although each device may really serve a useful purpose, it should be remembered that, as in traveling by other means or when camping, the less paraphernalia one has to bother with, the greater is his ease of mind and his consequent enjoyment. Too often we pack along on a trip or vacation a bothersome quantity of stuff, much of which is never used. On the other hand, if we confine ourselves to the things that are really essential, we are likely to be surprised by the small amount of baggage that we have to take. Conceding that the automobile tourist desires simply to fit up his car with the attachments and devices that will add to the utility of the machine and to the comfort and safety of the passengers, there are certain things which it will be absolutely necessary for him to have. A comfortable Cape top and glass front are indispensable. In buying a Cape top one should also get a waterproof protector, to be slipped over the top when it is thrown back. This will keep the dirt and dust out of the lining and prove a profitable investment. The machine should be fitted with a set of good shock absorbers, to protect the springs from breakage when traveling over rough country and also for the purpose of adding to the comfort of the occupants. A dashboard speedometer-odometer is another necessity when touring. Driving directions in many route books simply give the measured distances between prominent landmarks in sparsely-settled country. For example, the book might read: "After passing large red farm house on left continue straight ahead a mile and a half and keep to right at fork in road." It will be seen that it is absolutely necessary to know when that mile and a half has been passed, and the odometer is the only instrument that will accurately give this information,



A Tent Can be Carried Tourists Wish

Along in Case the to Camp Out.



It is Well to Carry New Reserve Tire Shoes.

## HOW TO TOUR IN AN AUTOMOBILE.

and five or ten miles an hour out of the way is no uncommon error. The speedometer will not cost much more than the fines a country justice may impose, to say nothing of the trouble and delay occasioned by arrest. Besides this, there is a great deal of truth in the statement, "It's nice to know how fast you go," and it is often fascinating to see the little needle on the

up in separate bags liberally sprinkled with French chalk, in order that they may not become chafed and so be rendered unfit for use.

An experienced tourist is not ready to start until the car is equipped with a full set of tools, extra valves, valve springs, spark plugs, and such small moving parts of the engine as are likely to wear quickly or break easily. Of course, this list will differ with each make of car. In machines that are chain driven, extra links of chain are carried in the toolbox. A jack, tire tools, and full tire repair kit are, of course, essential. In mountain touring it is necessary to have non-skid chains, which must be used when coming down long hills slippery with mud after a heavy rain. The car, unless equipped with these, may skid and become unmanageable. In the early days rope was tied around the rear wheels to give them traction, but the newer and more serviceable tire chains or non-skid treads have taken its place and made driving on slippery asphalt or "greasy" country roads much safer. Protection of the car and its occupants from mud and water has been looked after mostly by the manufacturer before the car left the factory. Cape tops and folding glass fronts do much to keep the car dry and comfortable in rainy weather. The machinery is also protected from mud and water by metal casings. It is advisable, however, to have mackintosh covers for the lamps when touring, so as to avoid the need of continual cleaning and polishing, and if the magneto is under the bonnet where rain may possibly reach the connections, they should be protected with a rubber arrangement suitable for that purpose. Many manufacturers neglect to furnish this, and as a consequence their cars have been stalled in wet weather

by water getting into the magneto and short-circuiting it. The greatest care should be taken to keep water away from all the electrical parts of the machine.

It is possible, of course, to make a tent part of the equipment, but this will scarcely be used unless the party intends to camp out for the night. The automobile of to-day has such a wide radius of action by




reason of its high speed that this is seldom necessary, as it is nearly always possible to reach a town or large city by night. It is best to have the car equipped with good headlights and a reliable generator or gas tank, as it sometimes becomes necessary to do night riding in a strange country. Even with good lamps it is never safe to drive faster than twenty miles an hour at night on roads with which one is not familiar, as danger can arise in an instant. The machine should always be kept under perfect control; half of the accidents that occur are due to careless driving.

Among the miscellaneous items that are needed and which come in very handy are a collapsible gasoline bucket with chamols strainer, collapsible water bucket, ammeter and voltmeter for testing the batteries, small electric flashlight to examine the car at night in the event of accident, and a dash clock.

Most cars of to-day have plenty of carrying and storage room. The extra tires are usually strapped to the running board with special holders. Inner tubes may be stored in the space under the rear seats. Extra boxes on the running board will provide a place for carrying tools, while a metal trunk rack fitted with leather auto trunks, that are dustproof and waterproof, will serve for baggage.

The modern touring car, properly equipped, is capable of railroad speed and will take a party safely across country, up hill and down, in rain or shine, with more pleasure than can be derived from any other method of transportation. The man who owns his automobile has his private car as luxurious as a Pullman, with all the roads of the country as his right



A Handy Refreshment Kit for the Tourist.

tourist who really wants to see the country through which he is passing and to enjoy a sensible ride rather than a mad dash against time, would do well to plan his schedule on the basis of covering twenty miles an hour—or less, if he does not have a high-powered car. This would be slow on the




A Good Spot for Luncheon.

of way and no schedule other than that fixed by his own fancy and convenience.

The writer has always found it preferable to lay out the route intended to be followed. He has also found it a convenient practice to have a leather case made with a celluloid front in which the road directions can be placed. The map or directions can be read through the celluloid, which, however, protects them in case of rain. The easiest way to get along when asking road directions of natives in various towns is to know the name of the next following town and then ask the best road to it, if the road book directions are not explicit. For instance, before starting on a trip I generally take a map of the country through which I am going to travel and ascertain the various small towns through which I have to pass. These are listed, and as I proceed I inquire the way from one to another. This method has been found satisfactory, for when one asks the road directions to the larger cities, which may be ten, twenty, or more miles apart, it is difficult to find anyone who can direct you properly, but any boy or girl can tell you the best road to the next town, which will probably be from three to five miles away.

Having selected a route that you wish to travel, it is well to make out a time schedule and try to follow it, making due allowance in advance for delays en route and for the time that will be spent in viewing the scenery and points of interest.

You may have a 50-horse-power car, capable of a mile a minute speed, but if you are going to use the car for touring and expect to get any pleasure out of the tour, it would be better to have the machine geared down to forty miles an hour, so that it will have additional hill-climbing power. It is not the car that can go fastest on the level that can cover the greatest distance in a day, but rather the machine that is consistent in its performance and keeps "plugging" along, up hill and down, hour in and hour out, and always drawing steadily toward its destination. The



A Cape Top and Waterproof Protector are Indispensable.

smooth, level roads, but where the country is rolling, an average of twenty miles an hour is a good one, and to maintain it the car will be going at twenty-five and even thirty miles at many places. Besides, twenty miles is the legal limit in most States. Connecticut's new law, however, abolishes the speed limit but makes arrest possible for reckless driving if one travels over twenty-five miles an hour.

It is safe to presume that every motorist seeks to get as much pleasure and comfort out of touring as possible. The States of New York, New Jersey, Pennsyl-


vania, Connecticut, Rhode Island, Massachusetts, Vermont, New Hampshire, and Maine offer not only the most beautiful and varied scenery but the finest of roads. One particularly beautiful route which I have had the pleasure of taking leads from New York city up along the west side of the Hudson River to Newburg and Pine Hill, N. Y., and then to Binghamton, Bath, and Buffalo, whence last year's Glidden Tour route may be followed to Rochester, Syracuse, Utica, Albany, Saratoga, and Lake Champlain, N. Y.; Three Rivers, Montreal, and Quebec, Canada; Jackman, Maine; Rangeley Lakes, and then to Bretton Wood in the famous White Mountains of New Hampshire. The roads, with the exception of some stretches in Canada, are good. The return journey may be made by the way of Concord, N. H.; Boston, Worcester, and Springfield, Mass.; then to Lenox in the Berkshire Hills, down through the beautiful Housatonic Valley, across to Poughkeepsie, and down along the east shore of the Hudson River to New York. This route can be considerably shortened and many bad roads avoided by following directly up the west side of the river from Newburg through Kingston, Albany, Schenectady, Saratoga, Glens Falls, Ticonderoga, and Plattsburg to Montreal.

Taking a trip like this, which is one of the most attractive in point of scenic grandeur in the eastern United States, the itinerary can be laid out so that each day's run can be made easily and comfortably, allowing time for a noonday stop for luncheon, and confining the riding to daylight. The shorter trip could be made with ease in from two to three weeks, allowing plenty of opportunity to jog along easily, rest each Sunday, and enjoy the tour without hurry or bustle.

#### Palimpsest Brasses.

The reformation in England during the sixteenth century, and the wave of puritanism which followed, resulted in the destruction of much church furniture and ornament—in many cases amounting to complete plundering or destruction of whatever was valuable. Among other things memorial brasses were often stripped from old tombs, and it has been thought that this was due to general dislike to the form of record. But lately a number of palimpsest—or used over—brasses have been found in English churches, and their occurrence suggests that the destruction of old brasses did not follow religious scruples; but that the brass was taken up and sold, often to be turned over and the reverse side engraved in memory of some person recently buried. As the brasses are usually engraved with an effigy of the deceased person, and cut to the shape of the engraving, it would not always be possible to alter an ancient memorial; but often it could be done. A rarer form of adaptation was to use the brass without reversal, adapting the ancient effigy to the requirements of the time, crests or incongruous attire being cut away, and new details worked in to take their place.

In splicing a wire rope experience has shown that the efficiency of a splice depends on its length, the larger the rope the longer the splice required. In ordinary splicing of a 3/4-inch rope, the length of the splice should not be less than 20 feet, for a 1-inch rope it should be 30 feet, and for rope over 1 1/4 inches in diameter it should be 40 feet.




Cape Top and Folding Glass Fronts do Much to Keep the Car Dry and Comfortable in Rainy Weather.



## NOVELTIES

## MOTOR CAR HEATER.

In cold weather the automobilist must wrap himself up into an unrecognizable bundle of fur in order to endure the chilled blasts produced by the rapid travel of his car, while beneath him is an engine that lives



HEATER FOR MOTOR CARS.

on fire, that is continually spitting forth hot gases, and that requires special appliances to prevent it from growing excessively hot. The incongruity of the situation has struck many a one, and efforts have been made to utilize the surplus heat of the engine to warm the occupants of the car. One method is to conduct the hot water from the water jacket to coils in the tonneau, and another method is to use the exhaust gases in a similar way. The accompanying engraving illustrates the latest development along this line. A jacket is fitted around the muffler, forming a hot-air chamber. The outside air is admitted into this chamber through a port in the forward end of the jacket, while at the opposite end the chamber communicates with a pipe that leads to a register in the floor of the car. The motion of the automobile provides the necessary draft, and the cold air entering the chamber is heated by the muffler, after which it passes through the register into the body of the car. When the register is closed, a shutter is opened, which permits the heated air to pass into the outside atmosphere. A heater of this class is best adapted for use in a closed car, although it can be used with some benefit in an open car. The makers claim to have heated a closed car with one of these heaters from a temperature close to zero up to 60 deg. F., in a few minutes.

## AN AUTOMOBILE USED AS A HOISTING ENGINE.

The novel use of an automobile shown in the accompanying illustration is but one more of the utilitarian purposes which such a machine can be made to carry out. The picture shows a standard double-opposed-cylinder, shaft-drive Maxwell runabout, one of the rear wheels of which has been removed and replaced by a windlass. The machine is being used as a hoisting engine for the purpose of raising men and materials to the upper story of the factory. This expeditious way of getting material directly into the building at the proper floor served to give the little car a very strenuous test, as the power had to be transmitted through the spur-gear differential, which was constantly in action while the windlass was turning, since the other wheel remained stationary upon the ground. Needless to state, the hoisting was done upon the low-speed gear, which also received a thorough testing.


## AUTOMATIC SPEED GOVERNOR.

It quite often happens that the owner of an automobile who has every intention of obeying the speed laws is brought into court simply because his chauffeur has exceeded instructions. It is such a temptation to put on a little more speed than is allowed and the excess will hardly be noticed by the owner unless his eye is on the speedometer. Sometimes, too, the driver will unconsciously increase the pace of the machine because, after riding for some time, the same speed seems slower than it did at the beginning of the run. As a safeguard against such violations of the law an automatic speed governor has been devised which places the control of the machine directly in the hands of the man who is held responsible for its running. With this device the owner can set his machine to run at a predetermined speed and it will then be impossible for this speed to be exceeded.

The accompanying diagram illustrates the device and shows how it is operated. At A is a speedometer of standard type which is electrically connected with a circuit-breaker, B, through the switch, C. The latter is provided with five or more contacts respectively marked 10, 15, 20, etc., to indicate the miles per hour at which the machine is set to run. The pointer of the switch may be turned to any one of these contacts. If, for instance, it be set at 15 miles, the machine may run at any speed up to 15 miles, but when this speed is reached the speedometer will automatically close the circuit through the switch contact 15 to the circuit-breaker B. This actuates the circuit-breaker through which passes the current to the primary of the induction coil, and thus cuts off the ignition current and shuts off the power. Another method is to have the circuit-breaker operate an

## THE AUTO-SLIP ARCHIMÈDE—A PORTABLE APPARATUS FOR LIFTING AUTOMOBILES FOR EXAMINATION AND REPAIR.

A French patent has been granted to E. Huchet, of Nantes, for an apparatus called the "Auto-Slip Archimède," which is designed to facilitate the inspection,



AN AUTOMATIC SPEED GOVERNOR.

cleaning and repairing of automobiles. As will be seen from the illustrations, the device consists essentially of two wooden rails, shod and flanged with iron, which turn on bearings in two troughs or hollow tracks that are bolted to three cross pieces.

In the middle of the first cross piece there is a winch which is operated by a tangent screw and crank. The front ends of the rails are connected by a tie-rod, and the steel cable by which the car is drawn up on the rails passes over a pulley, carried by this tie-rod. One end of the cable is attached to a hook on a winch, the other to a sort of whiffletree, which is

fastened securely to the axle of the car by two straps. Either axle may be used, but it is best to select the more heavily loaded axle.

The apparatus is portable and can be packed in a small space, as shown in Fig. 1. To reduce it to this form it is only necessary to take off the three cross pieces and the tie rod, and lay them parallel with the rails, each of which remains pivoted in its trough. Each end of the cross pieces and tie rod has three bolt holes, by means of which the width of the auto-slip can be adjusted to a car of any age, from 1.20 to 1.40 meters (46 1/4 to 55 inches).

The nuts of the bolts have wings, and can be screwed on by hand. The parts having been assembled in this manner, props or wedges are placed under the front or short ends of the rails, and the car (with its lighter end in advance) is hauled up on the rails until it strikes the hoppers. The brakes of the car are then set firmly and all four wheels are strapped securely to the rails, care being taken to make a turn of each strap about a spoke. Then, the wedges having been removed, the continued operation of the winch has the effect of tipping the rails and the car, which can thus be placed in the most advantageous position for the examination and repair of any part of the chassis or mechanism. The wedges may be used, also, to support the rear or longer ends of the rails, as indicated in Figs. 3 and 2.

It is preferable, however, to attach the cable to the heavier end of the car and to stop hauling when the vehicle has nearly reached the position of equilibrium. In this method no wedges are required, and the car

(Continued on page 339.)



THE NOVEL USE OF A MAXWELL RUNABOUT AS A HOISTING ENGINE.

electrically-controlled valve for shutting off the gas to the engine, when the car exceeds the speed at which the controlling switch was set. If the pointer on the controlling switch be set at an intermediate position, the device will impose no limits whatever on the speed of the car. In use the switch may be located within reach of the occupant of the tonneau or limousine, giving him entire control of the speed at which the vehicle may be operated and thereby permitting him to curb the recklessness of the chauffeur. By placing the control of the speed of a car entirely in the owner's hands, this device should add to the safety of those who employ chauffeurs.



Fig. 1.—The Auto-Slip packed for transportation.



Fig. 2.—The Auto-Slip balanced horizontally to determine the position of equilibrium.



Fig. 3.—The Auto-Slip tipped to its maximum inclination.



Fig. 4.—The car leaving the Auto-Slip.

THE "AUTO-SLIP"—A NEW PORTABLE DEVICE FOR USE IN REPAIRING A MOTOR CAR.





**Model G**  
**\$2,000**  
**Four-Cylinder—25 h. p.**

Distinctively "Cadillac" Throughout—  
**Model G**

# CADILLAC

**1908**

**This and All Models Now Ready**

Judge Model G by performance, not price. On track, road and hill its superiority over cars of twice its price and thrice its rated power has been repeatedly demonstrated. There is noticeable simplicity in its design, with unprecedented efficiency at every point—speedy, powerful, flexible, silent, sensitive. Material and workmanship distinctively "Cadillac" throughout—a guarantee of the best in motor car construction. Has endurance to the limit of mechanical possibility.

Twenty-five horse power (A. L. A. M. rating); sliding gear transmission; shaft drive; 100-inch wheel base; surprising speed capabilities. \$2,000 f. o. b. factory. Described in catalog G 47.


Among the other Cadillac winners are the sturdy single-cylinder cars (Model S, Runabout, \$850 and Model T, Touring Car, \$1,000) and the luxurious four-cylinder Model H. The smaller types, as dependable and carefully built as ever, now have increased wheel base and longer rear springs, greatly adding to their easy riding qualities. Described in catalog T 47.

### The Truth about the Automobile and What it Costs to Maintain One

This is the title of a 64-page booklet compiled from sworn statements of a large number of users of single cylinder Cadillacs. Gives facts and figures which buyers want to know. Mailed free if you ask for Booklet No. 47.

Model H is an example of exclusive automobile designing and careful execution. Possesses that quietness, smoothness, abundance of reserve energy and luxury of riding which other makers strive to accomplish by a greater number of cylinders with consequent complications. A comparative demonstration will prove this. Thirty horse power, capable of 50 miles an hour. \$2,500 f. o. b. factory. Described in catalog H 47.

CADILLAC MOTOR CAR CO., Member A. L. A. M., Detroit, Mich.



**Model T**  
 10 H. P. Touring Car  
**\$1,000**



**Model H**  
**\$2,500**  
 Four-Cylinder—30 H. P.



**Model S**  
 10 H. P. Runabout  
**\$850**

# A NEW MUSICAL INSTRUMENT WHICH PRODUCES VIOLIN EFFECTS.

BY LOUIS Z. STELLMANN.

It is rather difficult to classify the musical instrument shown in the accompanying engravings. Like a cabinet organ it is played by operating a pedal, but as it is a stringed instrument it has no bellows. Like a guitar it is provided with strings of catgut stretched over a fretboard, but the strings instead of being picked by hand are vibrated by means of an endless moving tape. Probably its nearest analogue is to be found in the ancient hurdy-gurdy, the predecessor of the viola, which while similar to a violin in other respects, was played by means of a revolving wheel instead of a bow.

The harmochord, as the new instrument is called, was invented by Prof. Ferdinand Freytag, of San Francisco, with a view to producing violin effects in a simple manner. The instrument is provided with five strings stretched over a sounding board. The sounding board is mounted on a stand in the lower part of which is the operating pedal. By means of a series of pulleys above and below the strings an endless tape is led either up or down in close proximity to each string. This system of pulleys is set in motion by the pedal and the speed of travel of the tape is thus directly under the operator's control. Above the sounding board is a series of rollers which bear against the endless tape near the strings. These rollers are connected to a set of selecting keys at the right-hand side of the sounding board. There are five of these keys, and they serve to select the string which is to be sounded. When a key is depressed it causes its roller to press the tape against the corresponding string. The string is thus vibrated in a manner similar to the vibration produced by means of a bow. Several strings may be vibrated at the same time to permit of playing chords. The instrument is provided with a fretboard which assists the beginner in fingering the strings.

The quality of the tone produced by the harmochord can be varied by regulating the speed of the tape and the degree of pressure applied to the keys. To be sure it will produce only "straight bowing" effects, but its range is greater than that of the violin. The strings are tuned in the following order, beginning with the highest tone: E, A, D, F, and A. Its scope is four and a half octaves, and in its lower notes it resembles a cello. The inventor claims that with this instrument any one musically inclined may learn to produce violin effects with a proficiency and finish that would require many years of practice on the violin.

## The Introduction of Lapland Reindeer into Labrador.

BY D. W. PROWSE.

Over the whole vast peninsula of Labrador both white men and the Eskimo have only one domestic animal, the Eskimo dog. Its only use is for transportation in winter. Years of training have made this savage beast into an admirable sledge dog, capable of performing marvelous journeys. All the time, however, he has remained a wild animal, as savage as a wolf. Every year one hears of his murderous attacks on human beings. Last winter, on a sledge journey which was protracted by blizzards, the pack of dogs fell upon their drivers, and devoured the whole family.

For over a year Dr. Grenfell, C. M. G., head of the Deep Sea Commission of Labrador, has been hard at work promoting the introduction of the Lapland reindeer into Newfoundland and Labrador, to supplant the treacherous dogs. The reindeer will furnish the Labrador population with food, both milk and meat, and splendid warm clothing, also with the very best means of transportation in winter. Anyone who knows about Sheldon Jackson's introduction of the tame reindeer into Alaska, and the splendid results achieved in that desolate country, can have no doubt about the like results at Lab-

rador. The condition of both the country and the inhabitants is very much on a par. I have always declared that the tragedy of last winter should sound the death knell of the murderous Eskimo dog.

While the credit of this great move is due to Grenfell, it is only right that we should also give honor to those who have aided him. Foremost was the present




The Harmochord in Use.

governor of Newfoundland, Sir William Macgregor, G. C. M. G. He is well known to the world of science in connection with the School of Tropical Medicine. He took the keenest interest in the reindeer. With the assistance of the Moravian missionaries he made a collection of the Labrador mosses and lichens, so as to ascertain if they were the true indigenous food of the reindeer. There have always been wild reindeer in Labrador, and it was believed that the true reindeer moss could be found. The collection of mosses




General View, Showing the Finger Board and Selecting Keys.

was sent to Kew, the headquarters of botanical investigation for the British Empire, and the authorities there certified that it contained all the varieties of the reindeer food. To make the project a success, it was felt that a herd should be brought over, two to three hundred reindeer, with Lapland herdsmen and their families. Grenfell on his round of lectures created such enthusiasm that the necessary money was soon contributed.



Plan View, Showing the Selecting Keys and Rollers Which Press the Tape Against the Strings.



The Pedal and Pulley System for Operating the Endless Tape.

A NEW MUSICAL INSTRUMENT WHICH PRODUCES VIOLIN EFFECTS.

Mr. Wood, secretary of the Deep Sea Commission in London, put himself in communication with correspondents in Norway, and secured a herd of three hundred then on an island off the coast. After long negotiations and hard bargaining, a steamer was chartered for £1,500 to take the deer across. Through Sheldon Jackson, a Norwegian in western America was secured who was an expert in the business of transporting the reindeer. All was going well. Nansen, the Norwegian ambassador in London, was doing all in his power to favor the project, when a difficulty cropped up that seemed for the time insurmountable. The laws of Norway prohibited the exportation of reindeer moss, and without this special food the reindeer could not possibly be carried across the Atlantic.

Wood, the secretary, was for a time in despair, but through the influence of Nansen, the King of Norway, and our Foreign Office, the difficulty was smoothed over, and Wood is now in Norway, attending to all the details of the expedition, which sails early next month. Every care has been taken to secure the very best animals. 270 are does and 30 bucks; about 25 are thoroughly trained sledge reindeer for journeys. The best and most intelligent Lapland herdsmen, with a Norwegian interpreter, have been secured, and all will be under the control of Kjellman, a Norwegian thoroughly experienced in the business.

For the future management of the herd at Labrador, advantage will be taken of Sheldon Jackson's experience in Alaska. Settlers and Eskimos will associate with the Laps, and be taught how to manage the herds. To guard the animals from possible attacks by the savage Eskimo dogs, every precaution will be taken. It will be made first of all a condition that all dogs be destroyed around the place where the herds are located, as a prime condition before distributing the tame reindeer among the inhabitants. The deer are also guarded by the Lap herdsmen and their trained dogs. The caribou, especially the bucks, are fighting animals, and can strike fierce blows with their horns and hoofs. They would be quite a match for their savage assailants. It is anticipated that the Eskimos and settlers will soon learn how to take care of the reindeer, and to appreciate the immense advantages of securing such valuable domestic animals.

## A Balloon-Sonde at 54,624 Feet Altitude.

According to an interesting report in Petermann's Mitteilungen, a balloon-sonde, or "sounding balloon," has been launched from Strasburg to a height of 16 miles. The altitude generally reached by balloons seldom exceeds 11 1/4 miles.

The phenomena as regards the temperature and moisture of air recorded during this ascension consist of a regular reduction of temperature until -62 deg. C. at a height of 9 miles, after which a regular heating through a thickness of up to 6 miles is observed in higher altitudes.

According to a note recently published by R. Donner in the Revue Scientifique, there would be a relatively hot layer, being the isothermal zone which corresponds to an altitude variable between 26,246 and 39,370 feet. There are generally in the atmosphere two main layers, which are strictly different as regards their thermal and hydrometrical properties. Whereas in the lower stratum the temperature and moisture undergo a reduction more or less rapid (according to altitude), such changes are of feeble intensity in the upper stratum, in which the atmosphere can be considered as made up of a number of thin layers, the temperatures of which would vary slightly either in one direction or another, thus determining changes in the speed and direction of winds. The lower stratum would on the contrary be affected by heavy vortices, cyclones, and atmospheric depressions.

Much trouble is caused in brazing by not using thoroughly fused borax. Dry borax does not answer, as it swells while brazing, and makes the joint porous. It should be melted in a clay or iron crucible to a clear liquid so as to drive off all water. Such borax will not swell when used for brazing.



# INDEX OF INVENTIONS

For which Letters Patent of the United States were issued for the Week Ending

October 29, 1907.

AND EACH BEARING THAT DATE

[See note at end of list about copies of these patents.]


Accordion, E. E. Brande	800,227
Accounting device, J. J. Bennett	800,614
Acid bath, carbonic, A. Zucker	800,610
Advertising device, M. Rosenfeld	800,733
Air brake, W. S. Billeby	800,543
Air brake system, L. A. Hawkins	800,364
Air brake system, G. Macleod	800,444
Air brake system, A. L. Goodkneller	800,837
Air brake system, F. H. Dukessmith, release	12,712
Air brake systems, automatic governor for, J. W. Richardson	800,731
Air brake systems, automatic warning alar	nal for, R. P. Nolan
Air compressing system, A. Sauer	800,739
Air cooler or surface, J. E. Starr	800,747
Air pressure brake, E. Krauser, release	12,710
Air ship, A. W. B. Griep	800,238
Alarm dead lock, M. Shelman	800,432
Alarm mechanism, L. Paisley	800,728
Amusement device, H. H. Fette	800,841
Animal trap, W. G. Stone	800,594
Animals from stalls, device for releasing, A. Ponkey	800,261
Arch clamp, M. Perkins	800,857
Aspirator, E. Fynchon	800,262
As, turpentine gatherer's, E. A. McKay	800,381
Back scratcher, F. J. Martin	800,250
Bag holder, L. L. Clippinger	800,691
Baling press, J. O. Maxwell	800,251
Baling press, A. Gastouguay	800,561
Battery grid, storage, R. N. Chamberlain	800,348
Bearing, journal, F. Fleming	800,629
Bed, C. H. Codere	800,772
Bed, E. J. Antoni	800,766
Bed, invalid, J. D. Birmingham	800,344
Bell ringing mechanism, W. A. Stearns	800,693
Belt fastener, N. P. Mader	800,333
Belt shifting mechanism, A. B. Gustafson	800,239
Bench, See Work bench	
Bench clamp, W. B. Bradford	800,290
Bevel, E. A. King	800,857
Bicycle boat, A. Travland	800,277
Blinder, infant's, A. Jarrett	800,784
Blinder, loose leaf, W. M. S. Miller	800,378
Blind stock, J. O. Michael	800,817
Blackboard cleaner, F. W. Wade	800,817
Block signal system, L. A. Hawkins	800,365
Block signal system, W. Daves	800,555
Block signaling system, L. H. Thelen	800,275
Blower, combined motor and hand operated, rotary, H. B. Kelper	800,247
Bobbin stripper, W. B. Leathers	800,856
Bolster, O. S. Fullin	800,654
Book clip, F. J. Mills	800,379
Bottle of hexamethyleneamine and making same, O. Mankiewicz, et al.	800,636
Boring machine, M. L. Andrew	800,223
Boring machine, E. C. Mueller	800,504
Bottle, non-refillable, R. J. Patterson	800,390
Bottle, non-refillable, A. E. Sutton	800,532
Bottle, non-refillable, E. L. Southwick	800,810
Bottle rinser and sterilizer, D. E. Shaw	800,333
Bottle stopper, J. J. Fraser	800,700
Brake actuating appliance to operate when a vehicle leaves the track in railways, G. S. Morison	800,795
Breast strap slide, N. Durand	800,234
Brick kiln, J. J. P. Casey	800,621
Brooder, S. G. Robinson, Jr.	800,295
Broom corn handling or compressing machine, J. F. Foley	800,358
Brush backs, supporting table for boring holes in, W. G. Liebig	800,313
Buckel, clam shell, J. Rogers	800,857
Buckle, K. Gluchowski	800,776
Buckles to belts or girdles, means for attaching, F. B. Montgomery	800,721
Bucles, jump seat for, G. D. Pette	800,592
Building apparatus and method of building construction, W. Peabody	800,391
Building block, W. B. Binstock	800,770
Building block and wall, W. W. Binstock	800,615
Building block making machine, E. H. Somers	800,271
Building block mold, C. J. T. Cordes	800,328
Building construction, J. Mulaney	800,380
Building ventilator, J. Benton	800,687
Bushings, tool for removing, J. L. Alpaugh	800,861
Button, collar, E. T. Atwell	800,405
Calculator, C. H. O'Connell	800,511
Calendar, W. T. Berry	800,411
Calendar, J. Ferrer	800,430
Can, See Oil can	
Canning apparatus, N. W. Tharp	800,751
Canning machine cap feeding mechanism, N. Nelson	800,509
Cane, W. Autenrieth	800,682
Car, box, C. W. Gill	800,630
Car brake, railway, E. A. Crose	800,425
Car door, R. Hall	800,339
Car door, grain, W. R. Smith	800,743
Car, dump, O. W. Meisner	800,445
Car, dumping, J. Bennett	800,613
Car, dumping, J. M. O'Kelly	800,726
Car, dumping, W. L. Phillips	800,804
Car grain door, C. E. Mapes	800,377
Car inclines safety stop or check for, Post	800,648
Car, motor, Otis & Hart	800,455
Car pusher, A. E. Brown	800,689
Car safety device, G. W. Sayre	800,831
Car stanchion, R. P. De Remer	800,831
Car step, folding, W. G. Folkner	800,429
Car wheel, Pilcher & Lemen	800,514
Car wheel, F. K. Vial	800,671
Car wheel locking attachment, tram, T. Parker	800,257
Cars, antifriction center bearing for, J. C. Barber	800,685
Carburetor, gasoline, A. Winston	800,675
Card, playing, L. Healy	800,302
Carriage, folding baby, A. B. Todd	800,534
Carrier, G. Fink	800,357
Cartridge box, multiple, H. B. Lemly	800,310
Cartridge carder, E. E. Drake	800,484
Cartridge from explosive gelatin, machine for forming a, G. P. Jones	800,307
Cartridge holder, A. L. Hockett	800,632
Chair and desk, combined, L. P. Agnew	800,472
Checking device, cigar sale, J. H. Bove	800,477
Checkrein hook, J. B. L. Brown	800,546
Cheese cutter, W. F. Kessler	800,308
Chimney valve construction, W. O. Amaler	800,763
Chuck, drill, A. J. McAllister	800,507
Cute, Langen & Carlson	800,495
Cigarette machine, S. Ragosa	800,304
Cigar, stogy, etc., A. H. Graves	800,361
Clasp, Freeman & Stevenson	800,774
Cleaning device, pneumatic, W. J. Bergena	800,542
Clock, alarm, F. Lux	800,376
Cloth cutting machine, F. J. Clark	800,419
Clothes drier, S. E. Wilson	800,673
Cutch mechanism, P. Jonsson	800,713
Coal cabinet, R. R. Faulkner	800,355
Coin counter, B. Cramer	800,626
Coke pulling apparatus, F. M. Hoag	800,305
Collar fastener, S. B. Howitt	800,367
Collar stiffener for negligee shirts, W. S. Peacock	800,250
Column, J. Lally	800,809
Column for fireproof construction, J. Lally	800,780
Combustion process, B. E. Eldred	800,488
Concrete block molding machine, J. Ingells	800,476
Concrete chimney, J. W. Rector	800,518
Concrete construction, E. Nichols	800,724
Concrete mixing machine, G. D. Schofield	800,522
Concrete pile and means for driving same, J. Stewart	800,336
Concrete walls, means for frost proofing, J. H. Walz	800,290
Condenser, J. Zellweger	800,842

## Stoddard-Dayton


### 1908 MODELS




S-G. Six-Cylinder, \$4,500  
Complete, Without Top




S-H. Runabout, \$1,700  
Complete, Without Top



S-F. Touring Car, \$2,500  
Without Top or Gas Lamp



S-K. Roadster, \$2,300



S-F. Limousine, \$3,500, complete



S-N. Landaulet, \$2,300, complete

SEND FOR 1908 CATALOG

THE DAYTON MOTOR CAR CO.  
DAYTON, OHIO, U. S. A.

## Stoddard-Dayton

Contact shoe, third rail, S. B. Stewart, Jr.	800,485
Control system, L. M. Aspinwall	800,824
Controller, H. W. Stull	800,812
Conveyer driving mechanism, H. von Harnstengel	800,488
Conveying apparatus, J. T. Cowley	800,250
Cooking utensil, J. W. Brown	800,680
Copping machine, F. Rosenheck	800,583
Core box, A. J. Baseley	800,224
Corset stay, H. M. McCormick	800,797
Cotton gin, J. Hodgkinson	800,635
Cotton picker, N. A. Gaston	800,703
Crate, knockdown, J. Follanshee	800,690
Culinary device, G. M. Smith	800,629
Cultivator, W. H. Daniel	800,481
Cultivator, L. A. Weaver	800,545
Cultivator knife attachment, corn, J. Meyer	800,580
Curtain shield, G. E. Barrett	800,280
Current apparatus, alternating, A. S. Hubbard	800,244
Curtain hanger, lacor, T. McCormick	800,250
Curtain pole ring, J. A. Rings	800,356
Curtain pole support, E. B. Pearson	800,368
Curtain stretcher clamping device, H. A. Schwarz	800,332
Curtain support, M. Keith	800,787
Cutter, rice cheese	800,505
Cycle engine, double two, W. L. Morrow	800,506
Damper attachment, J. W. Reynolds	800,506
Dental engine, J. F. Hardy	800,506
Dental engine, W. E. Hanson	800,506
Dental engine handpiece, J. F. Hardy	800,506
Dental grinding tool, steam-gauge for, F. W. Chandler	800,417
Dental impression pliers, M. A. Robbins	800,620
Electric camel, J. B. Twichell, release	12,711
Display rack, R. J. Wilcox	800,638
Door lock, pocket, J. J. Baxter	800,541
Draft equalizer, A. Bush	800,345
Draft gear, friction, I. Simpson	800,266
Draft rigging, frictional, C. A. Towson	800,754
Drawer guide, M. Rubin	800,735
Dredge cutter, suction, J. F. Orlieb	800,385
Dredging apparatus, E. B. Stoddard	800,275
Driving dog, S. W. Putnam	800,688
Dry cells, making, P. L. Meyer	800,446
Duplicating pad and holder, F. A. McCaskey	800,508
Dust removing pneumatic machines, regulating device for, J. B. Dlum	800,644
Ear muff, S. B. Wells	800,401
Egg beater, W. Ruppel	800,736
Electric currents, transformation of, T. Taylor	800,505
Electric furnace, G. Gin	800,432
Electric heater, G. E. Stevens	800,464
Electric heating fabric, W. Richmond	800,461
Electric machines, series shunt for dynamo, E. T. Mag	800,795
Electric motor, J. P. Hayes	800,780
Electric regulator, A. H. Barber	800,684
Electrical apparatus, T. W. Varley	800,685
Electrical apparatus clip, H. Krantz	800,685
Electrical distribution system, Hubbard & Turbayne	800,245
Electrical distribution system, E. Van Wagenen	800,270
Electrical distribution system, W. E. Winship	800,280
Electrical distribution system, Hubbard & Turbayne	800,300
Electrode, arc lamp, R. Fleming	800,390
Electrothermal protectors, automatic testing and resetting means for, F. R. Cook	800,554
Elevator, Pascoe & Bergen	800,800
Elevator, electrically controlled, C. T. Westlin	800,760
Engine cooling system, internal combustion, Hobart & Gore	800,300
Engines, hot head for explosive, C. L. Smalley	800,528
Engines, ignition system for explosion, R. Varley	800,601
Envelope, W. H. Hawshaw	800,393
Envelopes, G. H. Chapel, release	12,706
Eyeglass fittings, G. Moore	800,827
Excavating and filling mechanism, W. E. Laughierback	800,605
Excavators, sand and hoisting frame for, R. H. Ranch	800,433
Explosive engine, J. D. Anderson	800,611
Extensometer, W. H. Kenerson	800,716
Fastening clamp, S. J. Feinberg	800,210
Feed trough, C. W. Leonard	800,237
Fence post, metallic, C. Colvin	800,237
Fender, J. A. Sage	800,738
Ferrochromium, manufacture of, H. W. C. Arnold	800,681
Fibrous material and separating dust therefrom, apparatus for grading, blade & clearing	800,742
File, J. C. Dawson	800,420
Filling machine, F. C. H. Strasburger	800,811
Filter, Clark & Kruel	800,294
Filter submerged, G. W. Burboon	800,538
Filtering apparatus, D. J. Kelly	800,373
Fire extinguisher, G. E. Tilford	800,755
Fire extinguishing apparatus, C. E. Buel	800,415
Fire resisting curtain and channel therefor, E. H. McClood	800,447
Fishplace heater, H. D. Frisbie, Sr.	800,775
Fishing bait, artificial, E. J. Haverly	800,657
Fishing boat, C. J. Atwood	800,406
Fishing pot, C. J. Schmidt	800,474
Flue sections, means for connecting, V. C. Howe	800,710
Fluid brake, W. Heilmann	800,760
Fluid pressure brake, R. A. Farber	800,502
Fluid pressure brake, G. Westinghouse	800,964
Fluid pressure motor, S. Otis	800,453
Flushing elaters, T. Smith	800,540
Folding box, B. Rapoport	800,317
Folding box, J. T. Ferrer	800,832
Food product, J. H. Kellogg	800,371
Frame, See Picture frame	
Frequency changer, W. E. Bralley	800,412
Fuel economizer, E. B. Freeman	800,701
Furnace, T. S. Blair, Jr.	800,616
Furnace, J. & J. R. Eynon	800,698
Furnace attachment, H. F. Heer	800,445
Furnace door, C. J. F. Johnson	800,575
Gage, V. V. Hawley	800,480
Gage, J. L. Pringle	800,640
Gage attachment, automatic stop, W. A. Kramer	800,309
Game apparatus, M. Maris	800,516
Game counter, E. C. Hillier	800,241
Gas plant, E. V. Eldred	800,454
Garment clamp, J. P. Wilson	800,285
Garment hanger, F. P. Johnson	800,246
Garment hanger support, H. N. Drucker	800,233
Garment supporter, H. T. Sprague	800,744
Garter, Burton & Fuller	800,228
Gas apparatus, water, J. H. Tammis	800,814
Gas burner, blast, J. Himmendinger	800,298
Gas conduit connecting device, C. de Hoffmann	800,370
Gas cut-off, automatic, E. A. McDonough	800,589
Gas engine, W. L. Morrow	800,255
Gas engine, Powell & Norton	800,593
Gas generator, W. M. Cronin	800,225
Gas generator, acetylene, J. Magreth	800,719
Gas governor and street pressure changer, automatic, A. A. Fankes	800,471
Gas making, E. E. Eldred	800,487
Gas making apparatus, L. E. Lowe	800,687
Gas pressure regulating device, G. Daley	800,820
Gas, producing, Eldred & Ellis	800,480
Gate, C. E. Rice	800,550
Gear, change speed, C. B. King	800,401
Gear cutter, G. D. Marvin	800,310
Gelatin forms or molds, producing, A. Leitch	800,811
Glassware, machine for making hollow, S. H. Winder	800,638
Globe manipulator, J. Gaynor	800,836
Grading machine, C. D. Edwards	800,254
Grading machine, G. W. Barnett	800,628
Grain door, H. H. Boenker	800,412
Grain drill cleaner, R. M. Richards	800,720
Grain milling apparatus, E. E. Chamberlain	800,622
Grass catcher, J. H. Coult	800,349
Grinder, mower knife and tool, J. M. Ross	800,734
Hammer nail holding attachment, G. W. Puffer	800,615
Hand-hole cover, R. Park	800,427
Harrow attachment, draft, W. E. Perry	800,805
Harrow attachment, E. Schotts	800,600
Harrow, pulverizer, and drag, combination, A. D. Uley	800,756
Harrow tooth, L. W. Fild	800,360

## ELECTRIC INCUBATORS.

One of the latest applications of electricity is in the construction of electric incubators and poultry-breeding apparatus. While artificial processes have for some time past been in use, in connection with poultry breeding, they have been based on the use of compartments heated by gas, alcohol, or petroleum. The apparatus here described is, however, heated and regulated directly by electric current as derived from the mains, any complicated accessories being dispensed with.

The electric incubator shown in Figs. 1 and 2 has been designed by Mr. G. Kesel, of Kempten, Bavaria. In Fig. 2, which shows the apparatus opened, a wire mesh may be seen on the lid. Back of this the main radiator is arranged which takes up the whole of the lid, and which is worked only as long as the apparatus is kept closed. As the heating wires are strung out uniformly throughout the lid, all eggs are submitted to the same heating effect, regardless of their location in the drawer. The main heating body in the lid of the apparatus is assisted by auxiliary radiators placed on the bottom of the outfit, which are continuously energized even while the apparatus is opened, maintaining the hatching compartment at a uniform temperature of about 30 deg. C. (86 deg. F.) and preheating the air entering the hatching compartment.

The heating coils of the apparatus are energized as soon as the contact is connected to the mains. The temperature is controlled by the automatic switch of the main radiator and the heat regulator in the hatching compartment. Supposing a temperature of 39.5 deg. C. (103 deg. F.) to be required in the hatching compartment, the apparatus is heated until this temperature is recorded by the thermometer, after which the contact is thrown out by turning a screw fitted outside the apparatus. After a little adjusting of the screw a point will be reached at which the temperature in the hatching compartment is kept accurately at 39.5 deg. C. (103 deg. F.) when even during several months' operation fluctuations in the hatching temperature will be less than one-tenth of a degree, the mercury of the thermometer remaining most constantly at the point of adjustment. Whether the adjustment has been properly made, may be determined by the uniform ticking motion of the switch. This uniformity of temperature is obtained by the automatic switching in and out of the main radiator in the lid of the apparatus. While the auxiliary radiators, as above mentioned, will raise the apparatus to a temperature of about 86 deg. F., the main radiator supplies the surplus heat, being thrown alternately in and out of circuit by means of the switch at a rate depending on the temperature.

One of the most difficult features of artificial poultry breeding is a proper supply of fresh air. In the electrical incubator air is supplied from underneath, the entering fresh air coming in contact with the eggs after being properly pre-heated by special radiators. This ventilation is controlled by opening to a variable extent the lateral slides fixed at the top of the apparatus. When working in a heated room, the slides should be obviously opened to a greater extent than in a cold room. It should be remembered that ventilation plays the role of maintaining the life of the germ. While an ample supply of fresh air therefore is extremely valuable for the development of the germ, any excess of ventilation will prove detrimental; in fact, the surplus air will exert a drying action on the contents of the eggs. Nevertheless, it will be found



Fig. 1.—The Incubator Closed and in Operation.



Fig. 2.—The Apparatus Open, Showing the Manner of Holding the Eggs.

more advantageous to have too much ventilation than to risk killing the germ by stifling.

The incubator is provided with two thermometers, one of which is arranged in front in the drawer containing the eggs, and the other in the interior of the hatching compartment. The former is observed




Fig. 3.—The Apparatus Used as a Brooder After the Birds are Hatched.

through a glass window from the front, when the apparatus is closed, while the other thermometer is read from above through the double window in the lid of the apparatus. Both thermometers can be placed at the same height; and after adjusting for the desired temperature by means of the front thermometer, the

other thermometer is displaced until the temperature recorded by it is exactly the same. A better practice, however, is to so arrange the second thermometer as to have it record one degree more than the front thermometer. The second thermometer, located in the hatching compartment, serves as an emergency safeguard. Should the heat regulator fail to work, this thermometer will regulate the temperature in its turn by throwing the main radiator out of circuit.

A much-discussed point in connection with artificial poultry breeding is the supply of moisture. The constructor of this apparatus recommends using no artificial supply of moisture, the necessary amount being always provided by a proper ventilation. Nevertheless, the construction of the apparatus allows of any amount of moisture being supplied from outside, the degree of moisture being read from a special hygrometer.

Below the contact supplying the heating current, another contact box has been arranged for an incandescent lamp, which apart from lighting the apparatus, whenever required, serves for observing the actual condition of the eggs, any motion of the embryo being readily watched in the semi-transparent eggs, while foreign bodies in infertile eggs are detected. The operation of the incubator is so uniform that the time of hatching of all eggs of a given batch is about the same, the maximum difference being two to three days.

As soon as they are hatched the chicks are moved to a compartment in which they are kept for 24 hours without food. From this compartment they are taken to the electric breeding apparatus represented in Fig. 3. This is separated into two portions, one of which serves as a sleeping chamber and the other as a feeding room.

The most important feature of the electric breeding apparatus is the heating plant, which can readily be connected to the ordinary lighting circuit. The radiator of the sleeping compartment is fitted to the ceiling, and is so designed as to produce a uniform radiation of heat from the ceiling, thus preventing any crowding of the chickens. Three different degrees of heat can be obtained by actuating a switch, the temperature being made to decrease from day to day. The requisite heat depends on the number of chicks contained in the apparatus.

In the United States inventors have been successfully at work in this direction, and electric installations may be obtained to fit into existing oil incubators. A very ingenious adaptation has been worked out with a view to illustrate the hatching of chickens in nature classes or schools. This device is known as the "Electrehen"; an oval glass incubator, operated by the heat of an electric incandescent lamp, controlled by a delicate and sensitive thermostat which holds the temperature steadily at 103 deg. F.

The "Electrehen" has a neat metal base of ornamental design, with nickel-plate, oxidized copper, or gun-metal finish, the base forming the brooder for the newly-hatched chicks. A drawer is provided, which is partly drawn from the base, and the chicks run about in the fenced inclosure, about three or four feet square, making a most interesting exhibit.

This most attractive device is easily connected to any electric lighting circuit, either alternating or direct current, of 110 volts, by the usual flexible cord and plug. It is only necessary to turn the button, and sufficient heat is provided for hatching and brooding the chicks.




Fig. 4.—The "Electrehen," Showing Chicks Under Glass Dome.




Fig. 5.—Eggs and Newly-Hatched Chicks in the "Electrehen."



Harvester, beet, Hellig & Reed, release.....	12,708
Harvester, counting mechanism for grain, W. H. Crane.....	800,424
Hat, coat, and umbrella rack, G. W. Hartman.....	800,779
Headlight machine, H. A. Powers.....	800,516
Headlight adjusting device, F. B. Cobham.....	800,549
Headlight or lantern, F. P. Cobham.....	800,548
Heat, reducing compounds with electrically developed, F. J. Tuse.....	800,276
Heat-resisting composition, G. De Angelis.....	800,694
Heel, boot and shoe, W. G. Anderson.....	800,764
Hinge, C. W. Cook.....	800,553
Hinge, invisible, E. M. Kluge.....	800,717
Hinge, portable, J. D. Connelly.....	800,743
Hoof expanding pad, C. D. McAfee.....	800,642
Horsehoe, G. M. Green.....	800,838
Horsehoe calk, J. M. McKnight.....	800,599
Horsehoe calk, removable, A. E. Rehrig.....	800,330
Hose or pipe coupling, C. F. Snyder.....	800,602
Hose supporter, E. Pearl.....	800,457
Hub, sand-proof disk, E. L. Black.....	800,226
Hydrosulfite mixture, stable dry, A. Blackemberger.....	800,055
Hygienic cartridge battery, Thompson & Martini.....	800,509
Incubator, J. W. Russell.....	800,452
Incubator alarm attachment, Benedict & Hutcheson.....	800,409
Index, R. C. Russell.....	800,421
Index card holder, E. Burns.....	800,020
Indicator, See Work-locating Indicator.....	
Insect trap, J. E. De Haas.....	800,556
Insulated joint, F. E. Kinsman.....	800,788
Insulating coupling, W. Farrester.....	800,410
Insulating material and manufacturing same, R. Muller.....	800,321
Insulator, strain, A. Anderson.....	800,403
Journal box and lid, F. C. Foreman.....	800,903
Label affixing machine, C. H. Boston.....	800,545
Lacing, shoe, Caldwell & Drew.....	800,346
Lamp filaments to the stem wires, apparatus for cementing electric, J. Russell.....	800,318
Lamp, hydrocarbon, J. Landsiedel.....	800,440
Lamp mantle holder, J. M. Simmons.....	800,061
Lamps, multiple socket for incandescent, F. J. Russell.....	800,737
Land roller, J. Wolfinger.....	800,676
Lantern, electric, F. P. Cobham.....	800,550
Lathe, double arbor, D. Bacon.....	800,802
Launchee, adjustable top for, W. F. Walter.....	800,390
Laundry iron, J. R. Adams.....	800,679
Letter box, W. H. Hunsberr.....	800,844
Lineman's safety device, W. F. Newton.....	800,382
Liquid cooler, J. D. Spencer.....	800,560
Liquid dispensing vessel, H. Waechter.....	800,535
Liquids from vapors, apparatus for separating, Aitken & Mackie.....	800,090
Loading apparatus, F. M. Hogg.....	800,533
Lock, W. H. Taylor.....	800,805
Locomotive boiler, S. A. Reeve.....	800,804
Locomotive tank siphon, C. W. La Rue.....	800,854
Loom shuttle, W. L. H. Spencer.....	800,778
Loom stop-motion mechanism, failer for, Whitney & Eubank.....	800,819
Loom, self-replenishing, B. F. McGuinness.....	800,644
Lubricant controlling device, auxiliary automatic, Oelmann & Strub.....	800,383
Mail bag catcher, J. T. Hindman.....	800,304
Mail bags along railway lines, device for delivering, A. F. Martel.....	800,791
Mail carrier, A. & C. W. McIntire.....	800,448
Mangle roll covering, J. H. Hunt.....	800,672
Marker, pie, C. Sullivan.....	800,696
Marking apparatus, credit, J. J. Lehigh.....	800,858
Match-making machine, dipping device, Moreland & Landvatter.....	800,641
Measure, tailor's tape, B. Ricciardi.....	800,264
Measuring and weighing machine, E. G. Staudt.....	800,335
Measuring speed of rotation, apparatus for, W. D. Litchfield.....	800,442
Metal ware, machine for scouring and scratch-brushing flat, D. F. Broderick.....	800,478
Metallic powders, preparing, W. F. McNulty.....	800,591
Micrometer gage, limit, L. C. Woerner.....	800,702
Micrometer screw gage, Ellhauser & Ruckert.....	800,607
Mining machine, coal, W. Yeatts.....	800,600
Molding machine, crayon, Daniel & Keller.....	800,602
Money box, M. J. Ogden.....	800,384
Motor control, E. R. Carichoff.....	800,220
Motor control system, M. W. Day.....	800,582
Motor controller, W. Fiedler.....	800,582
Motor regulating device, W. C. Runge.....	800,331
Mower, lawn, A. B. Case.....	800,771
Mowing machine, W. Oster.....	800,790
Music playing instrument, autoneumatic, W. B. Crippen.....	800,480
Music playing instrument, autoneumatic, W. A. Watson.....	800,815
Musical instrument, wind, F. A. Buescher.....	800,619
Musical instruments, mechanically controlled solo-accent device for mechanical, P. Wuest, Jr.....	800,678
Musical players, pneumatic motor for use in automatic, G. P. Brand.....	800,414
Necktie fastener, Balla & Stein.....	800,683
Nest, trap, H. P. Rankin.....	800,243
Nut lock, B. A. Doty.....	800,696
Odorizer, B. Schneider.....	800,740
Oil can, S. E. Friend.....	800,702
Open hearth furnace, T. S. Blair, Jr.....	800,617
One concentrating table, F. H. Shepard.....	800,860
One concentrator, feed box for, W. & F. S. Card.....	800,303
One toaster, A. J. Garver.....	800,300
Ores, cyanid treatment of, A. Adair.....	800,287
Organ blowing apparatus, I. H. Spencer.....	800,808
Organ feeding machine, L. M. Nielsen.....	800,725
Packaging machine, E. Stanley.....	800,664
Packing case, A. R. Speer.....	800,463
Packing, metric, W. H. Leis.....	800,374
Packing, stuffing box metallic, J. C. W. Weber.....	800,536
Padlock, A. F. Bardwell.....	800,475
Paper, protecting commercial, E. E. Angell.....	800,823
Plane, combined automatic and manually operated, M. Clark.....	800,290
Pick, Olson & Boals.....	800,727
Picker, See Cotton picker.....	
Picture frame, Kasahn & Schaaf.....	800,786
Pin setter, ruby, C. A. Sloan.....	800,509
Pipe coupling, train, Myers & Stevens.....	800,506
Pipe fitting, A. C. Walworth, Jr.....	800,540
Pipe seaming machine, C. H. Gervey.....	800,704
Plane, J. H. Shaw.....	800,207
Plaster slabs for building, etc., making wooden core, G. S. Mayhew.....	800,628
Platen shift mechanism, G. W. Campbell.....	800,347
Plow barrow attachment, J. C. Foote.....	800,834
Plow, reversible disk, Mallory & Slaughter.....	800,499
Poultry fountain, M. L. Watson.....	800,400
Plow standard, adjustable, W. P. Wigley.....	800,672
Plows, caster controller for wheeled, W. L. Paul.....	800,258
Pneumatic despatch table apparatus, C. F. Steadman.....	800,338
Poke, animal, G. R. Munford.....	800,722
Post driving machine, W. W. Turner.....	800,815
Post lid, E. E. Spottswood.....	800,746
Poultry fountain, M. L. Watson.....	800,400
Power transmitting device, E. W. Harrell.....	800,820
Preserving and canning device, S. W. Harrell.....	800,564
Pressing machine, J. Lehr.....	800,587
Printing mechanism, F. G. Jahn.....	800,783
Printing press, A. K. Taylor.....	800,697
Printing press, ink fountain, S. G. Goss.....	800,237
Printing presses, automatic ink font for platen, Ben & Martin.....	800,863
Printing presses and similar machines, feed mechanism for, G. W. Prouty.....	800,320
Printing presses or the like, detector for, A. Oertel.....	800,324
Protector for ears, forehead, and eyes, I. Seitzman.....	800,741
Pulley, J. L. Coleman.....	800,527
Pump, A. Pappan.....	800,387
Pump, T. Foy.....	800,550
Pump, measuring, C. S. Jones.....	800,246
Pump, measuring, F. C. Wilson.....	800,460
Pump, pneumatic, D. J. Holden.....	800,781
Punching machine and feeding mechanism therefor, F. C. B. Page.....	800,326
Pyrometer, C. B. Thwing.....	800,008
Radiator, V. Loring.....	800,577
Radiator, C. Wright.....	800,822
Railway brake mechanism, inclined, S. E. Jackson.....	800,840
Railway frog, T. F. Donahoe.....	800,095
Railway rail joint, T. B. Check.....	800,470

## To the Technically Well Informed Man

The New Model D, 24 H. P.


# Maxwell

\$1750

presents the only logical solution of the problem of a four-cylinder car at moderate price.

What this car is and does, as to durability, economy and performance, is indicated by the fact that it is an exact duplicate in mechanical principles of the famous four-cylinder "Maxwell" which won the Deming Trophy in 1906, and served as pilot in the 1907 Glidden Tour.

Those "Maxwell" owners who have wanted a higher-powered car, and those to whom a four-cylinder car has heretofore seemed an extravagant luxury, will rejoice at the arrival of this new model.



FOUR-CYLINDER 24 H. P.

### SPECIFICATIONS

<b>MOTOR</b> —Four-cylinder vertical, cylinders cast separately.	<b>SPRINGS</b> —Semi-elliptic.
<b>TRANSMISSION</b> —Sliding gear, progressive type.	<b>CARBURETOR</b> —Float-feed, giving perfect mixture at all speeds.
<b>CLUTCH</b> —Multiple disc.	<b>COOLING</b> —The "Maxwell" thermo-siphon system of water-cooling.
<b>DRIVE</b> —Shaft.	<b>BODIES</b> —Sheet metal, upholstered with fine quality leather and hair.
<b>FRAME</b> —Pressed steel, channel section.	<b>WHEEL-BASE</b> —96 inches.
<b>LUBRICATION</b> —Positive forced-feed.	<b>WEIGHT</b> —2100 pounds.
<b>IGNITION</b> —Jump-spark; current supplied by dry cells and storage battery.	<b>EQUIPMENT</b> —Three oil lamps, tools, horn, etc.

This car is the result of the efforts and genius of Mr. J. D. Maxwell, whose pre-eminence as a designer of gasoline cars is acknowledged throughout the automobile world. Mr. Maxwell spent the entire past year in perfecting this model, and continually refused, in the face of a strong demand, to allow it to be put on the market until it had met with his approval in every detail.

I want you to prove this car to yourself.

Write to me personally and I will see that you get a demonstration. Address Dept. 42.

*Benj. Briscoe* President.

**MAXWELL-BRISCOE MOTOR CO.**

70 Spring Street, Tarrytown, N. Y.

Factories: CHICAGO, ILL., PAWTUCKET, R. I., NEW CASTLE, IND.

Railway safety device, inclined S. E. Jackson.....	800,847
Railway signal, C. W. A. Turner.....	800,407
Railway signal, electrically operated, H. J. Jones.....	800,785
Railway signaling, H. B. Struble.....	800,551
Railway system, electric, W. R. Foster.....	800,430
Railway tie, M. J. Nolan.....	800,045
Railway tie and rail fastening, G. W. Hitt.....	800,732
Railway train safety mechanism, Doyle.....	800,537
Railway trains, automatic apparatus for stopping moving, J. T. Thompson.....	800,507
Railway trains, controlling apparatus for, J. T. Thompson.....	800,508
Razor blade holder, safety, W. N. Ward.....	800,757
Razor, safety, J. W. Leslie.....	800,570
Receptacle, J. J. Steinhardt.....	800,748
Receptacle and closure therefor, C. C. Gibson.....	800,433
Receptacles, system for closing, P. Langouren.....	800,603
Regulator, R. E. Atkinson.....	800,612
Relay, L. F. Howard.....	800,490
Relay for circuit breakers, M. Fuss.....	800,550
Resistance unit, C. Macmillan.....	800,574
Riprap, F. W. Hawkes.....	800,506
Riveters, traveling frame for side shell, J. M. Mc. & J. M. Dobbie.....	800,427
Rock drill feed mechanism, T. Tenne.....	800,279
Rolling black plates and sheets, apparatus for, C. W. Bray.....	800,391
Rolling black plates or sheets, C. W. Bray.....	800,392
Rotary engine, T. Veltch.....	800,526
Rotary engine, Tippet & Reese.....	800,367
Rotary engine, C. H. Francis.....	800,500
Rotary motor, E. R. Mills, et al.....	800,867
Rubber, artificial, W. H. Brownlow.....	800,435
Rug turning machine, J. J. Baird.....	800,497
Rule or calipers, G. W. Le Compte.....	800,578
Safe cleaning apparatus, W. E. Mann.....	800,545
Safety safety stirrup release, H. Arnold.....	800,550
Safe, J. M. Allen.....	800,220
Safe door support, J. M. Allen.....	800,221
Safe lock, J. M. Allen.....	800,222
Sandpapering machine, J. Black.....	800,088
Sash, balance and pulley casing, C. W. O'Connell.....	800,512
Sash fastener, G. A. Orr.....	800,798
Sash holder, T. N. Jones.....	800,437
Saw, W. B. Hatcher.....	800,574
Saw guard, F. C. Pfeil.....	800,513
Sawmill feed, R. L. Woodruff.....	800,821
Sawmill gang, W. H. Wilkins.....	800,567
Sawmill set, works, A. Cunningham.....	800,567
Saw, portable crosscut, A. Schubert.....	800,650
Saw set, J. M. Hancock.....	800,707
Sawing machine, W. L. Jacobs.....	800,712
See Window screen.....	
Screen, J. L. Mallory.....	800,315
Screen handle fastener, M. & C. Murray.....	800,505
Screen mechanism, rotary, W. C. Matthias.....	800,720
Screen, sprayer, F. G. Land.....	800,717
Seal lock, J. A. Wilkinson.....	800,761
Seat guard locking device, S. E. Jackson.....	800,848
Separator bowl, centrifugal, P. B. Shee.....	800,503
Shed, sludges, treatment of, F. Spence, et al.....	800,272
Sewing machine take-up mechanism, P. Anschutz.....	800,745
Shade and curtain bracket, M. & C. McKee.....	800,438
Shade bracket, window, C. I. Wimmer.....	800,074
Shaft oscillator, mechanical, W. F. Bouche.....	800,825
Shaft support, E. Nestler.....	800,451
Sharpening means, disk, W. B. Clark.....	800,684
Shave block, W. H. Corbett.....	800,422
Sheep shearing machine, T. A. Martin.....	800,500
Shelving, G. H. Hurteau.....	800,491
Shoe polishing machine, F. Humphreys.....	800,425
Shoe tree and holder, H. G. Letta.....	800,498
Shower bath, C. Heaton.....	800,240
Shuttle, E. C. Ives.....	800,645
Sign, electric, N. Wallace.....	800,408
Signal apparatus, C. W. Coleman.....	800,552
Signaling system, E. E. Kleinhardt.....	800,570
Signaling system, wireless, J. L. Jones.....	800,714
Siphon, alternating, H. C. De La Hunt.....	800,492
Shut-off mechanism, D. Albertson.....	800,473
Sled, L. Theriault.....	800,506
Sling, H. Gehrmann.....	800,325
Slot machine, J. P. March.....	800,254
Solder feeding mechanism for caulding machines, A. Nelson.....	800,510
Solder for aluminum, T. T. Hosack.....	800,570
Sole or heel, shoe, J. H. Vinton.....	800,093
Sound amplifier, N. Baldwin.....	800,288
Spark plug, A. Holsten.....	800,805
Spectrum, mouth, J. F. Koehler.....	800,430
Speed-changing mechanism for hydro-extractors, H. Holt.....	800,732
Splaining or twisting frames for top rolls, travelling guide for, L. T. Houghton.....	800,571
Split switch, G. M. Ervin.....	800,298
Spooler, A. E. Rodes.....	800,512
Spring roller, J. H. Sweetland.....	800,306
Sputum cup, H. J. Potter.....	800,703
Sputum cup, C. W. Meinecke.....	800,703
Squaring machine for rolling carpenter's H. K. Jones.....	800,850
Stable equipment, J. Von der Kammer.....	800,715
Stair rod fastener, W. H. Joyner.....	800,462
Stamped fabric, C. E. Bentley.....	800,225
Stay log, E. F. Smith.....	800,270
Steam conduit, Aylsworth & Dyer.....	800,765
Steam generator, H. Cox.....	800,820
Steam generators, automatic stoker for, J. H. Dickinson.....	800,702
Stereotype plate holder, J. S. Weyl.....	800,697
Stoker, mechanical, D. A. Wood.....	800,550
Stool or seat, adjustable, C. E. Bentley.....	800,777
Stores, etc., auxiliary fuel box for, T. B. Lockley.....	800,581
Strainer, M. Hancock.....	800,433
Strap fastener, G. A. Malins.....	800,540
Superheater, M. Toils.....	800,650
Swaging mill, E. Winter.....	800,284
Swing, veranda, T. H. Newton.....	800,755
Table game attachment, C. J. Knudsen.....	800,718
Talking machine step mechanism, J. C. Stuckey.....	800,740
Tanning compound, H. M. Murray.....	800,723
Telegraph pole, fence post, and the like, H. Miller.....	800,252
Telegraph, printing, B. W. Cochran.....	800,420
Telegraph, wireless, W. B. Hogg.....	800,034
Telephone lines, measured service system for, J. L. McQuarrie.....	800,450
Telephone receivers, adjustable support for, R. Higgins.....	800,296
Telescope, L. Bell.....	800,700
Telescope, sight, P. Schuler.....	800,395
Thermal protectors, automatic resetting and testing means for, F. B. Cook.....	800,864
Thill coupling, A. F. Warele.....	800,755
Tie, J. F. Schwartz.....	800,298
Tie, H. Haugh.....	800,302
Timber framing machine, Peters & Clarkson.....	800,640
Tongue switch, E. Lewis.....	800,423
Tool chest handle, H. Cowan.....	800,700
Tool, combination, A. Weber.....	800,700
Tool, machine, F. Muller.....	800,598
Tool or small, combination, J. H. Hamilton.....	800,706
Toothpick machine, W. F. Hutchinson.....	800,573
Top, advertising, J. Russo.....	800,650
Top, badge, J. Mehan.....	800,702
Train, protecting device, automatic, H. Unverricht.....	800,398
Transformer, steam, S. Otis.....	800,454
Transmission device, O. & H. Matthei.....	800,201
Trap, L. A. Corbelli.....	800,423
Tree, grafting, P. Kerner.....	800,405
Trolley, R. D. Hunt.....	800,711
Trolley head for electric traction, Holmes & Allen.....	800,843
Truck, brick, H. J. Dundas.....	800,353
Truck, motor railway, S. Otis.....	800,456
Truck construction, car, D. S. Pulliam.....	800,402
Truck side frame, car, H. C. Hubbard.....	800,707
Truck wheel, G. F. Armstrong, Jr.....	800,625
Tube cutter, F. Fleming.....	800,476
Tubes, manufacture of, A. E. Beck.....	800,292
Tubes, mill for manufacture of, E. Winter.....	800,283
Tubes, etc., mill for manufacture of, E. Winter.....	800,283
Tubing machine, J. T. Fagan.....	800,428
Tug, barge, E. Eaton.....	800,613
Turbine, ventilation of, R. C. Davidson.....	800,227
Turbine, reversible elastic fluid, C. W. Dake.....	800,773
Typewriter machine, D. Briggs.....	800,680

# THE AERO CLUB TROPHIES AT THE AUTOMOBILE SHOW IN THE GRAND CENTRAL PALACE.

## THE SCIENTIFIC AMERICAN FLYING MACHINE TROPHY.

In presenting this trophy to the Aero Club of America the publishers of the SCIENTIFIC AMERICAN have recognized that the conquest of the air may not come through dirigible gas bags, but through the perfection of aeroplanes, machines which are heavier than air. The cup is offered for competition among the heavier-than-air machines and, year by year, as aeroplanes are developed, the conditions governing the contest will be readjusted. The cup stands 32 inches high and is a magnificent trophy of wrought silver mounted on a pedestal of onyx. At the base of the pedestal-shaft, graceful winged silver horses spring forth ridden by figures bearing olive branches. The shaft is surmounted by a whirlwind bearing a globe representing the firmament. On one side of the globe is the American continent, while on the other an aeroplane soars through the clouds, challenging the swallows in their flight. The whole is crowned by an American eagle, bearing a wreath of victory. The cup is of American manufacture and is valued at \$2,500.

## THE GORDON BENNETT INTERNATIONAL CUP.

The Gordon Bennett cup was offered in 1906 as an

stretched hands hold wreaths of victory. The lower limbs of the figures blend into the outstretched wings of supporting eagles, perched on small spheres rising from a firmament of stars and planets. Below is a portion of the northern hemisphere, which rests on an ebony base set with silver plates to bear the names of the winners of the trophy. The cup was made in New York at a cost of \$1,500.


## The Prevention of Fire at Sea.

The recent alarming fire on the steamer "Fortunatus" shows again the insufficiency of the methods adopted on most vessels to protect themselves against such an outbreak. A good fire appliance has not only before it the task of subduing a fire, but specially of saving the cargo from being damaged by water. In many cases after the fire has been finally extinguished, it has been found that the water damage far exceeded the damage by fire. It is therefore obvious that an ideal fire appliance can only be of a purely chemical nature.

It is not only the prevention of water damage which tells so much in favor of the use on board ship of a chemical fire protection. There is another reason, well known and feared in shipping circles, viz., that a fire cannot always be extinguished in cer-

pressure. The steam passing through the apparatus is merely for the purpose of heating the latter to aid in the expansion and flow of the CO<sub>2</sub> gas, and to prevent the formation of snow. The "Gronwald" system is not a gas-generating plant requiring special skill for its operation. The gas is always ready for instant use, and this is obviously a very important point.

The "Gronwald" CO<sub>2</sub> system is, above all, adapted for the prevention of spontaneous combustion and ignition. As soon as the air in a hold reaches an abnormally high temperature several bottles of liquid CO<sub>2</sub> can be discharged into the hold in order to displace the air from it, so cutting off the supply of oxygen, the source of every outbreak of fire. At the same time the liquid CO<sub>2</sub>, which has been so far in a liquid state, will evaporate rapidly and deprive the surroundings of its heat, thus lowering the temperature in the hold by 30 deg. and more—a point in its favor which, it is stated, no chemical fire appliance except the CO<sub>2</sub> system can claim. Another virtue of the CO<sub>2</sub> gas is that it is a thoroughly neutral gas. It does not affect the most delicate cargoes, as those of silk, tobacco, and wine. This is contrary to the action of most other chemicals, which damage many such cargoes and also the fittings of the ship if they happen to be wet or moist. The last state of that



The Gordon Bennett International Cup.

The Scientific American Trophy.

The Lahm Cup.

# THE AERO CLUB TROPHIES AT THE AUTOMOBILE SHOW IN THE GRAND CENTRAL PALACE.

International trophy for long-distance balloon races. At the initial contest one American balloon piloted by Lieut. Lahm was entered, and bore off the coveted trophy against fifteen competitors. The cup is a fine example of the silversmith's art and was modeled in accordance with suggestions made by the donor. The design represents a dirigible balloon, supported by clouds, and led in its course by a winged figure bearing in one hand the torch of science, and in the other a wreath of victory. On the body of the dirigible balloon, on one side, spherical balloons are shown high in the air and an aeroplane begins its flight. On the other side are shown a parachute and two Montgolfier balloons. The cup was constructed in Paris at a cost of \$2,500.

## THE LAHM AERONAUTIC CUP.

On the receipt of news that Lieut. Lahm was bringing the Gordon Bennett trophy to America, the Aero Club of America decided to commemorate the victory by offering a cup for distance contests. As the SCIENTIFIC AMERICAN and the Gordon Bennett trophies suggest aeroplanes and dirigible balloons respectively, so this one honors the spherical gas-bag, the lineal descendant of Montgolfier's balloons. This feature is a faithful reproduction of a balloon, supported lightly by the wing tips of two female figures whose out-

tain goods, especially in cotton bales. Such a cargo is not only easily combustible, but a fire in it cannot readily be checked, the water acting, as it were, as a source of oxygen. A gas, moreover, permeates all the small channels of woolen fibers which water is unable to reach. Similarly, water cannot extinguish a fire on an oil steamer, although it is easy work for a chemical fire appliance to do so.

Among the chemical fire appliances now in use at sea may be mentioned that known as the "Gronwald" system. It consists, briefly stated, of an apparatus through which carbonic acid gas is passed into perforated pipes, which are so fixed in the hold as to allow a good distribution of the gas. The gas is carried in the ordinary steel cylinders that are used for refrigerating plants on board vessels, the number of the cylinders depending on the size of the ship. From the steel cylinders the gas passes into the apparatus, where it expands before entering the pipe system in the compartments. To facilitate the flow of the gas, steam from the ship's boilers is let through a special arrangement of the apparatus. Each hold can be worked independently, the apparatus recommended for ordinary steamers and sailing ships of any size being portable. For its operation no machinery is required, the gas working under its own

ship may be worse than the first under such conditions.

For fire extinguishing purposes it is not necessary absolutely to fill up the hold with CO<sub>2</sub> gas, but the admixture of a certain percentage of gas to the oxygen in the space is quite sufficient, this depending on the nature of the burning goods, and ranging from 10 to 25 per cent. Taking as the outside limit an admixture of 25 per cent, the "Gronwald" appliances are able to fill with even so high a percentage as 25 per cent in about one hour's time a space of 67,200 cubic feet, which means the contents of 48 steel cylinders of 40 pounds liquid CO<sub>2</sub> each. According to the size of the ship, a number of 50 to 70 cylinders of CO<sub>2</sub> is a very fair supply for fire protection. Vessels having refrigerating installations can, of course, combine the use of the cylinders both for refrigerating and fire appliances, if provided with an ample stock.

The Japanese government intends to spend \$75,000,000 during the next five years on railway construction and equipment. Among other items, appropriations are made for doubling 830 miles of track, and for constructing 900 locomotives, 1,000 passenger cars, and 19,000 freight cars.



Typewriter mechanism, J. B. Becor.....	800,526
Typewriters, platen rotating mechanism for, H. J. Otto.....	800,380
Typewriting machine, H. W. Merritt.....	800,572
Typewriting machine, A. W. Buckwell.....	800,547
Typewriting machine indicator, H. A. Dewing.....	800,832
Valve, Wheldon & Maxwell.....	800,281
Valve and by-pass, hydraulic four-way, W. J. Tretch.....	800,755
Valve connection, triple, F. L. Clark.....	800,623
Valve, engine stop, J. L. Kimball.....	800,248
Valve, gate, and Schultze, E. Turnbull, W. Valve grinder, P. F. Pilliner.....	800,525
Valve mechanism for air compressors, Laferty & Spence.....	800,647
Valve, safety, L. Schultze.....	800,373
Valve, sensitive triple, W. H. Mann.....	800,524
Valve, steam actuated, G. W. Meyer.....	800,657
Vegetable topping machine, A. E. Vrooman.....	800,794
Vehicle body, H. E. Porter, Jr.....	800,816
Vehicle door, Ludwig & Bradbury.....	800,239
Vehicle spring suspension, W. W. Macfarren.....	800,249
Vehicle top support, T. Henry.....	800,583
Vehicles, means for checking side slip of road, W. E. Monro.....	800,567
Vending apparatus, A. Rosenfeld.....	800,640
Vending machine, cigar, A. Jacobs.....	800,807
Volatile substances, purifying, J. U. Lloyd.....	800,635
Wagon box and stock and hay rack, combined, O. K. Hibbets.....	800,351
Wagon, dumping, T. Wright.....	800,303
Warp stop-motion, B. F. McInnes.....	800,473
Wash and bath tub and ironing table, combined, A. Lombardo.....	800,645
Washer, C. G. Elitz.....	800,780
Water cooler, J. T. Cole.....	800,235
Water measuring gate, A. H. Stokes.....	800,274
Water meter, C. F. Merrill.....	800,320
Water meter, N. W. Hartman.....	800,841
Water motor, T. M. Heister.....	800,548
Water motor wheel, B. R. Bush, reissue.....	12,713
Wheelbarrow wheel, Baker & Smith.....	800,343
Wind power, machine for use with, J. Homola.....	800,709
Winding device, S. W. Wardwell.....	800,604
Windmill regulator, O. C. Hoevet.....	800,242
Window cleaner, B. A. Hill.....	800,842
Window construction, R. E. Turnbull.....	800,468
Window screen, H. Wright.....	800,470
Window screen, A. A. Day.....	800,683
Window tightener, J. M. Haddock.....	800,631
Wiping strip and making same, C. S. Clark.....	800,418
Wire and wood slats, machine for weaving, T. F. Hagerty.....	800,705
Wire fastener, L. B. Peoples.....	800,458
Wire stretcher, G. H. Weyant.....	800,402
Wire brush, portable, H. Rosenbaum.....	800,401
Work locating indicator, Dennis & Lindholm.....	800,483
Wrapping machine, J. M. Patterson.....	800,388
Wrench, C. H. Myers.....	800,380
Wrench, J. F. Large.....	800,255
Wrench, A. L. Shonars.....	800,496
Wrench, E. H. Vanderslice.....	800,527
Wrench, A. E. Pearce.....	800,670
Zinc skimmings, utilizing, B. Terno.....	800,802


TRADE MARKS.

Asbestos composition shingles, slate, and sheathing, Asbestos Shingle, Slate and Sheathing Co.....	65,862
Bitters, M. Rothenberg.....	65,859
Boots and shoes, leather, Seils, Schwab & Co.....	65,863
Boots and shoes, leather, Smith-Wallace Shoe Co.....	65,860
Boots and shoes, leather, Deane & Green Shoe Co.....	65,878
Candies, Adams Argood Chocolate Co.....	65,896
Canned fruits and vegetables, Burt Olney Canning Co.....	65,905
Canned fruits and vegetables, Warfield Pratt Howell Co.....	65,917
Cement, Portland, Fredonia Portland Cement Co.....	65,965
Chemise, regisfort, L. Rigault & Co.....	65,914
Chemicals, certain, Albright & Wilson.....	65,861
Coats, vests, and pants, Novick Bros.....	65,900
Corn or corn chops, cracked, Gulfport Grocery Co.....	65,907
Cotton duck, Mount Vernon-Woodberry Cotton Duck Co.....	65,946
Cotton fabric, certain, Mount Hope Finishing Co.....	65,945
Electric conduits, American Circular Loom Co.....	65,955
Fertilizers, Virginia-Carolina Chemical Co.....	65,894
Flavoring extracts, H. Hardisty Manufacturing Co.....	65,913
Flour, wheat, Allen & Wheeler Co.....	65,898
Flour, wheat, A. B. Smith & Co.....	65,916
Food, prepared stock, Gulfport Grocery Co.....	65,908
Foods, certain cereal, Allen Brothers Co.....	65,897
Furniture, certain, Simmons Manufacturing Co.....	65,960
Ginger ale, William J. Stange Co.....	65,954
Ice cream cones, Andalraft Bros.....	65,899
India rubber, gutta percha, and other vulcanizable gums, G. A. Alden & Co.....	65,872
Lignum, T. G. Cantor.....	65,862
Lumber, rough and dressed, J. M. Card Lumber Co.....	65,887
Mattresses, Southern Cotton Oil Co.....	65,893
Medicine, certain, W. C. Otterbein & Co.....	65,857
Medicine to perfume the breath, T. Mori.....	65,856
Metal polishing and abrasive material, W. R. Forbush.....	65,897
Metallic leaf depositing implement, W. L. Coe Manufacturing Co.....	65,951
Middlings and red-dog, Wells Flour Milling Co.....	65,918
Military equipments, certain, Mills Woven Cartridge Belt Co.....	65,890
Mouth wash and gargle, tooth paste, and throat pastil, J. F. Carnegie.....	65,851
Nozzles, H. B. Sherman.....	65,949
Oilnut, Thompson Drug Co.....	65,890
Paint, enamel, and varnish, Hockaday Paint Co.....	65,885
Paint, roofing, Pittsburgh-Salt Lake Oil Co.....	65,891
Paints and painters' materials, certain, Peninsular Paint and Varnish Co.....	65,911
Paper, cover, American Writing Paper Co.....	65,873
Pills, laxative, J. S. Berner.....	65,876
Printers' quoin, Wickersham Quoin Co.....	65,850
Razors, Gem Cutlery Co.....	65,902
Remedy for headache and heartburn, T. Mori.....	65,854
Remedy for indigestion, Physicians' Co-Operative Association.....	65,858
Remedy for seasickness, T. Mori.....	65,855
Sewing machines, Mark & Co.....	65,943
Shirts, dress and negligee, Burnham Hanna Munger Dry Goods Co.....	65,904
Soap, Max Hancock Chemical Co.....	65,886
Soap for laundry use, Procter & Gamble Co.....	65,892
Soap, laundry and toilet, Enterprise Soap Works.....	65,880
Soap, perfumed, A. & F. Pears.....	65,885
Soap, toilet, James S. Kirk & Co.....	65,888
Soaps and detergent washing powders, Fischer Bros.....	65,883
Sponges, certain prepared, G. Glass.....	65,884
Sugar, Rockwood Brothers Co.....	65,915
Teas, J. B. Brown & Co.....	65,902
Teas and coffees, J. B. Brown & Co.....	65,901
Tobacco, cigars, cigarettes, and snuff, smoking, De E. De W. J. Van Nello.....	65,877
Undergarments, combination, Birkenfeld Strauss & Co.....	65,900
Varnish, varnish stain, and paint, Hockaday Paint Co.....	65,886
Veterinary medicine, S. P. Crawford.....	65,853
Washing crystals, soluble, Magi Washing Crystal Co.....	65,942
Watch movements, A. Wittmayer Co.....	65,871
Water, mineral, Miraco Co.....	65,944
Wheat, breakfast, Pacific Milling Co.....	65,910
Whisky, Albert M. Gugenheim Co.....	65,910
Whisky, M. L. Bayer.....	65,920
Whisky, O'Neill & Richardson.....	65,948

LABELS.

"Brandy-Book Charentais," for brandy, Syndicat des Viticulteurs des Charentes et de la Société Co-operative amicale de Saintes.....	13,842
---	--------

# TRUFFAULT-HARTFORD SHOCK ABSORBER



## The Device That Made SAFE, SPEEDY and COMFORTABLE AUTOMOBILING Possible

The spring action of a car affects its smooth running qualities. Proper control of the springs prevents excessive oscillation, which insures LESS WEAR and TEAR, LONGER LIFE OF TIRES, GREATER SPEED and GENUINE COMFORT.

This control of the springs can be secured only by the use of TRUFFAULT-HARTFORD Shock Absorber—the device that has made SAFE, ECONOMICAL AND COMFORTABLE automobiling possible.

In the 1908 model we believe that we have practically obtained perfection.

A distinctly new feature has been added, consisting of a regulating dial with indicator, making it possible for even a novice to obtain a perfect and uniform adjustment to suit the exact requirements of the car as measured in terms of its gross weight, and easily secure the maximum benefit.

The Truffault-Hartford is the only spring retarding device manufactured with a regulating dial. It is automatically lubricated, absolutely dust and water proof, interchangeable, practically indestructible and fully guaranteed.

The superiority and individual qualities of the Truffault-Hartford Shock Absorber are best demonstrated by the fact that it has been adopted exclusively as equipment by such prominent cars as the:

Pierce Great Arrow, Studebaker, Stevens-Duryea Big Six, Stoddard-Dayton Six Cylinder, Marmon, Continental, Lane, Conover, Sultan, Frontenac and Acme Six Cylinder.

Write To-day for Our "Ruff Road" Booklet. Address Department 2.

## Hartford Suspension Company

E. V. Hartford, Pres. 72 Vestry St., New York

"Do-Not Liver, Kidney and Constipation Tablets," for medicine, L. G. Denton.....	13,846
"J. & H. Cup Quality," for roasted coffee, Jaines & Hug.....	13,843
"Katalol," for a medicinal preparation, I. C. Schmeifong.....	13,845
"Lava Salt-Herbs," for preparation of meats and vegetable soups, J. J. Ruegg.....	13,844
"Lightning Star," for a dressing for piano automobiles, carriages, bays, and all kinds of furniture, J. Gaudin.....	13,847
"Sweet-Ort Belt Grip," for trousers, Sweet-Ort & Co.....	13,848

PRINTS.

"Eik Brand," for shoes, G. A. Lutz.....	2,441
"Hans' Scatched Yet!!" 16 V's on the M'K't," for a searing soap, Bos Am Co.....	2,142
"Men's and Boys' Apparel," for men's and boys' apparel, H. C. Lytton.....	2,143
"Treat Yourself Right," for a brand of whisky, Meyer & Co.....	2,144

A printed copy of the specification and drawing of any patent in the foregoing list, or any patent in print issued since 1880, will be furnished from this office for 10 cents, provided the name and number of the patent desired and the date be given. Address Mann & Co., 361 Broadway, New York.

THE AUTO-SLIP ARCHIMEDE.

(Continued from page 332.)

can be tipped with ease to any desired inclination. The proper approximate position of equilibrium for any particular car can be determined, once for all, by hauling the car up until the rails can be propped in a horizontal position (Fig. 2), slackening the cable and moving the car by hand until it can be tipped by a moderate effort. The wheels are then strapped to the rails and their places are marked.

The car is removed from the apparatus by simply reversing the motion of the winch, allowing the vehicle to move slowly down the rails, which return automatically to their initial position.

"NEWMASTIC"—A RELIABLE AND ELASTIC FILLING FOR PNEUMATIC TIRES.

So much has been written about puncture-proof tires and spring wheels, which would make pneumatic tires no longer necessary, that everyone is inclined to be very skeptical toward any invention of this nature.

The records of the United States Patent Office at Washington show about three thousand patents as evidence of the efforts of inventors along these lines. Solid rubber tires of various forms of construction have solved the problem for many strongly-built automobiles, but it is a well-established fact that the pneumatic tire or its equivalent is an absolute necessity on the ordinary form of pleasure vehicle, as it is usually operated. Perhaps the best substitute and nearest equivalent to a pneumatic tire is what is known as a "filled tire," which consists of an ordinary pneumatic tire inflated with an elastic, soft, spongy substance instead of air. The method of manufacture employed is to inject the filling material in a liquid state under pressure, and to thus inflate the tire to whatever degree is desired. The main difficulty has been that the user is compelled to send his wheels, tires, and inner tubes to the factory for inflation, and that after the tires were filled there was no means by which the user could increase or decrease the inflation to suit his own particular case. "Newmastic" is the only one of these tire fillers that is known to any extent. In England and France "Elastes" has been used quite extensively, but this compound is said to be far from successful, for the reason that when first manufactured and injected into the tires, it requires two weeks in which to harden sufficiently to be safe. The main difficulty seems to be that the material continues to grow harder and harder as it gets older. "Newmastic," on the contrary, sets within a very few minutes after it is first put into the tires, and is ready to be used at once. Strange as it may seem, this compound appears to improve with age, remaining soft and resilient at all temperatures from 15 deg. below zero up to the burning point.

In order to overcome the objection of shipping wheels from distant points to the factory, and also to enable the user to vary the degree of inflation of his tires at will, a very simple form of universal clincher rim has been invented.

This is made by taking an ordinary one-piece standard clincher rim, and cutting it into two equal parts by removing about a quarter of an inch from the center of the rim all the way around. The inside half is securely fastened to a plain steel band upon the felloe of the wheel. The outside or removable half of the rim slips over this band, and is drawn toward the permanent half by a stiff ring which is drawn up by ordinary bolts through the felloe of the wheel. In this manner the width of the clincher rim may be slightly varied, and the edges of the clincher tire may be drawn closer together than the standard clincher measurement, or may be left slightly farther apart. This variation in the width of the tire is so small as to cause no injury to the tire, and yet it is sufficient to take up the stretch in the casing and to afford any required degree of inflation. This principle of inflating a tire by drawing the casing tightly about a filled inner tube is entirely new, and applications have been made for patents in the United States and all foreign countries.

Air under pressure in a tire expands and contracts according to the temperature, and an air-inflated tire is therefore subjected to a constantly varying pressure, and consequently to a constantly varying wear; while a tire inflated with an elastic solid material is always subjected to a constant pressure from within, for the reason that the filler expands and contracts in substantially the same ratio as the rubber itself. A tire thus inflated is never rim cut, owing to flat running, and the automobile owner can obtain from his tires an amount of wear which is as constant as that which he will receive from a suit of clothes. This affords a very great saving, but the greatest advantage of all is that tires filled with the new substance are no more affected by punctures than is a pin cushion by the pins that are stuck into it; even punctures from bolts or railway spikes will not ordinarily let the filler escape. When a really large and serious cut or break occurs in the casing, a tire bandage or gaiter will repair the damage sufficiently for the journey to be completed, and, in many cases, a tire will run hundreds of miles with such a temporary repair. Tires so inflated ride just as smoothly as tires inflated with air at the same pressure, and it is impossible even for an expert to tell from the outside of a tire whether it is inflated with this substance or with air.

#### THE GEARLESS TWO-SPEED TRANSMISSION.

(Continued from page 324.)

wear from this cause. Furthermore, instead of the drive being through friction disks at all times, in this instance it is through the friction rollers only, and that during a very small part of the time when the car is running.

The new transmission is similar in design to the ordinary two-speed planetary gear. It consists of an expanding-ring clutch mounted on the end of the crankshaft, and to which is attached a driving cone upon which can revolve five conical rollers arranged annularly around it, and contacting on their outer surfaces with the inner surface of a conical driving cup which is loosely mounted upon the propeller shaft. Either this latter cup or the cage containing the rollers can be locked to the propeller shaft by means of a sliding jaw clutch. An internal spring keeps the parts under pressure, so that the rollers will not slip when they are in use. To obtain the low speed, the driving cup is held stationary by a band brake, and the cage of rollers is locked to the propeller shaft by means of the jaw clutch. The drive is then from the inner cone to the rollers, and from the cage of the rollers to the propeller shaft. As the outer cup is held stationary, the rollers move around within it at a reduced speed. A speed reduction of three to one is thus obtained from the crankshaft

## The Lambert Friction Flyer, 1908

\$800

\$800



"The Lambert 18"  
The Car Without a Gear Box

**SPECIFICATIONS:** Capacity—three passengers. Wheel Base—95 inches. Tread—56 inches. Frame—pressed steel. Wheels—30-inch, wood artillery. Tires—30 x 3-inch Michelin. Motor—2-cylinder opposed, 18 h. p. Transmission—friction. Speed—1 to 35 miles an hour. Carburetor—float feed. Ignition—jump spark. Radiator—honeycomb. Drive—single chain to rear axle, encased. Brake—external on each rear hub. Bearings—Hyatt Roller and Standard Ball. Clearance—12 inches. Gasoline Capacity—12 gallons. Length of Body—from inside of dash, 76 inches. Width of Body—to outside mud guard, 63 inches. Width of Body—32 inches. Width of Front Seat—36 inches inside of cushion. Width of Rear Seat—18 inches inside of cushion. Height of Floor from Ground—29 inches. Painting—French gray. Upholstering—fine quality of leather; springs in cushions and backs of seats. Weight—1,350 pounds. Equipment—two oil lamps, horn and full tool equipment. Price—\$800 complete, f. o. b. factory.

\$800 "The Lambert 18" \$800

The Best Value in America at the Price

Ask the best posted mechanic of your acquaintance what he thinks of the Friction Drive, and the answer will be: "The Best on Earth." Ask a farmer and he will not know because his calling has not required that he keep abreast with the improvements in power transmission—especially as applied to automobiles.

Better still, see the Lambert, have a demonstration—examine the mass of testimony that has come to us unsolicited—we feel sure that the verdict will be: "I will buy a Lambert because it is the simplest, noblest and best car on the market for the money." Write for catalogue 18.

THE BUCKEYE MANUFACTURING CO.

A Few Good Agents Wanted.

ANDERSON, INDIANA

## NORTHERN

MOTOR CAR CO., DETROIT.

**For 1908** the Silent Northern embodies the same strong, enduring construction that has given it supremacy for five successive years, plus **MORE POWER**, due to large cylinders, larger valves and other refinements. Five years' experience manufacturing this one type insures that perfection of detail necessary to give you reliability and low cost of maintenance. This car will prove to be for you, as it has been for others, a genuine money-saver—and give you every pleasure and comfort possible to get from any car regardless of price. Investigate—find out for yourself. Send for Catalog.

The Silent Northern 24.2 Horse Power

(A. L. A. M. rating)

Price, - - \$1,600

TOP EXTRA

F. O. B. Factory including full lamp and tool equipment.



Member Association of  
Licensed Automobile Manufacturers

to the rear axle. To obtain the reverse, the cage of rollers is held stationary, by means of another band brake, and the outer driving cup is locked to the propeller shaft by the jaw clutch. The drive is then from the inner cone through the rollers (which merely revolve upon their axes) to the outer driving cup, which turns in the opposite direction. The high speed is obtained by the main expanding-ring clutch. All the parts are locked together on this speed. The only parts that can wear in this transmission are the rollers. These are made of a special paper composition that is said to be very durable. All the parts of the transmission are exceedingly large and heavy, and apparently they should easily outwear the other working parts of the car. The transmission appears to be a very neat solution of the problems encountered in the usual planetary gear and friction-disk types.

#### THE POWER PLANT OF THE HOLSMAN CAR.

(Continued from page 324.)

stroke of these cylinders is 4 inches. The new engine has a number of features that are more or less important. Principal among these are the arrangement of the bearings so that they can be readily removed and replaced without taking the engine apart or removing the crankshaft. Special oil wells have been arranged in the crankcase cover, and these catch the oil which is splashed up by the cranks, and feed it by gravity to the crankshaft bearings. A certain amount of oil is carried in the crank case for the purpose of splash lubrication, and as plenty of this oil is thrown into the rear cylinder, it is unnecessary to have a special oil feed pipe to this cylinder. The mechanical oiler, which is operated by a belt, therefore has but two feeds, one of which goes to the forward cylinder and the other to the center of the crank case. Instead of being mounted upon four feet, as heretofore, the motor is now clamped to two transverse steel tubes, as is shown in the photograph. An excellent feature of this motor is the method of ignition. There are two spark plugs in each cylinder. One of these is in the head of the cylinder, and the other is in the valve chamber between the inlet and exhaust valve. Two coils are used, the two plugs in the heads of the two cylinders being connected in series to one of these coils, and the other two plugs between the valves of the two cylinders being connected to the other coil. Thus it can be seen that the spark jumps both plugs at the same time, that is, the two plugs in the heads of the cylinders and also the two plugs between the valves, provided the second spark coil is switched on. Ordinarily, only one set of plugs is used, but if these become short-circuited, the other set can be immediately thrown in. It is also preferable to use both sets in starting. The engine is connected to a countershaft through two Morse silent chains. A sliding feather upon the engine shaft connects one or the other of these chains to that shaft, in order to obtain the low speed or the high speed. The final drive from the pulleys on the ends of the countershaft to the rear wheels is by means of cables, consisting of steel chains filled and covered with woven fabric. These cables are tightened by moving forward a hand lever, and the car is driven by them. When the lever is moved still farther, the cables are slackened and the brake is applied; while pushing the lever as far forward as possible, applies smaller pulleys to the tires of the rear wheels and reverses the car. There is no foot-operated brake, the entire control being effected with one hand lever. The car is fitted with a steering lever in place of a wheel, and the spark and throttle controlling handles are mounted on top of the steering-lever post, convenient to the driver's right hand.

On account of its very efficient form of drive, the Holzman machine has won in several economy and endurance tests. The machines can readily cover as high



Temporary prominence is no indication of merit. A publication may carry a considerable volume of automobile advertising for one issue, or a few issues—but a publication with Collier's record of leadership in the automobile trade, extending over a period of years, must return good value for every dollar spent. Now, that doesn't mean that you, Mr. Autosell Goods, can advertise just any automobile proposition at any time in Collier's and make money by it. Knowing when and what to advertise is important, but no more so than knowing when and what *not* to advertise. When the conditions are right for intelligent advertising, Collier's pays. Collier's staff, working together with the advertiser, knows pretty well when conditions *are* right—knows the how, when, and where of automobile advertising. With complete statistics showing just what every advertiser has done, we are in a position to plan successful advertising. Whether you sell cars or sundries, whether you propose to advertise or not, whether you finally use Collier's or some other successful medium, the fact remains: **Collier's advertising staff has data of interest to you.** This information is at your service. If you learn nothing else from it you will at least learn how advertising has paid some of your competitors. Why not learn at the same time how it will profit *you*? We are only awaiting your word to go over the proposition with you. It will cost you nothing. Write now.

*This table shows the number of lines of automobile advertising carried by the seven leading national magazines for the last three and three quarter years. It demonstrates conclusively where Collier's, the National Salesman, is ranked as an automobile salesman by these manufacturers.*

1903		1904		1905		1906		1907	
Publications	Agate Lines	Publications	Agate Lines	Publications	Agate Lines	Publications	Agate Lines	Publications	Agate Lines
Collier's	30,585	Collier's	32,503	Life	45,378	Collier's	45,956	Collier's	39,254
S. E. Post	23,585	S. E. Post	29,030	Collier's	45,239	Life	38,691	*Life	34,908
McClure's	20,136	McClure's	26,244	McClure's	33,480	McClure's	36,116	McClure's	21,056
Harper's	18,098	Harper's	22,396	S. E. Post	31,548	Ev'rybody's	27,188	Cosmo'itan	19,213
Scribner's	16,453	Life	20,350	Harper's	29,568	Century	26,614	S. E. Post	18,301
Century	15,232	Century	18,934	Scribner's	27,440	S. E. Post	25,712	Ev'rybody's	18,016
Rev. of Rev.	13,674	Scribner's	17,416	Century	27,005	Rev. of Rev.	25,616	American	17,934

\* Size of page now 420 lines; heretofore counted as 500 lines

A more effective bit of publicity for the motor car as an institution than Collier's special Automobile Section, issued with Collier's for October 26th, is hard to imagine. Short original articles, striking pictures and especially attractive advertisements guarantee it an audience where a manufacturer's circular would find only the waste basket. Get a copy at any newsstand.

# Collier's

THE NATIONAL WEEKLY



## Are You Going Away?

TRIPS OF

TWO WEEKS  
THREE WEEKS  
FOUR WEEKS  
OR OF LONGER DURATION  
TO

## Summer Lands

We dispatch superb passenger ships to the

## West Indies

Venezuela, Costa Rica, Panama Canal  
the Mediterranean  
the Adriatic, the

## Orient

Egypt, the Holy Land, etc.


Send for our illustrated book of travel,  
"Winter Voyages."

### HAMBURG-AMERICAN LINE

35-37 Broadway, New York

Boston Chicago San Francisco Philadelphia  
St. Louis

**ELECTRICAL APPARATUS REPRESENTED BY CONVENTIONAL DIAGRAMS IN DRAWINGS.**—Fifty diagrams showing the usual method of illustrating electrical apparatus in drawings. A labor saving paper, contained in SUPPLEMENT 1106. Price 10 cents. For sale by Munn & Co. and all newsdealers.



Do not buy a 1908 Speed Indicator without a Maximum Speed Hand and Instantaneous Resetting Trip Odometer

Maximum Hand and Instantaneous Resetting Trip Odometer are positive necessities. They are exclusive with the Jones Speedometer and are included on all Jones standard instruments without extra charge.

1908 Catalog on request to Dept. 69.

**JONES SPEEDOMETER**  
Broadway and Seventy-sixth St., New York

## How to Build a 5 H.P. Gas Engine at Home

IN SCIENTIFIC AMERICAN SUPPLEMENTS 1641 and 1642, E. F. Lake describes simply and thoroughly how a five horse power gas engine can be built at home. Complete working drawings are published, with exact dimensions of each part. Price by mail for the two Supplements, 20 cents.

Order from your newsdealer or from

**MUNN & COMPANY**  
Publishers  
361 Broadway, New York


as 30 miles on a gallon of gasoline under favorable conditions. On account of their ability to negotiate all kinds of country roads at a fair average speed (15 to 20 miles an hour) they are coming into extensive use by farmers, physicians, and others who want a moderate-priced machine that has a low cost of upkeep, and that can be depended upon to run regularly in all kinds of weather. As can be seen from the illustration, the Holsman is a "gearless" car in the true sense of the word. Even the differential gear is dispensed with. This has been found unnecessary, as the differential movement of the wheels in turning corners is allowed for by the slipping of the cables on the drums. Our illustration on page 328 shows the latest model Holsman machine.

### THE LAMBERT FRICTION DRIVE CHASSIS. (Continued from page 325.)

driving disk. The paper-covered driven disk is slidably mounted upon a countershaft which is capable of being moved slightly forward or backward, in order to press the driven disk against the driving one, or to withdraw it while it is being shifted. A pedal moves the countershaft forward, while a spring withdraws it. A single chain transmits the power from the countershaft to the differential upon the live rear axle. Forward movement of the car is obtained by placing the driven disk on one side of the driver, and reverse motion by placing it upon the opposite side. The nearer to the periphery of the driving disk the driven one is moved, the faster the car moves along the road. The simplicity of this device is as great as its antiquity. It is only within the past three or four years, however, that this type of transmission has been made thoroughly practical. Its cost of maintenance is extremely low, while its reliability is very great. The Lambert Company has applied it to trucks of the heaviest type with equal success.


### A NOVEL GASOLINE TESTER.

A novel tester for ascertaining the specific gravity of gasoline is shown in the annexed cut. This consists of three glass balls colored red, white, and blue, and arranged at different levels in the tube, which is but 3 inches high, small enough to pass through a  $\frac{3}{4}$ -inch hole, and which requires less than  $\frac{1}{4}$  ounce of gasoline to fill it. Each ball can rise vertically



about  $\frac{1}{4}$  inch. If the gasoline has a specific gravity of 60 deg. Baumé, the red ball will float; if 65 deg., the white one; and if 70 deg., the blue one. The instrument weighs but 2 ounces. It is provided with a chain a foot long. The maker is the Storage Battery Supply Co., 239 E. 27th Street, New York city.

## "Second" Imperial



## The Car with the Straight Line Drive

30-35 Horse Power  
Double Ignition System

Eiseman Magneto  
36-inch Wheels

## DOUBLE DROP FRAME

PRICE (including gas lamps and generator, horn, tools, etc.)

\$2,500, with folding Rumble

\$2,650, with four individual bucket seats

Manufactured by **IMPERIAL MOTOR CAR CO.**

WILLIAMSPORT, PA.

Member A. M. C. M. A.



Model A—\$500

## STAR RUNABOUTS

3 Models—\$500, \$600, \$700

The noblest little cars on the market. Beauty, Simplicity, Ample Power, Perfect Control, and Low Cost of Maintenance make them the Ideal Car for business, professional or pleasure uses. Flexibly built to withstand hard usage on rough roads in city or country. Have three-point spring suspension, pneumatic tires, shaft drive and many other good points. Let us tell you about them. Fine selling proposition for agents. Good territory still open. Special bodies for business purposes.

STAR AUTOMOBILE CO., 303 Dearborn St., Chicago

Gas Operating



## THE JEWELL STILLS


(Patented in the U. S. and Foreign Countries.)

For Drinking Water and Technical Use  
**PURE WATER H.O.**

They operate automatically—delivering the distilled water cold, aerated, palatable, crystal clear and germ proof. Homes, Apartments, Office Buildings, Hotels, Schools, Clubs, Hospitals, etc., have installed them. Saves expense of buying bottled waters. Made any capacity. Your architect has full details—See Sweet's Index, November 1st, 1907, or write us. We also manufacture water softening and filtering apparatus for industrial and municipal use.

**JEWELL WATER IMPROVEMENT CO., 118 W. Jackson Boulevard, CHICAGO**

Steam Operating.



## Motor Buggies, Little Roadsters

FURNISHED COMPLETE OR PARTS OF SAME



One and Two Cylinders—Vertical and Horizontal Air Cooled Motors. All Styles of Water Cooled Engines. Friction and Planetary Transmissions. Single or Double Chain Drive.

Differentials.—We Supply all the Necessary Parts to Convert Buggies into Auto Buggies.

**NEUSTADT AUTOMOBILE & SUPPLY CO., 3932 Olive St., St. Louis, Mo.**



## FREE College Course in Watch Repairing

To establish yourself in your locality, I will help ambitious young men of good habits to start a jewelry business within 3 months, after beginning my personal instructions. My time and instructions, all books, charts, diagrams and pictures necessary to complete the full course are absolutely free. If you are alert and worthy of a successful future, write for full particulars and Lesson 12 today. They cost you nothing.

**CHAS. F. ELMORE, Principal**  
Correspondence School of Watch Making  
Rogers, Thurman & Co., Props. 57 Michigan Ave., Chicago.

## Draw More Salary

Demand for mechanical draftsmen always exceeds supply. Drawing is the open door to promotion. We guarantee that any ambitious young man can complete one course and successfully fill a drafting-room position. 160 engineering and business courses. Expert instruction. Write, state what interests you.

**Intercontinental University**  
1411 L St., Washington, D. C.



We will mail this excellent **ELECTRIC FLASH LIGHT** for 50¢. Battery capacity 5000 flashes. Intense white light. Rechargeable battery 50¢. Write for 10 page Free Cyclopedic atlas experiments on Wireless, Collis, Electric Photography, etc. Electric Importing Co., 57 Warren St., N. Y.





MODEL No. 3.

# Another Perfect Score

## In the Chicago 150-Mile Non-Motor-Stop Reliability Run

It takes time to perfect an automobile just the same as it does any other piece of machinery. The HOLSMAN has now been on the market

### 5 YEARS

and has an established reputation for stability and reliability. Do not be induced to help some new inventor work out his experiments on you by buying a machine that has not been on the market more than a year. If you are a user you will regret it, and if you are an agent you will regret it still more.

## HOLSMAN AUTOMOBILE COMPANY


The Oldest and Largest Manufacturers of Carriage Automobiles

Room 403

MONADNOCK BLOCK, CHICAGO



MODEL No. 10.



MODEL No. 9.



MODEL No. 11.

### AUTOMOBILE TRAFFIC GROWTH IN NEW YORK.

Figures relating to the traffic of Fifth Avenue, New York, obtained as a result of twenty-four hours' checking of all vehicles passing a given point, were, says the New York Globe and Commercial Advertiser, given in the course of the Ahearn hearing before Gov. Hughes by J. W. Howard, the well-known paving expert of New York. The statistics were obtained by Mr. Howard and several assistants but a few days ago.

During the dullest hour of the twenty-four—from 2 to 3 A. M.—27 vehicles passed, of which 5 were automobiles, and only between 5 and 6 A. M. were motors unrepresented.

Comparing Fifth and First Avenues:




Diagram of Vehicle Traffic in New York. A. Total traffic on Fifth Avenue. B. Auto. traffic. C. Total traffic on First Avenue.

During the eleven hours from 7 A. M. to 6 P. M., there passed between Twenty-sixth and Twenty-seventh streets, on First Avenue, 4,445 vehicles. In the same period on Fifth Avenue, in the block between Fifty-eighth and Fifty-ninth Streets, the number counted was 7,857. The twenty-four-hour traffic on Fifth Avenue from Fifty-eighth to Fifty-ninth Street amounted to 10,379 vehicles, whereas that of First Avenue was but 2,665. From 12 P. M. to 1 A. M. the latter was practically deserted, whereas on Fifth Avenue there were 200 vehicles recorded. Between 4 and 5 in the afternoon on Fifth Avenue 1,100 vehicles were counted in one hour. The detailed traffic tables giving the number of vehicles for each hour of the twenty-four, separating the motors from the horse-drawn conveyances are full of interesting and suggestive comparisons.

Traffic on First Avenue, from noon to noon, October 9-10, at a point just north of Seventy-seventh Street:

### THE BEST LIGHT

The most brilliant, economical light made. Our light gives 100-candle power at the small cost of 2c per week. Is portable and there is no dirt, grease, odor or smoke. Over 100 different styles—every one warranted. Agents wanted Everywhere. THE BEST LIGHT CO. Owners of Original Patents. 87 E. 5th St., Canton, O.

### For Your Automobile

**Al-Lectro Polish**  
The best polish for fine surfaces. Glass, Silver, Nickel, Brass, Copper, Steel, Aluminum. Small can a dime, will make you a regular customer. At Auto and Hardware Houses, etc. L. B. ALLEN CO., Inc. 1535A Columbia Ave., Chicago. Literature and prices free FOR DEALER'S NAME

### Make Your Own Fertilizer

at Small Cost with WILSON'S PHOSPHATE MILLS From 1 to 40 H. P. Also Bone Cutters, hand and power, for the poultryman; grit and shell mills, farm feed mills, family grit mills, scrap cake mills. Send for our catalog. Wilson Bros., Sole Mfrs., Easton, Pa.

### Wizard Repeating LIQUID PISTOL

Will stop the most vicious dog (or man) without permanent injury. Perfectly safe to carry without danger of leakage. Fires and reloads by pulling the trigger. Loads from any liquid. No cartridges required. Over 6 shots in one loading. All dealers, or by mail, \$6. Rubber-covered holster, \$6, extra. Parker, Stearns & Co., 226 South St., Dept. G, New York

## American Homes and Gardens HISTORIC MANSIONS of THE JAMES RIVER



EVELYN BYRD

### SEPTEMBER, 1907

I. "Brandon," the Home of the Harrisons.

### OCTOBER, 1907

II. "Shirley," the Home of the Carters.

### NOVEMBER, 1907

III. "Westover," the Ancestral Home of the Byrds.

THIS series deals with three of the most beautiful colonial estates along the charming and historic James River. The illustrations are made from photographs taken especially for the purpose by an expert. The series is of unusual interest and beauty. Subscriptions can begin with the September number. Price \$3.00 per year. The three numbers will be sent on publication on receipt of 75 cents. Among the interesting articles in the October number are:

NINETEENTH CENTURY BEDROOMS HOW TO TOUR IN AN AUTOMOBILE GARDENING WITHOUT SOIL

SMALL AMERICAN HOMES PORT SUNLIGHT MILLBROOK FARM

All these articles are beautifully illustrated. 72 large pages, colored cover changing each month.

MUNN & COMPANY, Publishers Scientific American Office: 361 Broadway, New York City

Hours.	Horse vehicles.	Autos.	Total vehicles.
Noon .....	143	1	144
1-2 .....	216	0	216
2-3 .....	256	3	259
3-4 .....	231	3	234
4-5 .....	195	0	195
5-6 .....	199	2	201
6-7 .....	127	1	128
7-8 .....	64	0	64
8-9 .....	44	0	44
9-10 .....	26	0	26
10-11 .....	8	0	8
11-12 .....	7	0	7
Midnight .....	0	0	0
1-2 .....	1	0	1
2-3 .....	8	0	8
3-4 .....	25	0	25
4-5 .....	22	0	22
5-6 .....	56	0	56
6-7 .....	103	0	103
7-8 .....	131	1	132
8-9 .....	180	0	180
9-10 .....	209	1	210
10-11 .....	220	3	223
11-12 .....	177	2	179
Totals .....	2,648	17	2,665

Traffic on Fifth Avenue from noon to noon, October 9-10, at a point just north of Fifty-eighth Street:

Hours.	Horse vehicles.	Autos.	Total vehicles.
Noon .....	536	230	766
1-2 .....	548	184	732
2-3 .....	367	142	509
3-4 .....	693	331	1,024
4-5 .....	766	400	1,166
5-6 .....	588	329	917
6-7 .....	531	275	806
7-8 .....	219	115	334
8-9 .....	205	54	259
9-10 .....	134	75	209
10-11 .....	128	70	198
11-12 .....	130	71	201
Midnight .....	112	45	157
1-2 .....	48	20	68
2-3 .....	22	5	27
3-4 .....	26	4	30
4-5 .....	53	3	56
5-6 .....	70	0	70
6-7 .....	88	19	107
7-8 .....	191	31	222
8-9 .....	270	187	457
9-10 .....	333	179	512
10-11 .....	505	308	813
11-12 .....	507	232	739
Totals .....	7,071	3,309	10,379

Not the least interesting feature of these figures is the story they tell regarding the motor car. It appears that already more than one-third of the carriage traffic of the city is carried on in automobiles. The twenty-four-hour figures on Fifth Avenue, which may be taken as fairly typical, show 3,309 of the latter against 5,825 hansom, coupes, etc. Probably in carrying capacity the motor cars were very nearly equal to the horse-drawn vehicles, as a considerable proportion of the former have seven places, and few of them less than five, while a large part of the corresponding hay-

motors could carry but three persons, including the driver. It is also of some interest to note that on First Avenue during the same twenty-four hours, but seventeen motor cars of any variety, business or pleasure, were recorded.

#### SOME IMPROVEMENTS FOR THE MOTOR BICYCLE.

A NEW MOTOR CYCLE ENGINE.—The engine illustrated in the accompanying engraving represents three years of work in perfecting a design which should be perfectly suited to the requirements of the motor bicycle. It is a very light engine, weighing only 28 pounds and developing 2½ horse-power on the brake. Its principal claim to novelty lies in the fact



The Mueller Improved 2½ H. P. Motor Bicycle Engine.

that the cylinder is screwed into the crank case instead of being fastened thereto with lugs and bolts. The crank case is formed with an internally threaded cylinder. A setscrew threaded through one side of the crank case bears against the threaded portion of the cylinder to prevent it from being unscrewed. When thus locked there is no danger of the cylinder working loose, and thus are avoided the objections to the usual construction in which the bolts and nuts are often loosened by the vibration of the machine. The screw joint permits of a lighter, as well as a more lasting construction. The power of the motor is sufficient to climb grades of from twenty



Double Roller Bearing for End and Radial Thrust.

to thirty per cent. It may be applied to standard bicycles of 22 or 24-inch frame.

ANNULAR BALL BEARING.—A recent improvement, particularly designed for motor cycles, though also adapted for automobiles, is an annular ball bearing with two rows of balls running in separate ball races and designed to take both radial load and end thrust. The device is, in reality, two bearings in one, and it is claimed that it will bear twice the radial load of other bearings of the same size, and also an end thrust nearly equal to its radial load capacity. Our illustration shows the bearing broken away to reveal the interior arrangement. It will be noted that the balls are kept in place by means of a separator ring which is V-shaped in cross-section, and is formed with semi-circular indentations along the

The great success of my razor is chiefly due to the "GILLETTE" double edged flexible blades.

The "GILLETTE" blade is made of specially selected and tested steel of the very highest grade and is but 6-1000 of an inch thick. Every blade is individually hardened, tempered, ground, honed and stropped by special automatic machinery.

Because of the great strength and flexibility of this blade, the Gillette Safety Razor may be adjusted (by a slight turn of handle) for an easy or a close shave, with either a soft or a harsh beard—no stropping, no honing.

The "GILLETTE" double edged blades are so inexpensive that when they become dull you throw them away, as you would an old pen.

Ask your dealer for the "Gillette" today and shave yourself with ease, comfort and economy for the rest of your life.

*King Gillette*

The Gillette Razor Set consists of triple silver-plated holder, 12 double-edged blades—24 keen edges, packed in a velvet-lined leather case and the price is \$5.00 at all the leading Jewelry, Drug, Cutlery, Hardware and Sporting Goods dealers.


Combination Sets from \$6.50 to \$50.00.

If substitutes are offered, refuse them and write us at once for our booklet and free trial offer.

GILLETTE SALES COMPANY  
207 TIMES BLDG.,  
NEW YORK CITY

**Gillette Safety Razor**  
NO STROPPING NO HONING

## Locomobile



The New "40," \$4,750, Without Top

The new "40" Locomobile combines the proved reliability of six years with increased power, increased efficiency, and low cost of maintenance

Other models \$2,900 up.

All 1908 models have 4-speed selective transmissions, alloy steel springs, and longer wheel bases. Make-and-break ignition with low-tension magneto for the fourth season.

Send for 1908 Catalog

THE Locomobile COMPANY OF AMERICA, BRIDGEPORT, CONN.

NEW YORK, Broadway and 76th Street  
PHILADELPHIA, 245 N. Broad Street

Member Association of Licensed  
Automobile Manufacturers

BOSTON, 400 Newbury Street  
CHICAGO, 1354 Michigan Ave.



### AUTOMOBILES \$100 AND UP

We will mail our large Illustrated Bargain Sheet of new and slightly used Automobiles on receipt of your name and address. This sheet shows accurate photographic views of more than 50 Automobiles offered as low as \$100. Write plainly to


S. GRAHAM AUTOMOBILE CO.

Established 16 years.

601-603-605 Madison St., CHICAGO, ILL.


two edges which fit over the balls. The separator ring rests on the balls without friction at any stationary point. The two rows of balls are designed to distribute the load evenly between them. The bearing may be used as a substitute for end thrust and radial load bearings at present used in most automobiles. In such places as a bevel gear bearing where the line of strain is at right angles with the base of the gear teeth, the thrust is intermediate between the radial and end pressure, and with a bearing, such as here illustrated, this diagonal thrust may be taken care of to the best possible advantage.

TWO-SPEED GEAR.—The primary object of the gear illustrated herewith is to allow a motor cycle to run on the high speed without friction. This is accomplished by bringing the friction band into engagement with the pulley wheel and thus permitting practically the en-



Friction Band in Position for Low Speed.

tire mechanism of the gear to rotate as a single pulley. The usual fiber friction surfaces are dispensed with and the frictional engagement takes place between metal surfaces. When set for low speed the friction band is held stationary and the power is transmitted through step-down gearing connected with the band. The construction will be understood by referring to the sectional views. The power shaft is shown at A, and it carries a sleeve B to which is keyed the pulley C. The latter is provided with a V-shaped groove into which the friction band D is adapted to fit. The friction band is mounted to slide in axial direction on a drum E, to which it is secured by means of pins f on the periphery of the drum and engaging slots in the friction band. A series of spring-actuated plungers e serve to press the band D against the



Position of Parts on High Speed.

pulley C. At the opposite edge of the band D there is a flange which engages a slot formed in the inner periphery of an operating band F. The latter is provided with ratchet teeth f adapted to engage ratchet teeth g on a stationary band G secured to the crank box. Owing to the ratchet form of the teeth when the operating band F is rotated, it is moved axially away from the stationary band G, withdrawing the friction band D from the groove in the pulley C. Keyed to the shaft A is a pinion H which engages a gear wheel I. The latter is keyed to a pinion K, which is mounted on a shaft J journaled in the drum E. The pinion K in turn engages a gear L, formed on the sleeve B.

When the mechanism is set for high





## Commercial Power Wagons

# Your Delivery Problem Solved




Model D 11, 1 Ton. \$1600

Cut the cost down—increase the capacity of your delivery service—and advertise your store as modern and up-to-date, by installing Rapid Cars.

We have furnished complete and modern delivery equipment for hundreds of the most prominent merchants in the country. Our Rapid Delivery cars will replace from 3 to 5 horse-drawn vehicles, and give better satisfaction to you and your customers.

We make over twenty standard designs of modern commercial cars, including light and heavy delivery wagons, baggage trucks, hotel busses, hospital ambulances, fire engines, telephone service wagons, sightseeing cars, and other power wagons for commercial use. Besides these we design special bodies to meet our customers' requirements when needed. Every car guaranteed. Price from \$1600 to \$4000. Write me about your delivery problems. I will tell you all about the successful "Rapid" line. See our exhibit at the New York Automobile Show.



Model D 62, \$1600

G. S. HENRY, Sales Manager

Rapid Motor Vehicle Co., Pontiac, Mich.

speed the operating band *F* is turned to permit the friction band *D* to engage the pulley. No relative motion can take place between pinion *K* and gear *L* because the drum *E* and pulley *C* are locked together by the band *D*, hence the power transmitted from shaft *A* through pinion *H* to the gear *I* serves to turn the drum and pulley as a single pulley. For the low speed the friction band *D* is withdrawn by a turn of the operating band *F*, and brought into engagement with the stationary band *G*. This serves to keep the drum *E* stationary. The power of shaft *A* is then transmitted through pinion *H*, gear *I*, pinion *K*, to gear *L* on the sleeve *B*, thus driving the pulley *C*, which is



Novel Two-Speed Gear for Motor Bicycles.

keyed to this sleeve. The gearing is arranged to step down the speed the required amount. If the operating band is moved sufficiently to carry the friction band *D* clear of the pulley *C* and fixed band *G*, the engine will run free, for the drum *E* will then turn idly without transmitting any power to the pulley *C*.

The inventor of this ingenious speed gear is Dr. Sherman T. Lewis, of Room 1018 Hartford Building, Chicago, Ill.

### A NOVEL FLOATLESS CARBURETER.

The carbureter shown in partial section in the accompanying illustration is an extremely simple device, with less parts to give trouble than are found in the usual automatic float-feed carbureters now generally in vogue. The gasoline enters through the feed pipe, seen at the bottom, and flows upward through a vertical pipe, 1, to a horizontal feed needle valve, *V*. This valve is operated by a vertical lever and clapper, *J*, which has a weighted disk, *W*, for the purpose of returning the valve to the closed position. The suction of the motor, as it draws air in through the inlet, *I*, causes the clapper to move inward, and the feed valve to open. The fuel, as soon as it passes through this valve, flows downward through the adjoining vertical pipe, 2, and then upward once more, through the spray nozzle pipe, 3. This pipe terminates at its upper end in a spray nozzle, and contains a needle valve, *F*, which

## Do You Want Good Information Cheap?

Write to us and we will refer you to a SCIENTIFIC AMERICAN SUPPLEMENT that will give you the very data you need.

SCIENTIFIC AMERICAN SUPPLEMENT articles are written by men who stand foremost in modern science and industry.

Each SCIENTIFIC AMERICAN SUPPLEMENT costs only 10 cts. But the information it contains may save you hundreds of dollars.

Write for a catalogue of SUPPLEMENT articles. It costs nothing.

Act on this suggestion!


MUNN & COMPANY

361 Broadway, New York


Floors



Roofs



Wyckoff, Church & Partridge Garage, New York  
RAYMOND F. ALMIRALL, ARCHITECT



System C, Type I, used in the above building

Clinton Fireproofing System used throughout for floors and roof.

The continuous bond of Clinton electrically welded wire is the ONE best reinforcing for concrete.

CLINTON WIRE CLOTH CO.  
CLINTON, MASS.


Ceilings

FIRE-PROOFING DEPARTMENT  
ALBERT OLIVER  
1 Madison Ave., New York

Seattle: L. A. Korrle, 900 Alaska Building  
St. Louis: Bushnell-Wills Lumber & Cement Co.  
Syracuse, N.Y.: Paragon Plaster Co.  
San Francisco: 335 Monarch Building

Partitions

can be adjusted from below. This valve gives the proper mixture at high speed. The carbureter has a cylindrical throttle sleeve, *E*, which is moved by the lever, *B*. By means of suitable connections within, when the throttle is closed, another needle valve, *D*, located above the spray nozzle, is brought down into the latter, and has a throttling effect. This extra spray nozzle serves to keep the mixture uniform, for when the throttle is closed, on account of the small passage for the gas, the suction is very much increased at the spray nozzle, and there



The Miller Floatless Carbureter Shown in Partial Cross-Section.

is a tendency to get too rich a mixture. The lever, *A*, seen on top of the carbureter, operates another sleeve on the opposite side of the spray nozzle to the throttle sleeve, and makes it possible to decrease the size of the orifice for the gas in case this is too large to obtain the proper suction. The Automobile Editor of this journal has given this new carbureter a thorough trial upon a double-opposed-cylinder motor of the air-cooled type, and also upon a standard 4-cylinder, vertical motor. In both cases the carbureter has given very good satisfaction and proved its economy. As there is no float or float-operated needle valve, trouble from these sources is obviated. Another good point about the carbureter is that there is so minute a quantity of gasoline in it at any time that there is no danger of fire in case of a back fire from the motor. For air-cooled engines, especially, this carbureter will be found to give excellent satisfaction, as the needle valve which controls the fuel can be closed almost to the limit, and the mixture fed to the motor can be made so poor that there is little danger of the engine overheating and giving premature explosions, even though there are carbon deposits in the cylinder heads. The inventor of this carbureter is Mr. John H. Miller, of 94 Denver Avenue, Bridgeport, Conn.

#### SINGLE VIBRATOR APPARATUS FOR SYNCHRONIZING THE IGNITION SPARKS OF MULTIPLE-UNIT COILS.

This device is intended to eliminate the difference in adjustment and difference in time element of the various vibrators on the spark coil.

From the diagram it will be seen that the battery wires are transferred from the coil to the master vibrator or synchronizer, and that there is a wire which runs from the center binding post on the synchronizer to one of the battery binding posts on the coil. This places the synchronizer in series with the battery and coil, or with the magneto and coil, so that no matter which unit in the coil the timer closes the circuit on, this master vibrator vibrates for it, in place of the regular vibrator on that particular coil. Each vibrator on the coil is short circuited, as shown in the diagram, so that the current does not pass through the vibrators of the coils, but goes around them through the copper wire shunt, after which it goes through the large twin-blade vibrator of the Lacoste type. This is connected to a condenser of large capacity and having its layers of tinfoil




Diagram Showing Connections.

so far apart that it is practically puncture proof.

It matters not within reasonable limits what the adjustment of this vibrator is, for it vibrates for every cylinder, and no matter what its time lag is, this is the same for every cylinder, thus giving exact synchronism, and placing the sparks in every cylinder at exactly the same position of the piston and the same angle of the crankshaft, just as would a high-tension distributor and a single coil. It possesses an advantage, however, over the high-tension distributor system, for it does the synchronizing on the low-tension side of the circuit, and does not require any high-tension distributor with its consequent troubles. This device was one of the novelties at the auto shows.

#### LATEST IMPROVEMENTS IN THE FRANKLIN AIR-COOLED ENGINE.

(Continued from page 322.)

The illustration. The large lower washer is on the exhaust valve, while the smaller washer and spring are on the inlet valve. Each valve is operated by independent rocker arms. The push rods which operate these rocker arms fit into adjustable ball-and-socket joints on the latter. The incoming charge of cold gas makes its entrance through the port, 4, and the inlet valve. In doing this it passes through the hollow exhaust valve, 3, which it tends to cool.

About 60 per cent of the burnt gases are discharged through the auxiliary exhaust valve, the result being that only 40 per cent of these gases pass through the exhaust valve proper. As a consequence, this valve does not have the tendency to warp that does the exhaust valve of an ordinary air-cooled motor, and this despite the fact that the valve in this instance is a mere shell. On account of the rounding head of the cylinders, the interior surface of these is the smallest possible. This assures the use in work of the greatest number of heat units in the charges of gas, and, as a consequence, the new engine is more eco-

# Rambler Automobiles

For the year 1908 the entire facilities of the Rambler factory will be devoted to the production of two Models, 34 and 31.

**Model 34**, a five-passenger touring car with four-cylinder vertical motor, 32 horse power, has selective type transmission with shaft drive. The wheel base is 112 in., wheels 36 in., with 4 in. tires. Price, fully equipped, \$2,250. The same chassis, however, with appropriate changes in detail, will be equipped with a roadster body with rumble seat, at the same price.

**Model 31** is a five-passenger touring car with detachable tonneau, equipped with the Rambler unit power plant, comprising double opposed motor, multiple disc clutch and planetary transmission entirely enclosed. Price, fully equipped, \$1,400. This model can be furnished with torpedo deck in lieu of the tonneau, at \$1,300.

Both models have been brought to the highest possible degree of perfection in every detail that insures

#### Service, Economy and Comfort

A complete line of 1908 Ramblers will be shown at a private exhibit at the salesrooms of the Homan & Schulz Company, 38-40 West 62nd Street, New York City, during both New York Automobile shows.

You cannot afford to miss making a critical inspection of these 1908 models of

## The Car of Steady Service.

Advance catalog now ready; write for a copy today

**Thomas B. Jeffery & Company**  
Main Office and Factory, Kenosha, Wis.

Branches and Distributing Agencies: Chicago, Milwaukee, Boston, Philadelphia, San Francisco. Representatives in all leading cities.



Typewriters come and go,  
but the machine that always  
stays, always leads, always  
improves, always outwears,  
and always outsells all others  
is the

# Remington

Remington Typewriter Company

(Incorporated)  
New York and Everywhere

nomical, if anything, than the old one. All the valves in the new engine are mechanically operated from a single cam shaft. In this new model, too, the fan is driven positively by bevel gears. The cylinders are oiled by splash lubrication, and a rather high level of oil is maintained in the crank cases by means of a gear-driven mechanical oiler. Baffle plates are fitted at the base of each cylinder, and these cause the oil to be drawn up by the piston suction through an opening on the working or thrust side of the piston, where it is most needed, and from which point it gradually works around to the other side. Two of the larger types of Franklin cars are this year fitted with a gear-driven Bosch high-tension magneto in addition to the usual dry battery and coil ignition. The same multiple-disk clutch that was used last year is found located in the flywheel of the 1908 engine. The only improvement which it seems possible to make on this powerful, light-weight motor, seems to be the employment of non-adjustable ball bearings on the crankshaft in place of the plain bearings now used. Perhaps, after another year, this style of bearing will be tried.

#### THE NATIONAL 6-CYLINDER ENGINE.

(Continued from page 322.)

and inlet pipes on one side of the engine, and water and exhaust pipes on the opposite side. All joints are made with tapered nipples. The piping can be quickly removed after taking off one or two nuts. The distributor is now run up between two of the cylinders, instead of being placed at the back end of the engine as heretofore. The water pump, mechanical oiler, and Bosch high-tension magneto are all gear-driven. The magneto is connected to the gear on the front of the engine through a universal joint. It is fastened to the engine by a brass band, which passes over its top, and is held down by a couple of thumb nuts. It is, therefore, very easily removed, if necessary. All six cylinders are provided with two spark plugs, one of which is fed from the magneto, and the other from a single coil and distributor supplied by a battery. The material used in the engine cylinders and pistons is cast iron of an extra strong, special, fine-grained variety. The pistons are made somewhat longer than heretofore. While there are no radical changes, the engine shows many refinements and small improvements conducive to quietness of running, lack of vibration, and long life.

#### THE NEW STODDARD-DAYTON ENGINE.

The new engine brought out by the Dayton Motor Car Company, owing to complete changes in design and construction, is one of the most efficient and well-constructed motors on the market to-day. As can be seen from the illustration, the water-jacketed valve chambers surmount the cylinders, and form part of two integral castings. The inlet and exhaust valves are upon opposite sides, and each pair of valves is operated by a double rocker arm having a central roller bearing provided with a grease cup. Each pair of cylinders is fitted with a copper water jacket having four corrugations. The water is circulated by a centrifugal pump of generous size, which is gear-driven from the cam shaft. The shaft which drives the pump also rotates a Bosch high-tension magneto, which is located upon a bracket at the rear of the motor, if the purchaser desires magneto ignition.

The 30-35-horse-power motor shown has a bore of 4 1/4 inches and a stroke of 5 inches. The valves are all 2 1/4 inches in diameter. The crankshaft is a drop forging of nickel steel and is offset 1/4 of an inch from the center of the cylinders. This offset gives the greatest leverage, and reduces to a minimum the friction of the pistons on the side walls of the cylinders. The bearings are all positively oiled by a stream of lubricant, which is drawn from an oil well separate from the



crank case proper, and is forced to all the bearings by means of a gear pump. Special oil rings fastened to the crank cheeks carry the oil which comes from the crankshaft bearings, and feed it by means of centrifugal force to the pins. The camshaft bearings are also positively oiled. The fan is mounted upon two Timken roller bearings, and is provided with a thumb-screw adjustment for tightening the belt. The flywheel is bolted to a flange, which is forged on the end of the crankshaft.

The transmission is mounted in an aluminium case formed of one solid casting, and all the bearings in the transmission are of the roller type. There is not a nut or screw anywhere in the gear box which can loosen and get into the gears. The telescoping shaft of the transmission is fitted with a long, plain, roller bearing, while all the other bearings are of the Timken type. The gears are all made of chrome nickel steel, and the shafts of a special high-carbon steel. Both the propeller shaft and the floating rear axle run on Timken roller bearings. Internal and expanding brakes are fitted on the rear wheels, and consist of steel bands lined with camel's hair belting. The internal brake bands are 2½ inches wide, and are operated by a pedal. The other brakes are operated by a lever beside the driver's seat, and it is also possible to use the motor as a brake by cutting off the ignition. By opening the auxiliary air valve, which can be done from the seat, the motor will draw in only pure air while it is being used for braking. The ordinary ignition equipment of the motor consists of a four-unit coil and storage batteries, and the magneto is only fitted in case two systems are desired.

#### THE HEWITT 8-CYLINDER 90-DEGREE MOTOR.

(Continued from page 323.)

placed in valve chambers on the upper sides of the cylinders. A single cam shaft within the crank case and between the cylinders operates all the valves. The connecting rods and pistons, while light, are still strong and substantial. On account of the perfect balance of all the parts, the motor can be speeded from 250 to 2,500 revolutions a minute without trouble. The 50 to 60 horse-power engine which we illustrate has cylinders of 4 inches bore and 4½ inches stroke, and develops its rated horse-power at 850 to 900 R. P. M.

#### THE CARTER TWO-ENGINE CAR.

(Continued from page 323.)

Inventor claims one horse-power for every 75 pounds of total weight. He has carried his ideas still further in the construction of both 4 and 6-cylinder water-cooled cars having twin radiators and engines (that is, two 4-cylinder engines or two 6-cylinder engines). The advantage of the duplex radiators is said to be quite as great as that of the duplex engines; and as far as economy is concerned, the inventor claims that his system is more economical of fuel than the usual system of employing but one high-powered engine.

#### THE 1908 PEERLESS MOTORS AND TRANSMISSION.

Although the Peerless Motor Car Company has brought out a new 6-cylinder model for 1908, this has not been done altogether because the officers believe the 6-cylinder to be superior to the usual 4-cylinder. Mr. Charles Schmit, engineer and designer of the Peerless Company, spent some six months abroad visiting the different factories, before he designed and manufactured his first 6-cylinder car. He has been engaged during the past year in perfecting this car, and the company is now ready to place it upon the market. The trial car of this type will be seen illustrated on page 323. The new 6-cylinder motor does not differ from the 4-cylinder motor essentially, the only difference being that there are

#### Wood-working Machinery

For ripping, cross-cutting, mitering, grooving, boring, scroll-sawing edge moulding, mortising for working wood in any manner. Send for catalogue A. The Seneca Falls M'g Co., 105 Water St., Seneca Falls, N. Y.



#### Engine and Foot Lathes

MACHINE SHOP OUTFITS, TOOLS AND SUPPLIES. BEST MATERIALS. BEST WORKMANSHIP. CATALOGUE FREE. SEBASTIAN LATHE CO., 120 Culvert St., Cincinnati, O.

#### Keystone Well Drills

for Artesian and Ordinary Water Wells. Manual, Hand and Power Drilling. Placer Testing for Druggists. Deep Drilling for Oil and Gas. Custom-made Hole Drilling. River and Harbor Exploration, etc. Our five catalogues are sent free in these lines. KEYSTONE WELL WORKS, Beaver Falls, Pa.

#### Noteworthy Articles

##### ON TIMELY TOPICS

Each number of the Scientific American Supplement costs 10 cents by mail.

**SEWAGE AND ITS DISPOSAL.** A review of modern methods. By H. LEMMOIN-CANNON. SCIENTIFIC AMERICAN SUPPLEMENT 1551.

**ELECTRIC LIGHTING FOR AMATEURS.** How a small and simple experimental installation can be set up at home. SCIENTIFIC AMERICAN SUPPLEMENT 1551.

**CHEMICAL AFFINITY.** Simply explained by SIR OLIVER LODGE. SCIENTIFIC AMERICAN SUPPLEMENT 1547.

**CASE-HARDENING.** By DAVID FLATHER. SCIENTIFIC AMERICAN SUPPLEMENT 1547.

**ELECTRIC IGNITION SYSTEMS.** A comprehensive article by R. W. ROBERTS. SCIENTIFIC AMERICAN SUPPLEMENT 1546.

**CONCRETE.** A general article on its merits and defects. SCIENTIFIC AMERICAN SUPPLEMENT 1545.

**REINFORCED CONCRETE.** Some of its principles and applications with practical illustrations. SCIENTIFIC AMERICAN SUPPLEMENTS 1547, 1548, 1551.

**ELECTRONS AND THE ELECTRONIC THEORY** are discussed by SIR OLIVER LODGE in SCIENTIFIC AMERICAN SUPPLEMENTS 1428, 1429, 1430, 1431, 1432, 1433, 1434.

**THE PANAMA CANAL** is described from the engineering standpoint in SCIENTIFIC AMERICAN SUPPLEMENT 1559.

**WIRELESS TELEGRAPHY.** Its Progress and Present Condition are well discussed in SCIENTIFIC AMERICAN SUPPLEMENTS 1425, 1426, 1427, 1386, 1388, 1389, 1393, 1381, 1527, 1528, 1529, 1431.

**HOW TO CONSTRUCT AN EFFICIENT TELEGRAPH APPARATUS AT SMALL COST** is told in SCIENTIFIC AMERICAN SUPPLEMENT 1363.

**SUBMARINE NAVIGATION.** An exhaustive review of the subject is published in SCIENTIFIC AMERICAN SUPPLEMENTS 1414, 1415, 1222, 1223.

**SELENIUM AND ITS REMARKABLE PROPERTIES** are fully described in SCIENTIFIC AMERICAN SUPPLEMENT 1430. The paper is illustrated by numerous engravings.

**THE INTERNAL WORK OF THE WIND.** By S. F. LANGLEY. A painstaking discussion by the leading authority on Aerodynamics, of a subject of value to all interested in airships. SCIENTIFIC AMERICAN SUPPLEMENTS 946 and 947.

**LANGLEY'S AERODROME.** Fully described and illustrated in SCIENTIFIC AMERICAN SUPPLEMENTS 1404, 1405 and 1546.

**STEAM TURBINES.** Their Construction, Operation and Commercial Application. SCIENTIFIC AMERICAN SUPPLEMENTS 1306, 1307, 1308, 1422, 1400, 1447, 1370, 1372, 1521. The articles have all been prepared by experts in steam engineering.

**PORTLAND CEMENT MAKING** is described in excellent articles contained in SCIENTIFIC AMERICAN SUPPLEMENTS 1453, 1463, 1466, 1510, 1511.

**AERIAL NAVIGATION.** Theoretical and Practical Discussions. Pictures and Descriptions of actually-built dirigible balloons and aeroplanes will be found in SCIENTIFIC AMERICAN SUPPLEMENTS 1161, 1149, 1150, 1151, 1404, 1405, 1413, 1453.

**THE TANTALUM LAMP.** A full illustrated description of a lamp having a metallic filament and burning at once without preliminary heating appears in SCIENTIFIC AMERICAN SUPPLEMENT 1523.

**THE WATERPROOFING OF FABRICS** is thoroughly discussed in SCIENTIFIC AMERICAN SUPPLEMENT 1522 by an expert.

**THE SPARK COIL, ITS CONSTRUCTION AND MAINTENANCE.** Is the subject of a painstaking article in SCIENTIFIC AMERICAN SUPPLEMENT 1522.

**ELECTRIC IGNITERS FOR GAS ENGINES** are discussed in SCIENTIFIC AMERICAN SUPPLEMENT 1514.

**CARBURETERS,** a subject of immense importance to automobilists and the users of oil engines, is well treated in SCIENTIFIC AMERICAN SUPPLEMENT 1508.

**EPICYCLIC TRAINS,** which play an important part in toothed gearing, are ably described in SCIENTIFIC AMERICAN SUPPLEMENT 1524.

Each number of the Scientific American Supplement costs 10 cents by mail.

MUNN & COMPANY  
361 Broadway New York

three pairs of cylinders instead of two. Our illustration gives a very good idea of the appearance of the 1908 30-horse-power 4-cylinder motor. This engine has cylinders of 4¼ inches bore by 5½ inches stroke. With this bore and stroke, one can readily see that the rating of 30 horse-power is merely nominal. Imported material is used largely in the construction of this motor. The cylinders and pistons are imported castings, and much of the steel, such as the valves, etc., is made of silico-manganese alloy. The crank case is a single aluminium casting made in the factory, and designed especially for strength and non-leakage of oil. There are special pans at the bottom of the crank case for the collection of dirt and sediment, and this can readily be removed by taking out a plug. The connecting rod and crankshaft bearings can readily be adjusted by removing these plates on the bottom of the crankcase compartment. Splash lubrication is employed, the level in the crank case being maintained by special feed pipes from the mechanical oiler, which also supplies lubricant to all of the cylinders. The crankshaft is a solid drop forging, specially treated, hardened, and ground accurately to size. The front bearing is a ball bearing of the annular non-adjustable type, and it is fitted with a stuffing box to prevent leakage of oil. This type of bearing has been used in this place in order to shorten up the motor. All of the other bearings are plain. The two-to-one gears and other gears which drive the magneto, timer, etc., are completely housed and run in oil. In accordance with the usual practice now, the fan is positively driven by bevel gears. Great care is exercised in balancing perfectly all the working parts of the motor, and in order to do this all these parts are accurately weighed before they are assembled.

Instead of being located in the casing with the two-to-one gears as heretofore, the governor is now placed on the shaft which drives the gear water pump, and which is located on the left-hand side of the motor. The neat manner in which this governor is incased can be seen by a glance at the illustration. The rounded enlargement at the forward end of the aluminium casting which forms the crank case contains the two balls of the governor. These balls are rather small and light, but they have weight enough to operate the piston valve of the carburetor by means of suitable lever connections extending to the other side of the motor, where the carburetor is located between the two middle cylinders at the side of the crank case. The carburetor is of the usual type, with an automatic air valve, and the throttle is controlled by a hand lever on the steering wheel, by an accelerator pedal, and by the governor. The governor maintains the speed of the motor at the point which corresponds to the setting of the throttle lever on the steering wheel.

The motor is fitted with two separate ignition systems and two separate sets of plugs. There is the usual battery and coil system, and there is also an Elsemann high-tension magneto. The two systems are entirely independent, and can be used separately or together, as desired. The lead of the magneto armature can be changed by a special shifting collar that moves a sleeve with a spiral slot which surrounds the end of the armature shaft. The shifting collar and lever for operating the same can be plainly seen in the front view of the motor. All the wires are neatly incased in fiber tubing, and are made as short as possible. There are no thumb nuts to loosen in removing the wires, as they are all attached by means of spring clips. The commutator is located upon a vertical shaft brought up between the two pairs of cylinders. The commutator is built exactly like the commutator of a dynamo, it being made of eight copper segments, four of which are dummy segments, and the segments being insulated by mica. Great care is



Ask any conscientious dealer what are standard woollens. He will answer Jaeger. Ask any leading physician what is the best health underwear. He will answer "Jaeger." Can you afford to disregard such endorsement?

Write for samples and booklet of particulars.

Dr. Jaeger's S. W. S. Co.'s Own Stores  
New York: 106 Fifth Ave., 22 Maiden Lane.  
Brooklyn: 504 Fulton St. Boston: 228 Boylston St.  
Phila.: 1516 Chestnut St. Chicago: 82 State St.  
Agents in all Principal Cities

#### CORRECT STROPPING

There's a knack in stropping a razor. It's clearly explained in our free catalogue. It will pay you to send for it and learn about

#### Torrey Straps

and how to use them.  
A Torrey Strap costs 50c. to \$2.50 and your money back if not satisfied. Sent, post paid, if not at dealer.

Torrey's Cut-Edge Dressing keeps any strap soft and pliable. Use, or send by mail upon receipt of price. Torrey razors are the finest razors made.

J. R. TORREY & CO., Dept. 6, Worcester, Mass.

#### Kerosene Oil Engines

Marine, Stationary, Portable

NO DANGER. Maximum Power. Lightest Weight. Simple. Reliable. Economical. No Batteries. Self Ignition by Compression. Fully guaranteed. Write for Catalogue & A. 15¢ No charge for packing.

INTERNATIONAL OIL ENGINE CO.  
38 Murray St., New York, U. S. A.

#### Would You "Make the Round Trip" Without Uncertainty?

Investigate the Hildreth Marine Motors

We are ready to "SHOW YOU"

Send for valuable facts about Marine Motors.

THE HILDRETH MFG. CO.  
100 Sheridan, Lansing, Mich., U. S. A.

#### How to Run an Auto

Are You Interested in Automobiles?

If you are, an early purchase of "HOW TO RUN A SELF-PROPELLED VEHICLE" will prove a good investment.

This work is now the accepted standard on the practical care and management of motor cars—explaining the principles of construction and operation in a clear and helpful way, and fully illustrated with many diagrams and drawings. The presentation of subjects has been determined by consideration of the needs of the new automobilist. It is clear and concise in its treatment, and comprehensible to the most inexperienced automobilist, at the same time it is so thorough that the expert will learn much from its pages. This good book will be sent to any address in the world, postpaid, upon receipt of two dollars, or if desired, will be sent on approval to be paid for after examination. Contains 66 pages, over 60 diagrams and illustrations, printed on one paper, size 5½ x 7½ inches with generous margins. Good binding. Highly endorsed.

No Money in Advance Required. Size and Return.

These Andel & Co.'s "How to Run a Self-Propelled Vehicle" will immediately remit \$2.00 or return book to you.

NAME ADDRESS DATE



## Classified Advertisements

Advertisements in this column are 50 cents a line. No less than four nor more than ten lines accepted. Count seven words to the line. All orders must be accompanied by a remittance. Further information sent on request.

### BUSINESS OPPORTUNITIES.

**EQUIPPED FOR GIVING GOOD SERVICE.**—Best of references. Will accept good agencies. For full information address: Bertrando, Negodante, 214 Calle Méjico, Buenos Ayres.

**GOOD OPPORTUNITY FOR AMERICAN MANUFACTURERS.**—An official stock exchange broker in Madrid would accept the representation of a few American Manufacturers. New patented articles preferred. Cash with order. English Correspondence. References: Any Banker in Madrid or the Board of the Stock Exchange. Address: G. L. Quenda, Lagasca St. Madrid, Spain.

**LET US MARKET YOUR PRODUCT.**—We want a patented article of merit, and have abundant capital and excellent organization to sell your goods. Offices in 12 cities. Full description necessary to secure attention. W. J. S., Box 1, New York.

**PATTERN LETTERS AND FIGURES (White Metal and Brass)** for use on patterns for castings. Large variety, prompt shipments. Send for catalog. H. W. Knight & Son, Seneca Falls, N. Y.

**INVENTORS.**—Send for free sample copy "World's Progress," devoted to interests of inventors. All latest developments in scientific and industrial world. World's Progress, 501 12th St., Washington, D. C.

**M. M. FOR 1908 BEST MOTORCYCLE** proposition on earth. All new features. 54 H. P. Newly designed frame. New M. M. spring forks. Write for details and Catalogue. M. M. Motor Co., Brockton, Mass.

### AGENTS WANTED.

**AGENTS WANTED.**—Big profits: Gre-Solvent cleans hands instantly; removes grease, paint, ink, etc.; every mechanic has; get sample and terms. Utility Co., 60 West 4th Street, New York.

**EXCLUSIVE AGENCIES GIVEN.**—We want a good man in every town to sell first-class electrical specialties during spare hours to houses, stores and especially factories. Many centers and good big profits. Write for our Sole Agency. Hill-Wright Electric Company, 128 Reade Street, New York City.

### PATENTS FOR SALE.

**FOR SALE.**—U. S. Patent No. 842,807, improved plow for unloading ore for double track work. The chief improvement on the machine the dirt can be carried out ten or twelve feet or far enough from the old grade to make new grade with one operation, thus saving half the expense. This is a great labor saving machine and will bear close inspection. For particulars inquire Peter McNeer, N. St. Paul, Minn.

**SAV MR. CAPITALIST.** U. S. Patent No. 808,409. Canadian Patent No. 167,281 Cooking Utensil for Camps, indispensable for any one using an open fire to cook by, also very useful in the home. IS FOR SALE. If you are a live man, let me hear from you. Profits enormous. Hundreds of Thousands of Sportsmen and Outdoor People will buy it on sight. For descriptive particulars, etc., address Chas. A. Vogler, Baker, Washington, U. S. A.

**FOR SALE.** American patent rights on Reinforcing Bar for concrete construction. Patent No. 897,631. For full particulars address A. V. Heyburn, Jr., 121 Montrose Place, St. Louis, Mo.

**FOR SALE.** Alligator Socket Wrench Patent 961,000, specially adapted to turn staybolt in steam boilers, etc. Simple and handy for hand and motor. Address for full particulars Victor Hansen, Sparks, Nev.

### TYPEWRITERS.

**START MAKING MONEY** by buying a reliable rebuilt typewriter. Remingtons, 615 Lexington, Caligraphs, Williams, Blickensderfers, Franklins, \$10 up. Rentals, repairs. "Atlantic" Typewriter Co., Dept. S, 245 B'way, N. Y.

**PATENTED ARTICLES** in wire, brass and other metals made to order. Stamping, press work. Prices reasonable. Also prices to low prices to established trade. The Fletcher Mfg. Co., Paterson, N. J.

**TYPEWRITER "Bargain List"** free. Deal direct, save agents' commissions. Underwoods, Remingtons, Oliverts, \$25 others \$10, \$25, shipped on trial. Old Reliable, Consolidated Typewriter Co., 361 Broadway, N. Y.

### MACHINERY.

**THE "IDEAL"** is the only DRILL GRINDER that will sharpen small drills 1/4 inch down to No. 70. It costs little, does much, and is durable. Ideal Machine Works, Brooklyn, N. Y.

### MOTION PICTURES.

**THE MOVING PICTURE WORLD**, weekly, 10 cents per copy; yearly subscription, \$2. The only paper devoted to the moving picture, illustrated song and lantern lecture field. Moving Picture World, Box 460, N. Y.

**WANTED.**—Addresses of enterprising men contemplating entering the moving picture business. Biggest paying proposition for small capital known. Write for information. The Actograph Co., 50 Union Square, N. Y.

### MODELS & EXPERIMENTAL WORK.

**EXPERIMENTAL WORK.**—Machines designed for special purposes and built to order. Sample, sketch or blueprint for estimate. Hull Brothers, 30 Hudson Street, Jersey City, N. J.

### BOOKS AND MAGAZINES.

**ELECTRICIAN AND MECHANIC.**—Practical monthly magazine for electrical and mechanical students and workers. Publishes illustrated directions for constructing dynamos, motors, gasoline engines, wireless telegraph, electroplating, electrical wiring, mechanical drawing, using tools, furniture construction, boat building, all kinds of mechanical work. One dollar yearly; trial subscription for three months, twenty cents. List of electrical and mechanical books free. S. A. Sampson Pub. Co., 6 Beacon St., Boston, Mass.

### CORRESPONDENCE SCHOOLS.

**PATENT LAW AND OFFICE PRACTICE BY MAIL.** Free booklet and specimen pages of thoroughly practical course. Price reasonable. Correspondence School of Patent Law, Dept. A, 1883 Mintwood, Wash., D. C.

### SCHOOLS AND COLLEGES.

**PRACTICAL INSTRUCTION** in the engineering use of Algebra, Geometry, Trigonometry, Conic Sections, Rule, Planimeter, Perspective and Scales. All by mail. Geort Blauw, 25 Broad St., 20th floor, Room 12, N. Y. City.

### PHOTOGRAPHY.

**AMERICAN PHOTOGRAPHY** succeeds American Amateur Photographer. Camera and Dark Room and Photo Season. The editors of each now join in making a magazine which should be in the hands of every photographer, professional or amateur. It costs monthly, \$1.50 per year. Three specimen copies for a quarter. Am. Photographic Pub. Co., 361 Broadway, New York.

### TALKING MACHINE NEEDLES.

**I SEND FREE** samples of patented improved Putnam's Multi-tone Needles to all interested in talking machines. Each needle plays 10 records. Millions sold weekly. Putnam's, 361 Broadway, New York.

### DUPLICATORS.

**MULTICOPYING.**—The Bensinger "Rapid" Duplicator, quick, inexpensive, benefits business and professional men. Numerous exact copies, forms, letters, diagrams, music, or anything in pen, typewriter. C. N. Bensinger Co., 34 Stone St., N. Y.

### TIME STAMPS.

**WHAT TIME WAS IT?** Hoggson's time stamps correctly print the date and correct time on any smooth surface the hand can reach. Ten years' successful use. S. H. Hoggson & Co., 228 Fulton Street, New York.

used in grounding the current, this being done by means of a special brush wired to the contact brush, and which bears upon the vertical shaft. Instead of moving the commutator when it is desired to advance the spark, there is a very convenient arrangement which advances the shaft carrying the roller contact brush. This shaft is in two parts, the lower of which is driven by spiral gears from the cam shaft and is connected to the upper half through a movable sleeve with a spiral slot, which can be moved by means of a sliding collar and which thus causes the upper half to turn with relation to the lower.

The flywheel contains the usual internal expanding ring clutch, which is very light, consisting, as it does, of a leather-lined steel band mounted upon an aluminum core. This clutch has given very good satisfaction during the last few years, and it is a type that can be readily adjusted with a screw-driver or a pair of pliers. The transmission used in conjunction with the motor is of the 4-speed selective type. An illustration of this transmission appears on page 325. An improvement worthy of notice is the meshing of the reverse pinion face on with the other gears, and a special cam, which positively locks this pinion out of mesh when it is not in use. The operating rods which slide the gears are now made round instead of square, and are notched so that the gears can be locked in place by means of a suitable latch. Two universal joints are fitted between the engine and transmission as well as in the propeller shaft. Cardan joints are also placed in the rear axle driving shaft on each side of the differential. This arrangement makes it possible to give a slight camber to the rear wheels as well as to the front ones.

The Peerless Company makes a touring car, roadster, limousine, and landaulet with a 30 and a 45-horse-power engine, and the first two models with a 6-cylinder engine of 57 horse-power as well.

### A NEW TWO-CYCLE MOTOR AND TRUCK.

During the last year the two-cycle motor has come into prominence for use on automobile trucks. This is largely due to the fact that the two-cycle motor is of the slow-speed type, and that it has no valves or other parts which can easily get out of order. A good two-cycle engine will run regularly, day in and day out, until the bearings become worn. As this only occurs gradually after a long period of use, the engine will show symptoms of decreasing power, and will give warning that it needs attention. Then, if the owner lays up the truck for a day or two, the bearings can be readily renewed, and the motor will work as well as ever. The simplicity of this type is apparent from a glance at the photograph of the 3-cylinder Reliance motor shown in the illustration on page 323. The cylinders of this motor have a bore of 5 1/2 inches and a stroke of 5 inches. They are cast separately, with an integral water jacket completely surrounding the cylinder and head. The engine is of the usual three-port type, which dispenses with all valves of any kind whatever. The crankshaft is forged from a solid billet of special high-carbon steel, which has a tensile strength of 100,000 pounds. The crank case is cast of nickel-aluminum alloy. The lower half may be easily removed for inspection of the crankshaft and bearings. The latter are of a high grade of Babbitt metal, and they are so arranged that they may easily be removed and replaced. The connecting-rod bearings may be adjusted by removing plates in the side of the crank

## SCHACHT 'AUTO-RUNABOUT

### "THE INVINCIBLE"

As cheap or cheaper than a Horse and Buggy to maintain and will give ten times the service. Motor 12 H. P. two cylinders, four cycle type.

### FRICION DRIVE—GEARLESS

All parts interchangeable, no crawling under car to make adjustments, Simplicity, Durability. Cushion Tires—no more tire troubles. An all the year 'round car. PRICES RIGHT. Send for Catalogue and Details. Up-to-date Agents wanted.

THE SCHACHT MFG. CO., Cincinnati, O.



### Yankee Silent Muffler For Automobiles and Marine Engines



See that the Yankee Muffler is attached to your engine. Thousands of Yankee Mufflers are used on automobiles and boats because they are silent and without back pressure at all speeds of the engine. Made for two or four cycle engines. Every atom of sound is eliminated. The new muffler delivers the smoke in a thin sheet and is quickly evaporated. Made in various sizes from 1/4 to 150 H. P. Catalogue free. B. B. SMITH & CO., Utica, N. Y., U. S. A.

### \$40 MOTORCYCLE

We have the largest line of New and used Motor Cycles, Parts and Supplies in the country, at the lowest prices. Every machine guaranteed. We are the largest and only exclusive Motorcycle House in the world. Send for our 1907 Catalogue. Repulse a specialty.

**Motors and Castings for Air Ships**  
Harry R. Gear Co., 851 McLaran Ave., St. Louis, Mo.

**Convert Your Bicycle into a Motorcycle**  
By using one of our Attachable Outfits. Will fit any wheel. Also machine motors for small boats. Finished motors or rough castings for automobile, marine or stationary. Send stamp for catalogue.

**GAS ENGINE DETAILS.—A VALUABLE** and fully illustrated article on this subject is contained in SUPPLEMENT No. 1292. Price 10 cents. For sale by Munn & Co. and all newsdealers.

### FRICION DISK DRILL

**FOR LIGHT WORK.**  
Has These Great Advantages:  
The speed can be instantly changed from 6 to 1600 without stopping or shifting belts. Power applied can be graduated to drive, with equal safety, the smallest or largest drills within its range—a wonderful economy in time and great saving in drill breakage. Send for Drill Catalogue.

W. F. & JNO. BARNES CO., Established 1875.  
1909 Ruby Street, Rockford, Ill.

TRADE "Cibridge" MARK

**Electric Lights**  
Cost previously nothing when generated by our Type "B" Dynamos  
A complete plant for 2-10 h. p. lamps cost only \$44.00  
We make nothing but first-class, fully guaranteed apparatus.  
Cibridge Electrical Mfg. Co.  
Chicago, Ill. U. S. A.

**SENSITIVE LABORATORY BALANCE**  
By N. Monroe Hopkins. This "built-up" laboratory balance will weigh up to one pound and will turn with a quarter of a postage stamp. The balance can be made by any amateur skilled in the use of tools, and it will work as well as a \$125 balance. The article is accompanied by detailed working drawings showing various stages of the work. This article is contained in SCIENTIFIC AMERICAN SUPPLEMENT No. 1284. Price 10 cents. For sale by MUNN & Co., 361 Broadway, New York City, or any bookseller or newsdealer.

## SELF-EDUCATION

TEACH YOURSELF AND INCREASE YOUR WAGES  
ONLY DRAKE'S PLAINLY WRITTEN PRACTICAL BOOKS  
CAN TEACH YOU WITHOUT THE AID OF INSTRUCTORS

Every volume positively UP-TO-DATE and written in a language so plain that even a child can understand. DRAKE is the largest publisher of Modern Mechanical Books for home and shop study in the world. We publish good books on every mechanical subject. Our large illustrated Catalogue now ready. Sent free.  
**FREDERICK J. DRAKE & COMPANY**  
350 Wabash Avenue CHICAGO, U. S. A.  
In ordering our catalog please mention this paper

## Your Advertising

INSERTED IN THE



would mean its being seen and read by the leading minds in

## EVERY BRANCH OF INDUSTRIAL PROGRESS

The SCIENTIFIC AMERICAN reaches a thinking class of people who buy freely.

They are amply able to purchase any product advertised attractively.

There is no other publication having the same advertising value for your purpose, because it combines the best elements of the technical papers in your particular line with the large result-giving circulation of a general advertising medium.

In one year it carried successfully the advertisements of 298 different lines of goods, from paper clips at 10 cents to ice machinery at \$15,000.

We have a department of experts to co-operate with prospective advertisers.

Will you let us take up your advertising and show you Why?

**MUNN & CO., 361 Broadway, New York**



## CURTISS 1908 WORLD RECORD MOTORCYCLES



Load in Reliability, Handling and Power. See Catalog H and Booklet "Achievements." G. H. CURTISS MFG. CO. Hammondsport, N. Y.

## Home-Made Experimental Apparatus

In addition to the following articles, the Scientific American Supplement has published innumerable papers of immense practical value, of which over 17,000 are listed in a carefully prepared catalogue, which will be sent free of charge to any address. Copies of the Scientific American Supplement cost 10 cents each.

If there is any scientific, mechanical, or engineering subject on which special information is desired, some papers will be found in this catalogue, in which it is fully discussed by competent authority.

A few of the many valuable articles on the making of experimental apparatus at home are given in the following list:

**ELECTRIC LIGHTING FOR AMATEURS.** The article tells how a small and simple experimental installation can be set up at home. Scientific American Supplement 1551.

**AN ELECTRIC CHIME AND HOW IT MAY BE CONSTRUCTED AT HOME.** is described in Scientific American Supplement 1566.

**THE CONSTRUCTION OF AN ELECTRIC THERMOSTAT** is explained in Scientific American Supplement 1546.

**HOW TO MAKE A 100-MILE WIRELESS TELEGRAPH OUTFIT** is told by A. Frederick Collins in Scientific American Supplement 1005.

**A SIMPLE TRANSFORMER FOR AMATEUR'S USE** is so plainly described in Scientific American Supplement 1578 that anyone can make it.

**A H.P. ALTERNATING CURRENT DYNAMO.** Scientific American Supplement 1558.

**THE CONSTRUCTION OF A SIMPLE PHOTOGRAPHIC AND MICRO-PHOTOGRAPHIC APPARATUS** is simply explained in Scientific American Supplement 1574.

**A SIMPLE CAMERA-SHUTTER MADE OUT OF A PASTEBOARD BOX, PINS, AND A RUBBER BAND** is the subject of an article in Scientific American Supplement 1578.

**HOW TO MAKE AN AEROPLANE OR GLIDING MACHINE** is explained in Scientific American Supplement 1582, with working drawings.

**EXPERIMENTS WITH A LAMP CHIMNEY.** In this article it is shown how a lamp chimney may serve to indicate the pressure in the interior of a liquid; to explain the meaning of capillary elevation and depression; to serve as a hydraulic tourniquet, an aspirator, and intermittent siphon; to demonstrate the ascent of liquids in exhaustive tubes; to illustrate the phenomena of the bursting bladder and of the expansive force of gases. Scientific American Supplement 1593.

**HOW A TANGENT GALVANOMETER CAN BE USED FOR MAKING ELECTRICAL MEASUREMENTS** is described in Scientific American Supplement 1584.

**THE CONSTRUCTION OF AN INDEPENDENT INTERRUPTER.** Clear diagrams giving actual dimensions are published. Scientific American Supplement 1515.

**AN EASILY MADE HIGH FREQUENCY APPARATUS WHICH CAN BE USED TO OBTAIN EITHER D'ARSONVAL OR OUDIN CURRENTS** is described in Scientific American Supplement 1618. A plunger battery of six cells, a two-inch spark induction coil, a pair of one-pint Leyden jars, and an inductance coil, and all the apparatus required, most of which can be made at home.

**SIMPLE WIRELESS TELEGRAPH SYSTEMS** are described in Scientific American Supplements 1363 and 1381.

**THE LOCATION AND ERECTION OF A 100-MILE WIRELESS TELEGRAPH STATION** is clearly explained, with the help of diagrams, in Scientific American Supplement 1622.

**THE INSTALLATION AND ADJUSTMENT OF A 100-MILE WIRELESS TELEGRAPH OUTFIT,** illustrated with diagrams, Scientific American Supplement 1623.

**THE MAKING AND THE USING OF A WIRELESS TELEGRAPH TUNING DEVICE.** Illustrated with diagrams, Scientific American Supplement 1624.

**HOW TO MAKE A MAGIC LANTERN.** Scientific American Supplement 1546.

**THE CONSTRUCTION OF AN EDDY KITE.** Scientific American Supplement 1555.

**THE DEMAGNETIZATION OF A WATCH** is thoroughly described in Scientific American Supplement 1561.

**HOW A CALORIC OR HOT AIR ENGINE CAN BE MADE AT HOME** is well explained, with the help of illustrations, in Scientific American Supplement 1575.

**THE MAKING OF A RHEOSTAT** is outlined in Scientific American Supplement 1504.

Good articles on **SMALL WATER MOTORS** are contained in Scientific American Supplements 1494, 1495, and 1496.

**HOW AN ELECTRIC OVEN CAN BE MADE** is explained in Scientific American Supplement 1472.

**THE BUILDING OF A STORAGE BATTERY** is described in Scientific American Supplement 1493.

**A SEWING-MACHINE MOTOR OF SIMPLE DESIGN** is described in Scientific American Supplement 1510.

**A WHEATSTONE BRIDGE.** Scientific American Supplement 1595.

Good articles on **INDUCTION COILS** are contained in Scientific American Supplements 1514, 1522, and 1527. Full details are given so that the coils can readily be made by anyone.

**HOW TO MAKE A TELEPHONE** is described in Scientific American Supplement 946.

**A MODEL STEAM ENGINE** is thoroughly described in Scientific American Supplement, 1527.

**HOW TO MAKE A THERMOSTAT** is explained in Scientific American Supplements 1561, 1563, and 1566.

**ANEROID BAROMETERS.** Scientific American Supplements 1500 and 1554.

**A WATER BATH.** Scientific American Supplement 1464.

**A CHEAP LATHE UPON WHICH MUCH VALUABLE WORK CAN BE DONE** forms the subject of an article contained in Scientific American Supplement 1568.

Each number of the Scientific American Supplement costs 10 cents by mail.

Order from your newsdealer or from  
**MUNN & CO., - 361 Broadway, New York**

case. The crankshaft is provided with suitable counterweights, and at one end a spur gear drives the gear on the mechanical oiler; while the commutator and pump, which are placed on a vertical shaft above and below the center line of the crank case, are each driven by spiral gears. The pump is of the usual gear type, and the carburetor is of the float-feed variety. The company builds a 2, a 3, and a 4-cylinder engine for use on their two, three, and four-ton trucks, respectively. Each cylinder is rated at 15 horse-power, and if any truck is underpowered for the work it has to do, it can be equipped with the next size larger engine. The Reliance trucks are all equipped with a heavy three-speed sliding gear transmission. The final drive is by chain from the countershaft to the rear wheels. The construction throughout is very simple and substantial, and of a kind which should stand up well in use.

## TYPES OF SHOCK ABSORBERS FOR AUTOMOBILES.

(Continued from page 326.)

Another method of retarding excessive spring action by frictional resistance is employed in the Gabriel shock absorber (Fig. 4). Two long strips of finely-tempered spring steel are bolted together at their ends, with steel blocks and thin steel washers between, so as to leave a long, narrow space between the two strips. A steel plate, recessed on each side to hold pads of camel's hair belting, is placed between the long steel strips, the pads of camel's hair belting being next to the inner surfaces of the strips, and causing them to spring apart considerably. A stud in the steel plate projects through a long slot running the full length of one of the steel strips, and this stud is screwed into the frame of the car, just above the middle of the spring. One end of the pair of steel strips is secured to the middle of the car spring by a special angle plate adapted to be held down by the clamps that secure the spring to the axle. As the car rises and falls on its springs, the padded plate slides up and down between the spring steel strips. While the car runs on fairly smooth roads, where spring movement is slight, the movement of the padded plate is confined to the central portion of the device, where there is but little friction, and the free play of the springs is not checked. When rougher roads cause a wider range of spring action, however, the padded plate is moved further up or down toward the ends of the strips, where the space is more contracted and friction is, consequently, much greater. Thus the friction increases gradually as the spring movement increases, whether the movement is upward or downward. The thin steel washers, already mentioned, inserted with the steel blocks between the ends of the strips, can be removed to increase the spring pressure on the padded block, or more can be put in to reduce friction, thus providing a simple means of adjustment. Lateral motion of the car body, or swaying, is provided against by elongating the bolt holes in the top of the device, and by not setting up the bolt at that point very tightly, allowing a little play. Camel's hair belting, it may be said, is remarkably well adapted to resist wear under the conditions imposed here. This material is also frequently used for the facing of brake bands, especially on the contracting and expanding brake bands generally used on the rear-wheel drums of almost all high-powered automobiles.

Springs of special form are utilized in the Shippey shock breaker (Fig. 5). Two flat steel springs, bolted together at their lower ends, curve away from each other toward the top. Extensions of the main springs are carried inward and downward, coming together at the center and acting as auxiliary springs to add to the force holding the main springs apart. This forms the part of the device which is attached to the axle or spring of the



## COMPARE THE COST

TO COVER 25,000 MILES WILL REQUIRE

1 SET SWINEHART'S  
NO REPAIRS  
NO EXPENSE  
NO DELAY  
NO UNCERTAINTY  
NO UNEASINESS

20 PNEUMATIC TIRES  
CONSTANT REPAIRS  
REPLACEMENTS  
DELAYS, INDIGNITIES  
& WORRY, UNCERTAINTY, UNEASINESS

Get our booklet "Proof of the Pudding." Also Catalog "E"

THE SWINEHART CLINCHER TIRE AND RUBBER CO.  
New York City AKRON, OHIO Chicago

## CEMENT

Its Chemistry, Manufacture, and Use

**SCIENTIFIC AMERICAN SUPPLEMENT** 1372 contains an article by A. D. Elbers on tests and constitution of Portland cement.

**SCIENTIFIC AMERICAN SUPPLEMENT** 1396 discusses the testing of cement.

**SCIENTIFIC AMERICAN SUPPLEMENT** 1325 contains an article by Professor William K. Hatt giving an historical sketch of slag cement.

**SCIENTIFIC AMERICAN SUPPLEMENTS** 955 and 1042 give good accounts of cement testing and composition, by the well-known authority, Spencer B. Newberry.

**SCIENTIFIC AMERICAN SUPPLEMENTS** 1510 and 1511 present a discussion by Clifford Richardson on the constitution of Portland cement from a physico-chemical standpoint.

**SCIENTIFIC AMERICAN SUPPLEMENT** 1491 gives some fallacies of tests ordinarily applied to Portland cement.

**SCIENTIFIC AMERICAN SUPPLEMENTS** 1465 and 1466 publish an exhaustive illustrated account of the Edison Portland cement works, describing the machinery used.

**SCIENTIFIC AMERICAN SUPPLEMENT** 1519 contains an essay by R. C. Carpenter on experiments with materials which retard the activity of Portland cement.

**SCIENTIFIC AMERICAN SUPPLEMENT** 1561 presents an excellent review by Bryson Cunningham of mortars and cements.

**SCIENTIFIC AMERICAN SUPPLEMENT** 1553 contains a resume of the cement industry and gives some valuable formulae.


**SCIENTIFIC AMERICAN SUPPLEMENT** 1575 discusses the manufacture of hydraulic cement. L. L. Stone is the author.

**SCIENTIFIC AMERICAN SUPPLEMENTS** 1587 and 1588 contain an able paper by Edwin C. Eckel on cement material and industry of the United States.

Any one of these Supplements will be sent for 10 cents. The entire set costs \$1.60, and constitutes an invaluable text book on the subject.

Order from your newsdealer or from

**MUNN & COMPANY, 361 Broadway, New York**



Almost every comfort, convenience, and luxury of modern life is dependent upon it. Under these circumstances and with the unlimited opportunities that the study of electricity offers for advancement, do you think you can make any mistake by devoting a few hours a day to the study of this subject?

## Cyclopedia of Applied Electricity

Five handsome volumes, 2,500 pages, 2,500 full-page plates. Bound in three-quarters morocco. Handsomely illustrated with gold stamped titles and edges.

This work contains the essence of the most successful methods yet devised of getting a practical knowledge of electricity at home. Storage Batteries—The Telephone—Telegraphy—Trolley Car—Electric Light—Wiring for Light and Power—Burglar Alarms—Door Bells—and hundreds of other daily uses of electricity are explained in a simple manner within the understanding of any intelligent man. All rules and formulae are stated simply and illustrated with diagrams and practical examples. The books have been compiled by practical men for the use of practical men, and contain information that is found only in the private note book of the Superintendent or Foreman.

**LESS THAN HALF PRICE**  
Special 30 Day Price, \$14.80. Regular List Price, \$30.00

**FREE FOR INSPECTION**  
These books are compiled from the best instruction papers in the Electrical Engineering course of the American School of Correspondence, and to bring our home study course widely before people interested in electricity we have made a special price of \$14.80 for 30 days, payable \$2.00 within 5 days and \$2.00 per month until the special price of \$14.80 is paid—books sent express prepaid. We employ no agents to annoy you, but depend entirely upon the merit of the books to sell themselves.

**Brief List of Contents:** Elements of Electricity—The Electric Current—Electrical Measurements—Electric Wiring—The Electric Telegraph—Wireless Telegraphy—The Telephone—Light and Power—Electric Welding—Direct Current Dynamos—Types of Dynamos—Electric Machinery—Direct Current Motors—Electric Motors—Storage Batteries—Electric Lighting—Electric Railways—Management of Dynamos—Electric Machinery—Power Stations—A Modern Central Station Design—The Alternator—The Transformer—Switchboards and Station Appliances—Power Transmission—Mercury Vapor Converters—Telephone Instruments—Telephone Lines—Telephone Exchanges—Common Battery Systems—Telephone Systems—Automatic Telephone—Wireless Telegraphy—Review Questions.

**AMERICAN SCHOOL OF CORRESPONDENCE**  
CHICAGO

Name.....  
Address.....

**COUPON**  
Please send me the Cyclopedia of Applied Electricity for 30 days free examination. I will send \$2 within 5 days and \$2 a month until \$14.80 is paid, otherwise I will notify you to send for the books.

car. Secured to the frame is a steel bracket carrying two hardened steel rollers, between which the springs of the shock absorber move up and down as the car springs play. There is but little resistance to the downward movement of the car springs or to the first part of the upward movement; but as the spring begins to exceed normal limits of motion on the rebound, the shock absorber springs are drawn down between the rollers, and the force required to compress them checks the upward movement. The higher the car body rises the greater is the resistance offered, as the springs are furthest apart at the top, and more force is required to compress them.

In the Hotchkiss anti-jolt device (Fig. 6), the resistance offered by a small aperture to the passage of a liquid is made to check the rebound of the car springs. A circular chamber (Fig. 7) accurately finished interiorly, is filled with glycerine and fitted with a radial piston on a steel shaft, the piston being packed with leather to make it tight in the chamber. The shaft passes out through a stuffing-box in the cover, which is fitted on with a ground joint to prevent leakage. In the chamber there is also a metal partition extending from the inner circumference to the shaft, where another packing of leather makes a tight joint. In the partition is a small opening controlled by a needle valve, adjustable from the outside. Another passage, much larger, runs through the chamber casting from one side of the partition to the other at the top, forming a bypass, and in it is a check valve which permits the flow of liquid in one direction only.

An arm is attached to the outer end of




Fig. 7.—Hotchkiss Shock Absorber With Cover Removed and Section Broken Away to Show Check-valve and By-Pass.

the shaft carrying the radial piston, and to this arm is pivoted a link; the chamber with its piston is bolted to the car spring, while the upper end of the link is attached to the frame above. Any movement of the spring is of course communicated to the link and thence to the arm, the shaft, and the piston. In order to move the piston, however, the glycerine in the case must be displaced, as it is confined in the two spaces formed by the piston and the partition, the only communication being through the small valve-controlled hole and the larger bypass. On the downward movement of the car body the glycerine is permitted to pass freely through the check valve in the bypass, and the opening is of such size that there is little or no retarding effect. On the upward movement, however, the check valve closes, and there is left only the small hole in the partition. Through this the glycerine is forced comparatively slowly, and the speed of the spring rebound is retarded to conform to the rate at which the glycerine can pass the orifice. Obviously, the smaller the hole the slower the movement; and as the opening can be regulated by the needle valve referred to, the speed of action permitted can be adjusted to a nicety.

If desired, the chamber can be attached to the car frame and the link to the spring; the attachments furnished permit either arrangement, and the device works equally well either way. The glycerine acts as a lubricant and is non-freezing.

Spring action and friction are com-

## The Varnish that lasts longest

Made by Murphy Varnish Company.

### The Schildback Divided Windshield

Properly built to stand the very roughest usage, it will not rattle, jar loose and fall to pieces. The material—brass, mahogany and plate glass—of the best that money will buy, and the workmanship cannot be excelled. Descriptive booklet for the asking. Limousine Carriage Mfg. Co. 2510 Michigan Ave., Chicago, Ill.

**RADIUM AND THE RADIO-ACTIVE** Substances. No better or clearer scientific account has been published than that contained in SCIENTIFIC AMERICAN SUPPLEMENT 1429. The paper presents all that is at present known about radium and the radio-active substances. Price 10 cents, by mail. Munz & Co., 301 Broadway, New York City and all newsdealers.

### Convert Your Bicycle into a Motorcycle

at small cost by attaching the self-starting Erie 3 H. P. Power Unit. This includes all parts. Anyone can easily make a powerful motorcycle. Speed 25 miles an hour. 3 H. P. Motorcycles. Send stamp for either on slip. MOTORCYCLE EQUIPMENT CO., 5 Lake, Hammondport, N. Y.

### \$650 A. B. C. Motor Surrey

This is the lowest priced good machine in America. It has fewer working parts than any other car—that means less repairs. The A. B. C. Motor Surrey is absolutely the most durable, economical and safest motor car made.

#### At Home On Any Road

This motor speeds up to 25 miles an hour. It will climb any hill and glide along the roughest road without the slightest jolt. Other models built for 2 and 3 passengers. Has a dignified stylish appearance. Write to-day for handsome illustrated catalogue.

A. B. C. MOTOR VEHICLE CO. 1812 Locust Street, St. Louis, Mo.


### "Porox" Ignitor Storage BATTERIES

High Capacity. Light Weight. Proved as the best for both ignition and light. No loss of current. It stores and returns the power to your machine. You can see and examine the interior without exposure and discharging, because it is made up in transparent celluloid jars. No danger of breakage like hard rubber. Plates and jars are guaranteed for one year. Send for catalog. Albert Muller, 205 West 41st St., New York

**HOW TO MAKE AN ELECTRICAL** Furnace for Amateur's Use.—The utilization of 110 volt electric circuits for small furnace work. By N. Monroe Hopkins. This valuable article is accompanied by detailed working drawings on a large scale, and the furnace can be made by any amateur who is versed in the use of tools. This article is contained in SCIENTIFIC AMERICAN SUPPLEMENT, No. 1429. Price 10 cents. For sale by MUNZ & CO., 301 Broadway, New York City, or by any bookseller or newsdealer.

### Regal Marine Engines

Guaranteed steady and reliable under all weather conditions. Start and run on kerosene. 4 cycle. Jump spark ignition. Auto type. Built to run and they do it. Made in two types: 3 h. p. single cylinder to 20 h. p. four cylinder, high speed motor boat engines. Also in 2 h. p. single cylinder to 40 h. p. four cylinder, slow speed, heavy duty working engines. Send for catalog 30—FREE. REGAL GASOLINE ENGINE CO., 82 W. Pearl Street, Coldwater, Mich.



## The YOUTH'S COMPANION

THE BEST PAPER FOR FAMILY READING.

The 52 issues of 1908 will give for \$1.75 as much good reading as twenty 400-page books of fiction, travel, biography, etc., costing ordinarily \$1.50 each. The contents will include



It Comes Every Week the Year Round.

**250 Good Stories**  
Serial Stories and Stories of Character and Heroism.

**350 Articles**  
Sketches and Reminiscences by Distinguished Men and Women.

**1000 Up-To-Date Notes**  
on Current Events, Discoveries and Inventions in Nature and Science.

**2000 One-Minute Stories**  
Bits of Humor and Miscellany, the Weekly Health Article, Timely Editorials, the Children's Page, etc.

### EVERY NEW SUBSCRIBER

Who cuts out and sends this slip (or mentions this publication) at once with \$1.75 for The Youth's Companion for 1908 will receive

**FREE**

All the issues of The Companion for the remaining weeks of 1907. The Thanksgiving, Christmas and New Year's Holiday Numbers. The Companion's 4-Leaf Hanging Calendar for 1908, in full color. Then The Companion for the 52 weeks of 1908.

Send for Free Sample Copies and Announcement for 1908.

THE YOUTH'S COMPANION, BOSTON, MASS.

bined in the Baldwin spring recoil check, made by the Baldwin Chain and Manufacturing Company, of Worcester, Mass. This is shown in Figs. 8 and 9. From the body or frame of the car is suspended a cylinder, A, open end down, by two rods depending from a pivoted yoke, H, and carrying compound springs, F, G. In the middle cylinder is a plunger




Fig. 8.—The Baldwin Combined Spring and Friction Recoil Check.

B, divided vertically into halves and faced with cork on its bearing surfaces. Rod E has a slotted head engaging the inner ends of two small toggle arms whose outer ends bear on the two halves of the plunger, so that a downward pull on the rod tends to force apart the two halves and bring them into more or less forcible contact with the cylinder walls, while the upward movement of the rod withdraws the plunger from contact with the cylinder walls. The action of the toggles is modified by small helical springs, so that a rapid, sudden pull of the rod will cause the plunger to exert a greater pressure against the cylinder walls and a consequent slower movement. Within each of the smaller cylin-




Fig. 9.—View Showing the Combined Spring Recoil and Friction Check Partly in Section.

ders are a pair of coiled springs, F and G, one of these springs being lighter than the other. With an up-and-down movement of about 4 inches, the rebound is checked by these springs. Should, however, a much greater movement of the frame with respect to the axle occur, the piston, B, will travel upward in the cylinder, A, while the frame is approaching the axle, but will immediately lock, and then travel slowly downward as soon as the rebound begins.



# WINCHESTER



## Repeating and Single-Shot Rifles

shoot straight and strong  
They are made in all desirable calibers and for accuracy, reliability and finish represent the highest development in gunmaking. Shoot a Winchester once and you'll shoot one always.

Winchester Rifles and Winchester Cartridges are made for each other.

WINCHESTER REPEATING ARMS CO.  
NEW HAVEN, CONN.



## Little Giant

Reliable, Reversible, Two Cycle, Two and Three Port. Guaranteed for one year. Simple and easy to operate. Our Free Catalog A3 is worth your having. Send 10 cents in stamps for our book entitled "Ignition, Vaporization, Installation and Operation of a Gasoline Motor."

UNITED MFG. CO., - - Detroit, Mich.

## FIRE PROTECTION SMALL COST

If you want the surest fire protection for your factory, warehouse, place of business, home, etc., and at lowest cost it will pay you to write us for full particulars. Our system is in use by leading business houses all over the country. May we explain further?

FAIR MFG. CO., 773 1/2 Fifth St., Racine, Wis.



## THE "LEADER."

1 1/2 H. P. Gasoline Auto-Marine Engine

Built like a watch. Beautifully Finished. Accurately Constructed. Light, Strong, Reliable, and Noiseless in operation. Suitable for launches from 15 to 18 feet in length. Price complete, \$75 net, no discount. Thoroughly guaranteed. Perfect Speed Control. Complete descriptive Catalog upon application. Manufactured by

CLAUDE SINTZ,  
292 S. Front St., Grand Rapids, Mich.


## Chemical Analyses

Industrial products examined and working formulae provided, processes improved, counsel and expert evidence. Assay of ores, alloys, water and fuels, etc., etc. Inventors assisted; instruction. Established 1885. Monadnock Laboratory, Chicago.



Anyone sending a sketch and description may quickly ascertain our opinion free whether an invention is probably patentable. Communications strictly confidential. HANDBOOK on Patents sent free. Oldest agency for securing patents. Patents taken through Munn & Co. receive special notice, without charge, in the

**Scientific American.**  
A handsomely illustrated weekly. Largest circulation of any scientific journal. Terms, \$3 a year; four months, \$1. Sold by all newsdealers.  
**MUNN & Co., 361 Broadway, New York**  
Branch Office, 625 F St., Washington, D. C.



## Foot and Power "Star" Lathes

Built for Accurate Service  
We have put a "Quality" of material, workmanship, efficiency and accuracy into "Star" Lathes that has not been excelled.  
Can furnish draw-in chucks, taper, milling and gear-cutting attachments, metric lead screw, etc. Send for Catalog B. It also describes bench lathes, speed lathes, wood lathes and 12 in., 14 in. and 16 in. heavy engine lathes.

THE SENECA FALLS MFG. CO.  
656 Water St., Seneca Falls, N. Y., U. S. A. 13157

Last month we proved to many people that they could make \$3000.00 clear profits each year. We are ready to prove that

## \$3000.00 Can be Made

This year, next year, and the years after Cleaning houses by our patented machinery, by energetic, competent men. Over 300 operators in as many towns in the United States.

We make the most efficient stationary systems for Residences - Hotels - Office Buildings, etc.

Central Booth Machinery Bldg., Jamestown Exposition.

GENL. COMPRESSED AIR AND VACUUM MACHINERY CO.  
4479 B Olive Street, ST. LOUIS, MO.



## LET US BE YOUR FACTORY

We estimate on anything you want made to order. STAMPINGS, MODELS, EXPERT WORK  
We publish "The Silent Partner," a brainy little magazine, full of good thoughts. Sample free. Write us. THE GLOBE MACHINE AND STAMPING CO.  
970 Hamilton St., Cleveland, O.

ICE MACHINES Corlies Engines, Brewers' and Butlers' Machinery. THE VILBER MFG. CO., 800 Clinton St., Milwaukee, Wis.

MODELS & EXPERIMENTAL WORK. Inventions developed. Special Machinery. E. V. BAILLARD, 24 Frankfort Street, New York.

RUBBER Expert Manufacturers Fine Jobbing Work PARKER, STEARNS & CO., 225-229 South Street, New York

MODELS & EXPERIMENTAL WORK. INVENTIONS PERFECTED. UNION MODEL WORKS 191-201 E. 12th St., CHICAGO

MODELS & EXPERIMENTAL MACHINERY. Gears, Dies, Tools. Novelties manufactured. Fine, Accurate Work a Specialty. M. P. SCHILL, 1729 Union Street, San Francisco.

## HOW TO MAKE ELECTRICAL BOOKS


Full Directions and Working Drawings  
25. An Ammeter. 26. A Thermometer. 27. An Electric Furnace. 28. Motor Rotation. 29. A Hand Feed Air Lamp. 30. An Electric Soldering Iron. 31. A Jump Spark Coil. 32. A Small Electric Heater. 33. A Rheostat.  
RUBIER PUB. CO., Dept. 5, Lynn, Mass.

Do Your Own Printing  
\$5 press prints cards, labels, etc. Circular, book, newspaper press \$18. Money saver, maker. All easy. Rules sent. Write factory for press catalog, type, paper, etc. THE RUBIER CO., Meriden, Conn.

HOME MADE DYNAMOS. - SCIENTIFIC AMERICAN SUPPLEMENTS 181 and 600 contain excellent articles with full drawings. Price 10 cents each, by mail. Munn & Company, 361 Broadway, New York City, and all newsdealers.

CEMENT BOOKS. How to Use Portland Cement. How to Cement Sidewalk Construction, etc.; Reinforced Concrete Construction, etc.; How to Construct Bank Building Construction, etc. Best postpaid. CEMENT AND ENGINEERING NEWS, Chicago, Ill.

We Supply Dies, Pressed Steel Products, Sheet Metal Stampings, Tools, Models, Novelties, Patterns, Special Machinery. Quick deliveries, attractive prices. Chicago Model Supply Co., 68 Sheffield Ave., Chicago, Ill.



Out December 7, 1907

## THE SPECIAL Navy Number

of the  
**SCIENTIFIC AMERICAN**

36 Pages in Handsome Cover in Colors. Fully Illustrated

Price 10 Cents

TEN YEARS AGO the American Navy, which won imperishable laurels under Dewey, Sampson and Schley, had 3 first-class battleships and 2 armored cruisers. To-day it has, in commission or near completion, 22 battleships and 10 armored cruisers from which to select a fleet to visit the Pacific. That is not all: Ships, guns, armor protection and gunnery are alike superior to the best of ten years ago. The special number of the SCIENTIFIC AMERICAN will tell in full of this growth during ten years' peace.

Among the contents will be a graphically illustrated article comparing the powers of the various navies of the world; an illustration of every type of vessel from battleship to submarine; various powerful guns and their intricate mechanism; the manufacture and testing of armor plates; the problems of warship design and construction, with a special article on the towing tank where models are tested; the warfare of the future as affected by modern vessels; and a table showing the size, speed, armor and armament of every boat in our navy, down to torpedo boats.

The number will be a double one—36 pages, lavishly illustrated, in a colored cover—and charged at the usual rate of 10 cents. It will be advisable to order a copy early.

ORDER FROM YOUR NEWSDEALER OR FROM  
**MUNN & CO., 361 Broadway, New York City**



"Tanks with a Reputation."

## CALDWELL Tanks and Towers

provide abundance of water for all purposes in Mills, Factories, Towns and Country Homes. Reliable and permanent service assured. Ample pressure, as well, for fire protection.

Our building plans, in connection with selected high-grade material, insure great tank durability and enormous water supply.

Endorsed by eminent architects, engineers, and thousands of satisfied customers.


25 YEARS' EXPERIENCE

We erect anywhere in United States, Canada and Mexico. For catalogue, full information and references name your address Dept. 5 F.

W. E. CALDWELL CO., Louisville, Ky.

Tanks (Steel-Wood) Towers

Wind Mills—Pumps—Gas Engines



## Fresh Air is HEALTH

## National Ventilators

Fit Any Window Cost Nothing to Maintain

Work automatically day and night, producing a continual change of air. Prevent drafts, keep out dirt, rain and snow.

Send for Details and Price List. Agents Wanted.

NATIONAL VENTILATOR & MFG. CO.  
68-70 W. Monroe St., Chicago



## Make Big Profits selling the famous Standard Hydro-Carbon Light

for homes, stores, halls, churches, etc., etc. Better than electricity, cheaper than kerosene, no smoke or odor, absolutely safe and guaranteed. Can be installed by any handy man. Exclusive territory to agents with liberal terms. Our "Sales System" aids you in selling. Write today for terms. Standard-Gillett Light Co.  
900 N. Halsted St., Chicago

## A Home-Made 100-Mile Wireless Telegraph Set

Read SCIENTIFIC AMERICAN SUPPLEMENT 100 for a thorough, clear description, by A. Frederick Collins, of the construction of a 100-mile wireless telegraph outfit. Numerous, adequate diagrams accompany the text. Price 10 cents by mail. Order from your newsdealer or from

MUNN & CO., 361 Broadway, New York

## Automobile Running Gears

WITH PRESSED STEEL ON ANGLE IRON FRAMES

Also all styles of bodies. Write for catalogue at once, mentioning this paper.

BORHEIM AUTO CO., 2109 North Ninth Street, St. Louis, Mo.



## FOR AUTOMOBILE

SAMPLES FREE WRITE US

NEVER SETTLES HARD IN BOTTOM OF CAN

The Harvey Chemical Co.  
LAFAYETTE, IND.

## ALUMONITE

TRADE MARK REGISTERED

## The Wonderful New ALUMINUM SOLDER

which we absolutely guarantee to solder

ALUMINUM TO ALUMINUM or ALUMINUM TO OTHER METALS

It Merits Investigation

ALUMINUM SOLDER AND REFINING CO., Oswego, N. Y.

See our Exhibit No. 547, Automobile Show, Madison Square Garden, New York City.





## Rubber Pump Valves

For Cold and Hot Water, Oils, Acids, High Pressure Mine Service and for every pumping requirement.

Mechanical Rubber Goods of every description of unsurpassed qualities, including BELTING, HOSE PACKINGS, Gaskets, Mats and Matting, Tubings, Springs, Interlocking Tiling, Emery Wheels and MOULDED and CUT SPECI-LTIES for any mechanical and commercial device.

**NEW YORK BELTING & PACKING COMPANY, Ltd.**  
91 & 93 Chambers Street, New York

**Scales** All varieties at lowest prices. Best Railroad Truck and Wagon or Stock Scales made. Also 500 useful articles, including Saws, Sawing Machines, Bicycles, Tools, etc. Saye Money. Lists Free. CHICAGO SCALE CO., Chicago, Ill.

**TRY IT YOURSELF FOR 10 DAYS WITHOUT DEPOSIT**  
If not satisfactory, return it and no question asked. **Dans' Improved Tip Dupliator** is the result of 25 years experience, and is used and endorsed by thousands of custom houses and individuals. 100 copies from pen-written and 50 copies from type-written original—clear, clean, perfect. Complete Dupliator, made up size (prints 8 1/2 x 11 in.), price, \$7.50.  
**Felix U. Dans Dupliator Co.,**  
Dans Building, 115 John Street, New York

**Bausch, Lomb, Saegmuller Co.**  
Manufacturers of  
High grade Astronomical, Engineering, and other Instruments of Precision. Send for catalog.  
**BAUSCH, LOMB, SAEGMULLER CO.**  
Rochester, N. Y.

## Perhaps You Want To Know

something about a particular Tool, or Tools. This 960 page, cloth-bound **Tool Catalogue No. 24** tells you all you need to know about every tool made with illustrations of each. It will be sent to your address post-paid for \$1.00 which you will get back from the first \$10.00 purchase you make from us. Write for it to-day.  
**MONTGOMERY & CO.**  
108 Fulton St., N. Y. City

**IT PAYS BIG To amuse the Public With Motion Pictures**  
NO EXPERIENCE NECESSARY on our instruction Book and "Business Guide" tells all. We furnish Complete Outfits with Big Advertising Posters, etc. Humorous dramas, variety of fun, travel, history, religion, temperance work and songs illustrated. One man can do it. **Amusement Opportunity** in any locality for a man with a little money to show in churches, school houses, lodge halls, theatres, etc. Big profits each entertainment. Others do it, why not you? It's easy; write to us and we'll tell you how. Catalogue free.  
**AMUSEMENT SUPPLY CO., 607 Chemical Bank Bldg., CHICAGO.**

**YOUR BATTERY WILL LAST LONGER**  
If you keep it charged as fast as it gives off current. The **Apple Battery Charger** is a dynamo right on your car, but or gas engine that charges the battery at full to current in hours from drive. Write to-day for full information about the Apple Ignition System. Specify this outfit on your automobile, motor boat or stationary engine.  
**The Dayton Electrical Mfg. Co., 38 St. Clair St., Dayton, Ohio.**  
"Floating the Battery on the Line."

**LUFKIN TAPES AND RULES**  
ARE THE BEST.  
For sale everywhere. Send for Catalog No. 16.  
**LUFKIN RULE CO.**  
Saginaw, Mich., U. S. A.  
New York and London.

**UNIVERSITY SHOE**  
(Trade-Mark)  
Heaviest city grain leather—tan colored. Watertight construction. Comfortable and heavy indestructible. Send for pamphlet.  
**J. P. WADELL**  
1910-1912 Market St., Philadelphia



**What Does This Mean?**  
Simply that this appreciative community is enjoying the world's greatest singers and instrumentalists.

## VICTOR

**The Fireside Theatre**

brings to each family exactly the music that it wants, when it wants it; the veritable voice, the actual performance. And all in the comfort and privacy of home.  
Send for list of new records.



**VICTOR TALKING MACHINE CO.**  
Camden, - N. J.

Berliner Gramophone Co., of Montreal, Canadian Distributors.

The new Victor records for each month are for sale on the 28th of the preceding month—the Simultaneous Opening Day throughout America.



## The ONLY MACHINE

The only machine ever invented which will add, multiply and divide by automatic, instantly responsive keys. **No lever to operate.**

The only machine which can prove its claims for being the most rapid adding or calculating machine.

The only machine which can show a record (16 yrs. 8 mo. 13 das.) for durability to exceed 8 years **without a single repair.**

The only machine which has been used on all additions, multiplications and divisions found in bookkeeping, bill extending, cost keeping and pay-roll departments of practically every line of business and proven successful in every place.

The only machine ever invented which will add all the columns at one time by the simple touching of keys and nothing more. Write for pamphlet and special trial offer. Comptometer sent, express prepaid, on trial to responsible parties in the U. S. or Canada.

Felt & Tarrant Mfg. Co.,

W. Wabansia and Paulina Sts., Chicago, Ill.

## Great Strength!

Continual use does not affect the simple yet strong mechanism of

**NEW YORK STANDARD "CHRONOGRAPHS" Or STOP-WATCHES**

Many marvel at how they can be sold at the price, yet they are the only ones made anywhere in the world that are **Fully Guaranteed.**

Ask to See Them at Your Jeweler's

New York Standard Watch Co., 401 Communipaw Ave., Jersey City, N. J.



**WRITE FOR FREE BOOKLET**  
SHOWING OTHER STYLES  
\$7.50  
In Silver Case



## YOUR OWN ELECTRIC LIGHT PLANT.

We have Standard Complete Outfits for any size place, summer homes, residences, launches, yachts, etc. Every detail included; very best material money can buy; thoroughly practical; so simple no electrician required. **Light all the time** with our Storage Battery Outfits. Gas, kerosene, or steam engines used give plenty of power for pumping water, sawing wood, refrigeration, etc.  
For latest printed matter covering over a hundred outfits address  
**ELECTRIC DEPARTMENT**

**RICHARDSON ENGINEERING CO. HARTFORD, CONN.**

## Expansion Bolts



CATALOG AND SAMPLES ON REQUEST  
Star Expansion Bolt Co., Trank Ave. & 2d St., Bayonne, N. J.

## COLD GALVANIZING. AMERICAN PROCESS. NO ROYALTIES. SAMPLES AND INFORMATION ON APPLICATION.



**NICKEL**  
Electro-Plating Apparatus and Material.  
**Hanson & VanWinkle Co.,**  
Newark, N. J.  
28 & 30 S. Canal St. CHICAGO.




## HARDERFOLD HYGIENIC UNDERWEAR

**Inter-Air-Space System**  
is two-fold throughout, affording protection against the vicissitudes of our variable climate to Invalids, Athletes, Professionals Men, Merchants, Accountants, and all occupations in life, indoor or out.  
Over 1100 Physicians have united in testifying to the sanitary excellence of the HARDERFOLD system of underclothing.  
**HARDERFOLD FABRIC CO.**  
163 River Street, Troy, N. Y.  
Send for Catalogue

## Automobile Accidents

Nearly always happen at night and can be traced to poor, unreliable lights.  
Safeguard yourself and car by equipping with an

## "AUTOGAS" Tank




## Stored-Up Night Sunshine

ready to turn on and use in any kind of Gas Lamps.  
Absolutely reliable. Write us for catalog and nearest distributor.

**EVERY PORTABLE LIGHTING CO.**  
14 Martin St. 51 West 63rd St.  
MILWAUKEE, WIS. NEW YORK CITY

## 'Ever-Ready' Safety Razor \$1.00



**12 BLADES With Every Set**

**First and Original Motor Buggy \$250 "SUCCESS" AUTOMOBILE**  
Practical, durable, economical and absolutely safe. A light, strong, steel-tired Auto-Buggy. Suitable for city or country use. Speed from 4 to 40 miles an hour. Our 1908 Model has an extra powerful engine, patent ball-bearing wheels; price, \$275. Also 10 h. p., \$400. Rubber Tires, \$25.00 extra. Write for descriptive literature. Address  
**SUCCESS AUTO-BUGGY MFG. CO., Inc., St. Louis, Mo.**

## WELL DRILLING Machines

Over 70 sizes and styles, for drilling either deep or shallow wells in any kind of soil or rock. Mounted on wheels or on skids. With engine or horse power. Strong, simple and durable. Any mechanic can operate them easily. Send for catalog.  
**WILLIAMS BROS., Ithaca, N. Y.**

**HELMET OIL LUBRICATES FOR ANYTHING**  
15-21 S. CLINTON ST. CHICAGO, ILL.



# Twenty=Four Million Dollars

Ordinary Life Insurance issued in

## THE FIRST TWELVE WEEKS

Shows the Splendid Welcome the Public has given

## THE NEW LOW COST POLICY

of

# The PRUDENTIAL

### SOME REASONS STATED FOR SELECTING THIS POLICY:

"I Believe it is the Best Life Insurance Issued."

"You Prudential People have Bested Everything in Life Insurance."

"My Prudential Policy is the Cheapest and Best Insurance I Have."

"The Prudential's New Policy Gives Me More for My Money."

"Policy Eliminates All Elements of Uncertainty."

"New Prudential Policy Beats Any Policy I have Examined."

"Rates Much Lower Than Charged by Other Companies."

"Guarantees Are Better Than Estimates. I Recommend The Prudential."

"Gives the Public What They Really Demand."

"Keeping the Dividends in My Pocket Looks Good to Me."

"I Buy The Prudential Policy Because Everything is Guaranteed."

"You have Certainly Eliminated Competition."


"We have Been Looking for Just This Policy."

"The Rates Alone, Backed by the Name 'Prudential,' Catch the Public Favor."

### THIS IS A COMMON SENSE POLICY

The Rates on the New Policy are the Lowest, Consistent with Liberality and Safety, offered by any Company of Corresponding Size, Importance, and Responsibility in the World

**Definite Cost,  
Definite Benefits,  
Definite Returns.**



**Every Feature  
Absolutely Guaranteed.**

Send in your age, nearest birthday, and we will give you full particulars.  
The Low Rates will Surprise You.  
Address Dept. 121.

**The Prudential  
Insurance Company of America**


Incorporated as a Stock Company by the State of New Jersey

**JOHN F. DRYDEN**  
President

**Home Office  
NEWARK, N. J.**

**DO YOU WANT TO MAKE MONEY?**

Splendid Opportunities in Selling this Popular New Ordinary Policy.  
Write direct to us to-day.  
Address Dept. 121



## 1908 Seven-Passenger

Peerless car illustrates true progress. Good points have not been discarded because they are old, nor other good points refused because they are new.

Peerless principles of design and construction and high standard of materials have been maintained.

The 1908 model has a splendid parent in the 1907 car, whose tested and proven excellencies it has retained. Added to these are higher power, larger wheels, longer wheel base and double ignition system.

The Peerless principles of design were already established, but a few changes in the use of these principles have given increased efficiency.

*Write to-day for New Illustrated Catalogue "P" which fully describes all the Peerless Models*

**PEERLESS MOTOR CAR CO., 2447 Oakdale Street, Cleveland, O.**

Member A.L.A.M.

*Peerless*  
All That The Name Implies